

**NEW**

## UM-ZL28

ϕ28 | 110V | 220/240V



**NEW**

## UM-ZF100

110V | 220/240V

- Anti vibration rubber isolator for easy removal and maintenance of head/board
- UM-ZF100 is for external vibration, ideal for construction of walls, pillers, etc.

### UM Specifications

| model | vib.head dia. 【D】x shaft length 【A】 (mm) | vib.board size (mm) | amplitude (mm) | vibration Hz (V.P.M.) | power (W) (single phase) | weight(kg) |
|---|---|---|---|---|---|---|
| UM-Z28 | 28 x 785 | – | 1.4 | 200-258 (12,000-15,500) | 280 | 5.3 |
| UM-ZF100 | – | 100(W) x 78(T) | – | 166-200 (10,000-12,000) | | 5.2 |

# GS Concrete Vibrator

■ Coupling type



● Mikasa original



● Pin type



● Two claws type




### GS Specifications

| model | vib.head dia. x length (mm) | flexible shaft dia. (mm) | rubber casting dia. (mm) | rubber hose (m) | amplitude (mm) | vibration Hz (V.P.M.) | shaft set weight 4m / 6m (kg) |
|---|---|---|---|---|---|---|---|
| GS-28 | 28 x 477 | 10 | 30 | 4 or 6 | 1.4 | 150-208 (9,000-12,500) | 10.6 / 14.7 |
| GS-32 | 32 x 520 | | | | 1.8 | | 11.2 / 15.1 |
| GS-38 | 38 x 480 | | | | | | 11.9 / 15.7 |
| GS-45 | 45 x 494 | | | | 2.0 | | 13.3 / 17.4 |
| GS-60 | 60 x 479 | 13 | 32 | 6 | 2.4 | | 22.3 |