
Satisfy Professional's Needs

Cordless High Pressure Washer
HW001G

Various options



Cyclone jet nozzle set

A spiral jet is ejected. Suitable for removing stubborn dirt.

Cyclone guard set

Reduces splash back when cleaning corners with the cyclone jet nozzle.



Variospray nozzle set

Variospray nozzle ext. set

Jet pressure can be adjusted by rotating the nozzle.



Variospray lance set

Jet pressure can be adjusted by rotating the nozzle



Variable nozzle set

Jet width can be adjusted from 0° to 25° by rotating the front end of the nozzle.



Foam nozzle set

Detergent can be sprayed as foam.



Wash brush set

A nozzle equipped with a brush. Useful for washing out dirt while scrubbing with brush.



Rotating brush set

Three brushes inside rotate slowly when ejecting the jet. Suitable for cleaning light dirt on an exterior wall, car body, bath tub, etc.



Under body spray lance set

An extra long spray lance with angled nozzle. Best for cleaning hard-to-reach areas such as car under body and roof gutter.

Extension pipe set

Pipes to extend the length of the trigger gun. Three different lengths are available by changing the number of the pipes to be used.

Accessory joint set

A joint to connect with a nozzle from other model.



Absorption connector G3/4

With filter

Pipe cleaning hose

10m, 15m

For cleaning and unclogging plumbing and downpipes.



Trigger gun set

High pressure extension hose

5m, 8m, 10m

Total length up to 20m

Extension hose to connect the high pressure washer body with the trigger gun.

High pressure hose

Length: 5m

Twist prevention joint set

Prevents the high-pressure hose from being twisted.

One touch joint set

For commercial hose connection

Hose assembly set

Length: 3m

A hose assembly to connect a faucet to the product, or the strainer assembly to the product.

Strainer assembly set

A strainer assembly to supply water from a tank or reservoir. Use the hose assembly to connect to the product.

Self-suction hose set

Replace the water hose with this set to supply water from a tank or reservoir.

Charging Time

	Fast Charging DC40RA	DC40RC
BL4020 2.0Ah	**22** min	**30** min
BL4025 2.5Ah	**28** min	**38** min
BL4040/F 4.0Ah	**45** min	**67** min
*1**BL4050F** 5.0Ah	**50** min	**85** min
*1**BL4080F** 8.0Ah	**76** min	**170** min

*1 Recommended battery

Cordless High Pressure Washer
HW001G

Electronic 3-Speed

Anti-restart function

Standard Equipment :

Trigger gun set, High pressure hose 5 m, Strainer assembly set, Absorption connector G3/4, Cleaner pin, Variospray nozzle set*1, Extension*1, Variospray lance set*1, Cyclone jet nozzle set*1, Variable nozzle set*1, Foam nozzle set*1, Wash brush set (Vertical form)*1, Hose assembly set*1, Hose clamp*1, Battery, Charger

*1 Country specific

Max. Flow Rate	*7.0 L/min*
Regular Flow Rate	*Mode 1/ 2/ 3: 3.0/ 4.2 / 5.5 L/min*
Max Permissible Pressure	*11.5 MPa*
Regular Pressure	*Mode 1/ 2/ 3: 3.0/ 5.5 / 8.5 MPa*
Max Feed Temperature	*40 °C*
Max Suction Height	*1 m*
Max Run Time	*w/ BL4050F x2:*
	Mode 1/ 2/ 3: 60/ 30/ 18 min
Hose Length	*5 m*
Noise level	*84 dB(A)*
Dimensions	*334 x 383 x 520mm*
(L x W x H)	*(13-1/2 x 15-1/8 x 20-1/2")*
Net weight	*10.3 - 13.4 kg (22.7 - 29.5 lbs.)*

The weight may differ depending on the attachment(s), including the battery cartridge.
The lightest and heaviest combination, according are shown in the table.
Items of standard equipment and specifications may vary by country or area.



Makita Corporation
3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202308

XGT 40Vmax Li-ion



Two in parallel or one

Good mobility and transportability









Large diameter wheels
Equipped with ø140mm wheels, allowing for good mobility even on bumpy road surfaces.

BL MOTOR High power brushless motor

IPX5

rated for weather and water resistance



Telescopic handle
for easy transportation and storage







3 operation modes; operation mode can be selected to suit the contamination degree of the object to be cleaned.

Max permissible pressure 11.5 MPa

3 operation modes

Mode With Vario-spray nozzle	Mode 3	Mode 2	Mode 1
Regular pressure	8.5Mpa	5.5Mpa	3.0Mpa
Regular flow rate	5.5L/min	4.2L/min	3.0L/min
Continuous use*	18min	30min	60min
Examples of recommended work	Washing of building exterior, etc.	Washing of vehicles, farm equipment, etc.	Light washing work

* (approx) on fully charged batteries (with two BL4050F batteries)







Self-priming function
- Water can be supplied not only from faucet but also from water reservoirs, such as poly tanks, large buckets, using this function.
- Max suction height: 1m
- Minimal water level: 15mm
- No need to operate air drain valve



Accessory storage
Side section: Trigger gun
Rear section: High pressure hose, Foam nozzle, Lance



NEW Foam nozzle set
- New foam nozzle with improved foaming performance
- Bottle capacity: 350mL



