Air Tools

# Grinders

## Angle Grinders with governor control

### TAG-40FLH




### TAG-40FRH

• Ideal for removing burs on the material and smoothing welds







Female Type



Male Type



### TAG-40/50MR

Angle Grinders Specifications: Air pressure 6kg/cm²

| MODEL | Wheel Size (mm) | Wheel Max Speed (m/min) | Free Speed (rpm) | Net Weight (kg) | Overall Length (mm) | Maximum Air Cons (m³/min) | Air Inlet (PT) | Hose Size (in) | Horse Power |
|---|---|---|---|---|---|---|---|---|---|
| TAG-40MR | 100×6×16 | 4300 | 13000 | 1.4 | 195 | 1.00 | 1/4 | 3/8 | 0.9 |
| TAG-40FR | 100×6×16 | 4300 | 13000 | 1.4 | 195 | 1.00 | 1/4 | 3/8 | 0.9 |
| TAG-40FRH | 100×6×16 | 4300 | 13000 | 1.8 | 217.5 | 1.00 | 1/4 | 3/8 | 0.9 |
| TAG-40FLH | 100×6×16 | 4300 | 13000 | 1.6 | 213.5 | 1.00 | 1/4 | 3/8 | 0.9 |
| TAG-50MR | 125×6×22 | 4300 | 10300 | 1.4 | 195 | 1.00 | 1/4 | 3/8 | 0.9 |



Air Tools

# Grinders

## Angle Grinders/Straight Grinders with governor control

- Turn throttle type : 2"/4"/5"/7" model available
- Lever throttle type : 2"/4"/7"/9" model available
- Safety lock off throttle
- 360 free rotating exhaust for7"&9"

### TAG-700 Turn throttle type



### TAG-700QJL/900QJL Lever throttle type

• Ideal for heavy duty work such as smoothing welds and cutting material



• Ideal for various types of finishing tasks



### TSG-6L Lever throttle type Safety Lock-off throttle



### TSG-3F/5S/6S Turn throttle type

Angle Grinders / Straight Grinders Specifications: Air pressure 6kg/cm²

| MODEL | Wheel Size (mm) | Wheel Max Speed (m/min) | Free Speed (rpm) | Net Weight (kg) | Overall Length (mm) | Air Cons (m³/min) | Air Inlet (PT) | Hose Size (in) | Horse Power |
|---|---|---|---|---|---|---|---|---|---|
| TAG-700 | 180×8×22 | 4300 | 7500 | 3.1 | 274 | 0.8-1.0 | 3/8 | 1/2 | 1.3 |
| TAG-700QJL | 180×8×22 | 4800 | 8400 | 3.1 | 304 | 1.0-1.3 | 3/8 | 1/2 | 1.3 |
| TAG-900QJL | 230×8×22 | 4800 | 6500 | 3.4 | 304 | 0.7-1.0 | 3/8 | 1/2 | 1.3 |
| TSG-3F | 75×13×9.5 | 3000 | 12700 | 1.6 | 305 | 0.8 | 1/4 | 3/8 | 0.7 |
| TSG-5S | 125×19×12.7 | 3000 | 7600 | 3 | 400 | 1.1 | 3/8 | 1/2 | 1.4 |
| TSG-6S | 150×25×15.9 | 3000 | 6300 | 4.2 | 430 | 1.2 | 3/8 | 1/2 | 2.1 |
| TSG-6L | 150×25×15.9 | 3000 | 6000 | 4.2 | 430 | 1.2 | 3/8 | 1/2 | 2.1 |