Satisfy Professional's Needs

Cordless Fan CF003G 40Vmax / 18V / AC

XGT 40V max Li-ion

18V LITHIUM-ION

450 mm fan diameter









Compatible with
- **40Vmax XGT Li-Ion battery**
- **18V LXT Li-Ion battery**
- **AC (through AC adapter)**





AC



DC AC

XGT 40Vmax Li-ion

18V LITHIUM-ION



Front fan cover has been redesigned to supply air widely around the appliance therefore, this model is suited for air blowing or ventilation in a large place such as factory, warehouse, etc.

Max air flow volume
120
m^3/ min

Max air speed*
300
m/ min
*Measured at 1.0 m away from the appliance

Compatible with 40Vmax / 18V Li-Ion battery /AC



XGT battery and LXT battery can be installed simultaneously.

Stepless air flow volume setting



Dial-style air flow volume adjustment
(38 - 120m^3/min)

Can be mounted onto MAKPAC cart



Portability can be enhanced by mounting the appliance onto MAKPAC cart.

Manual angle adjustment of fan head



90° up/45° down with a locking knob

Automatic oscillation



Automatic oscillation angle adjustment:
60°, 90°, 120° left/right

Accessory case



Located on the front of the appliance for storing AC adapter, etc.



Foldable carrying handle



Three Off timer settings
1 hour, 2 hours, 4 hours

Continuous use (approx)

on a full battery charge [at Max air speed]

Battery	Without oscillation	With oscillation
BL1860B	90 min	85 min
BL4040	115 min	110 min
BL4080F	230 min	220 min

Charging Time

40Vmax Li-ion	Fast Charging DC40RA	DC40RC	18V LITHIUM-ION	Fast Charging DC18RC	DC18SD
BL4020 2.0Ah	**22** min	**30** min	**BL1815N** 1.5Ah	**15** min	**30** min
BL4025 2.5Ah	**28** min	**38** min	**BL1820B** 2.0Ah	**24** min	**45** min
BL4040 4.0Ah	**45** min	**67** min	**BL1830B** 3.0Ah	**22** min	**60** min
BL4050F 5.0Ah	**50** min	**85** min	**BL1840B** 4.0Ah	**36** min	**90** min
BL4080F 8.0Ah	**76** min	**170** min	**BL1850B** 5.0Ah	**45** min	**110** min
			BL1860B 6.0Ah	**55** min	**130** min

Cordless Fan

CF003G 40Vmax / 18V / AC

Variable Speed

Air velocity	*96-300 m/min*
Air flow	*38-120 m^3/min*
Fan diameter	*450 mm (17-3/4")*
Fan head angle	*Up: 90° / Down: 45°*
adjustment	*Left: 90° / Right: 90°*
Automatic oscillation	*Left: 60, 90, 120°*
	Right: 60, 90, 120°
Continuous use (min.)	*w/ BL4040: 115 / w/ BL4080F: 230 /*
w/o oscillation	*w/ BL1860B: 90*
Continuous use (min.)	*w/ BL4040: 110 / w/ BL4080F: 220 /*
w/ oscillation	*w/ BL1860B: 85*
Dimensions (L x W x H)	*w/o Battery: 312 x 633 x 770 mm*
	(12-1/4 x 25 x 30-1/4")
Net weight	*w/o Battery: 7.9 kg (17.4 lbs.)*

Standard Equipment : AC adaptor

not covered by EPTA-Procedure

Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202307