TAMPER & SAND RAMMER

TAMPER & SAND RAMMER

- Toku tampers are ideal for compacting backfill for trenches and compacting soil around foundations and other structures.



T-6



TF-1N TF-2N



TB-00G



TB-0G

MODEL	PISTON DIAMETER mm	PISTON STROKE mm	BLOW PER MIN. b.p.m.	NET WEIGHT kg	NET WEIGHT lb	OVERALL LENGTH mm	BUTT DIAMETER mm	AIR CONSUMPTION m³/min	AIR CONSUMPTION c.f.m.	HOSE SIZE mm	AIR INLET SIZE PT
TB-00G	18	50	1,600	1.7	3.7	280	51.5	0.25	8	12.7	3/8
TB-0G	22	65	1,000	2.7	5.9	395	54	0.3	9.6	12.7	3/8
TF-1N	25.4	100	800	6.8	15	1,070	67	0.7	22.4	12.7	1/2
TF-2N	32	125	700	9	19.8	1,105	75	0.85	27.2	12.7	1/2
T-6	38	140	600	18	40	1,240	146	1.1	38.9	12.7	1/2

AIR AUGER DRILL

AIR AUGER DRILL

- Water swivel attachment available to control dust and chips from drilling.



TAA-400

ACCESSORIES FOR AUGER DRILL



Water swivel




Air swivel complete



Wet shank



Dry shank



Spiral rod (Thread type)

Rod size 500, 1000, 1200, 1500mm



Bit (Thread type)
Gauge size
42, 48, 50, 55, 65mm




Rod connection

MODEL	PUT OUT mm	SPEED AT NO LOAD r.p.m	SPEED AT LOAD r.p.m	NET WEIGHT kg	NET WEIGHT lb	OVERALL LENGTH mm	AIR CONSUMPTION m³/min	AIR CONSUMPTION c.f.m.	HOSE SIZE mm	AIR INLET SIZE PT	START TYPE
TAA-400	4.0	1,200	600-950	10.2	22.5	275	3.4	119	19	3/4	LEVER TYPE

ROD

ROD



TAPER ROD FOR ROCK DRILL

TYPE	SHANK SIZE (HXR)	OVERALL LENGTH (L)
22HS	7/8×3-1/4	0.3, 0.4, 0.5, 0.6, 0.9, 1.0, 1.2, 1.5, 1.8, 2.0, 2.1, 2.4, 2.5, 2.7, 3.0, 3.5, 4.0, 4.5, 5.0, 5.5
22HL	7/8×4-1/4	

TAPER ROD FOR ROTARY HAMMER

TYPE	SHANK SIZE (H)	OVERALL LENGTH (L)
15T	R3/4•5/8H	0.25, 0.3, 0.4, 0.5, 0.6, 0.7, 0.8,0.9, 1.0,1.1
19T	R3/4•5/8H	0.3, 0.4, 0.5, 0.6, 0.7, 0.8, 0.9, 1.0

BIT

BIT




CARR BIT(TAPER ROD TYPE)

TYPE	G SIZE (mm)	AVAILABLE TAPER ROD
TC-22	28,30,32,34,36,38,40,42,44,46,48	22HS,22HL



CROSS BIT(TAPER ROD TYPE)

TYPE	G SIZE (mm)	AVAILABLE TAPER ROD
TX-22	28,30,32,34,36,38,40,42,44,46,48,50,55,60,65	22HS,22HL



Reaming Bit Set

REAMING BIT SET

TYPE	G SIZE (mm)	AVAILABLE TAPER ROD
TXW-	60,70,80,90,100,110,120,130,150	22HS,22HL

NOTE:FOR 130 AND 150 , SPECIAL ROD SHOULD BE USED.



Bit



Reaming Bit




Adapter

HOSE COUPLING

HOSE COUPLING





Coupling (Size)1/2",3/4",1",1-1/4",1-1/2",2"



Joint-nipple



Spud



Hose Nut



Stem



Hose Band