

NEW

UM-ZL28

ϕ28 | 110V | 220/240V



NEW

UM-ZF100

110V | 220/240V

- Anti vibration rubber isolator for easy removal and maintenance of head/board
- UM-ZF100 is for external vibration, ideal for construction of walls, pillers, etc.

UM Specifications

model	vib.head dia. 【D】x shaft length 【A】 (mm)	vib.board size (mm)	amplitude (mm)	vibration Hz (V.P.M.)	power (W) (single phase)	weight(kg)
UM-Z28	28 x 785	–	1.4	200-258 (12,000-15,500)	280	5.3
UM-ZF100	–	100(W) x 78(T)	–	166-200 (10,000-12,000)		5.2

GS Concrete Vibrator

■ Coupling type



● Mikasa original



● Pin type



● Two claws type



GS Specifications

model	vib.head dia. x length (mm)	flexible shaft dia. (mm)	rubber casting dia. (mm)	rubber hose (m)	amplitude (mm)	vibration Hz (V.P.M.)	shaft set weight 4m / 6m (kg)
GS-28	28 x 477	10	30	4 or 6	1.4	150-208 (9,000-12,500)	10.6 / 14.7
GS-32	32 x 520				1.8		11.2 / 15.1
GS-38	38 x 480						11.9 / 15.7
GS-45	45 x 494				2.0		13.3 / 17.4
GS-60	60 x 479	13	32	6	2.4		22.3