Satisfy Professional's Needs

CXT

# Cordless Ratchet Wrench
## WR100D 9.5 mm (3/8") / 6.35 mm (1/4 ")




## Cordless ratchet wrench powered by 12V max CXT Li-Ion battery

12V max LITHIUM-ION




XPT

# No load speed: 800 min.$^{-1}$

providing high efficiency fastening.

## Compatible with variable sockets with socket adaptor





**Socket adaptor**
9.5 mm (3/8" )
Part No.191A50-3



**Socket adaptor**
6.35 mm (1/4" )
Part No.191A51-1

## Easy to grip ergonomic design

The grip diameter is smaller than that of the competitors, providing the same good handling as hand ratchet wrenches.







**Can also be used as a hand ratchet wrench**

**Switch lever**


XPT
EXTREME PROTECTION TECHNOLOGY

12V max LITHIUM-ION

## Forward / reverse rotation change

Turn the reversing lever to the A side for clockwise rotation or to the B side for counterclockwise rotation.





## Able to tighten 13mm nut onto M8 threaded rod



13mm nut only

## LED job light

with preglow and afterglow functions



## Standard Equipment

Tool bag
Part No.
832071-7





## Li-ion Battery & Charging Time Reference, Compatibility Chart

| 12V max LITHIUM-ION *with Battery fuel gauge | BL1016 12V max 1.5Ah | *BL1021B 12V max 2.0Ah | *BL1041B 12V max 4.0Ah |
|---|---|---|---|
| DC10SB | 22 min | 30 min | 60 min |
| DC10WD | 50 min | 70 min | 130 min |

## Cordless Ratchet Wrench

### WR100D 9.5 mm (3/8") / 6.35 mm (1/4 ")

- Variable Speed
- Brake
- Reversing
- Built-in Job Light
- Carrying Case

| | |
|---|---|
| ***Capacity*** | *Standard Bolt: M5 - M12 (3/16" - 1/2")* |
| | *High Tensile Bolt: M5 - M10 (3/16" - 3/8")* |
| ***Square Drive*** | *9.5 / 6.35 mm (3/8" / 1/4 ")* |
| ***No Load Speed (RPM)*** | *0 - 800* |
| ***Max Fastening Torque*** | *47.5 N·m (420 in.lbs.)* |
| ***Max Output*** | *250 W* |
| ***Vibration Level*** | *2.5 m/s$^2$ or less* |
| ***Sound Pressure Level*** | *74 dB(A)* |
| ***Dimensions (L x W x H)*** | *w/ BL1016/BL1021B: 341x67x63 mm (13-7/16"x2-5/8"x2-1/2")* |
| | *w/ BL1041B: 341x67x84 mm (13-7/16"x2-5/8"x3-5/16")* |
| ***Net weight*** | *1.0 - 1.2 kg (2.3 - 2.7 lbs.)* |

***Standard Equipment :*** Socket Adapter, Battery, Charger, Tool bag

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combinations, according to EPTA-Procedure 01/2014, are shown in the table

*Items of standard equipment and specifications may vary by country or area.*

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201908