Satisfy Professional's Needs

LXT

Cordless Hammer Driver Drill
Cordless Driver Drill
DHP489 / DDF489 13 mm (1/2")



photo: DDF489

Cordless Hammer Driver Drill

DHP489



18V LITHIUM-ION

Cordless Driver Drill

DDF489



18V LITHIUM-ION

Max Lock Torque

80 N·m

BL MOTOR XPT


photo: DHP489


photo: DDF489

Excellent drilling capacity

with up to 1" ship auger bit in high speed mode

Mechanical 2-speed





photo: DHP489

Twin LED job light



with preglow and afterglow functions

Robust keyless drill chuck with single metal sleeve

Variable speed control by trigger



Excellent maneuverability

DHP489 only

Despite increased efficiency, the overall length is shorter than that of our current model due to optimally redesigned gear assembly.



18V LITHIUM-ION

BL MOTOR

XPT

Accessories

Grip assembly

Part No. 1912A4-3
Model: DHP489



Part No. 1912A3-5
Model: DDF489



Stopper pole

Part No. 122576-8
Model: DHP489



Hook

For BL1815N / BL1820B
Part No. 346449-3

For BL1830B / BL1840B / BL1850B / BL1860B
Part No. 346317-0



Charging Time

18V LITHIUM-ION	Fast Charging DC18RC	DC18SD
BL1815N 1.5Ah	**15** min	**30** min
BL1820B 2.0Ah	**24** min	**45** min
BL1830B 3.0Ah	**22** min	**60** min
BL1840B 4.0Ah	**36** min	**90** min
BL1850B 5.0Ah	**45** min	**110** min
BL1860B 6.0Ah	**55** min	**130** min

Cordless Hammer Driver Drill **DHP489** 13 mm (1/2")

Cordless Driver Drill **DDF489** 13 mm (1/2")

- Variable Speed
- Brake
- Reversing
- Mechanical 2-Speed
- Keyless Chuck
- Torque Setting 21
- Built-in Job Light
- Carrying Case

Standard Equipment :
Belt clip, (+)(-) Bit, Battery, Charger

	DHP489	DDF489
Capacity	*Masonry: 16 mm (5/8")*	*Steel: 13 mm (1/2")*
	Steel: 13 mm (1/2")	*Wood (Auger-Bit): 38 mm (1-1/2")*
	Wood (Self-feed bit): 51 mm (2")	*Wood (Self-feed bit): 51 mm (2")*
Chuck capacity	*1.5 - 13 mm (1/16 - 1/2")*	*1.5 - 13 mm (1/16 - 1/2")*
Impacts per minute (IPM)	*High: 0 - 27,000 / Low: 0 - 8,250*	-
No Load Speed (RPM)	*High: 0 - 1,800 / Low: 0 - 550*	*High: 0 - 1,800 / Low: 0 - 550*
Max fastening torque	*Hard: 73 N·m (650 in.lbs.)*	*Hard: 73 N·m (650 in.lbs.)*
	Soft: 40 N·m (350 in.lbs.)	*Soft: 40 N·m (350 in.lbs.)*
Max lock torque	*80 N·m (700 in.lbs.)*	*80 N·m (700 in.lbs.)*
Sound pressure level	*81 dB (A)*	*74 dB (A)*
Sound power level	*92 dB (A)*	-
Vibration level	*Work mode: impact drilling into concrete: 9.5 m/s²*	*Work mode: drilling into metal: 2.5 m/s² or less*
Dimensions (L x W x H)	*w/ BL1815N / BL1820B: 175 x 81 x 244 mm (6-7/8 x 3-3/16 x 9-5/8")*	*w/ BL1815N / BL1820B: 174 x 81 x 244 mm (6-7/8 x 3-3/16 x 9-5/8")*
	w/ BL1830B / BL1840B / BL1850B / BL1860B: 175 x 81 x 261 mm (6-7/8 x 3-3/16 x 10-1/4")	*w/ BL1830B / BL1840B / BL1850B / BL1860B: 174 x 81 x 261 mm (6-7/8 x 3-3/16 x 10-1/4")*
Net weight	*1.8 - 2.5 kg (4.0 - 5.5 lbs.)*	*1.8 - 2.5 kg (4.0 - 5.5 lbs.)*

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.
Items of standard equipment and specifications may vary by country or area.

Makita Corporation
3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202404