Satisfy Professional's Needs

XGT

Cordless Lawn Mower

LM003G 380 mm (15")
LM004G 430 mm (17")

XGT 40V max Li-ion



Continuous run time

LM003G	LM004G
49 min	52 min

Battery: BL4080F on a full battery charge

XPT

Powered by 40Vmax XGT Li-Ion battery



Mowing area

on a full battery charge (with BL4080F)

The results shown here are mowing area under actual load and continuous operation time (when the grass is cut from 50 to 30mm in height), which are approximate values when a fully charged battery is used; therefore, they depend to a great extent on grass density, cutting height, etc.

LM003G (380mm)

about 780 m²

LM004G (430mm)

about 830 m²

Continuous use

on a full battery charge (with BL4080F)

The results shown here are mowing area under actual load and continuous operation time (when the grass is cut from 50 to 30mm in height), which are approximate values when a fully charged battery is used; therefore, they depend to a great extent on grass density, cutting height, etc.

LM003G (380mm)

about 49 min

LM004G (430mm)

about 52 min

Higher mowing performance



The blade is designed to tilt down towards the front of the mower when attached, minimizing double-cutting to reduce the load on the machine for reduced energy consumption, better feeling of cutting and improved grass collecting performance.



Warning lamp for Battery capacity, High temperature and Overload

Cutting, Collecting, Mulching*

*Mulching plug required.

Easy-to-operate handle lock levers

- each side of the handle can be locked/unlocked with just a single action without tool.
- allows for easier folding of handle when storing the mower.





Upright storage





LM003G

380 mm (15")

Plastic Deck



LM004G

430 mm (17")

Plastic Deck



Easier cutting height adjustment

- The increase/decrease directions have been reversed so that they can synchronize easier with the high/low directions of height adjustment in user's mind.
- Easy-to-grip egg-shaped lever top
- U-shaped notches, which provide positive stops for lever, can be visually checked, making it easy to adjust cutting height.



Less force required to turn on the mower

Reduction in user fatigue has been achieved by redesigning the shape of switch lever and the specification of spring to reduce the force required to pull switch lever to turn on the mower.

Pull force required to turn on the mower
Approx. 11 N



The inside of cutting deck can be washed.



eXtreme Protection Technology / IPX4-compatible

XGT 40V max Li-ion

Lawn care/Grass care

Cordless Lawn Mower

LM001G (480mm)
LM002G (530mm)
40V max



LM003G (380mm)
LM004G (430mm)
40V max



Cordless Scarifier

UV001G (380mm)
40V max



Cordless Grass Trimmer

UR012G
40V max x2
Max Output 2.0 kW



Cordless Grass Trimmer

UR013G
UR014G
40V max
Max Output 1.5 kW



UR006G
UR007G
UR008G
40V max
Max Output 1.0 kW



UR002G
UR003G
40V max
Max Output 0.55 kW



UR016G
UR017G
40V max
Max Output 0.6 kW



Cordless Multi Function Power Head

UX01G
40V max
Max Output 1.0 kW



Cordless Blower

UB001G
40V max







Accessories

Blade type	Model (size)	Applications and features
Blade (2-tooth bar blade) 	LM003G (380mm)	• Standard blade for both grass collection and mulching • Features Improved grass collecting performance achieved by redesigning blade tips to increase air flow volume.
	LM004G (430mm)	
Mulching blade 	LM003G (380mm)	• Cuts grass clippings into small particles and scatters them evenly on the ground for mulching. • Ensures proper air flow volume required for mixing grass clippings in the deck.
	LM004G (430mm)	

Mulching plug

Model: LM003G
Size: 380mm

Model: LM004G
Size: 430mm

Essential component for mulching





Charging Time

	Fast Charging DC40RA	DC40RC
*1 **BL4020** 2.0Ah	22 min	30 min
*1 **BL4025** 2.5Ah	28 min	38 min
*1 **BL4040/F** 4.0Ah	45 min	67 min
*1 **BL4050F** 5.0Ah	50 min	85 min
*1 **BL4080F** 8.0Ah	76 min	170 min

*1 Recommended battery

Cordless Lawn Mower

LM003G / LM004G 380 mm (15") / 430 mm (17")

Brake
Anti-restart function

	LM003G	LM004G
Cutting width	*380 mm (15")*	*430 mm (17")*
Cutting height adjustment	*Adjustment range: 20 - 75 mm (13/16 - 2-15/16")* *Stage: 8*	*Adjustment range: 20 - 75 mm (13/16 - 2-15/16")* *Stage: 8*
No load speed (RPM)	*3,800*	*3,800*
Wheel diameter	*140 / 165 mm (5-1/2 / 6-1/2")*	*140 / 165 mm (5-1/2 / 6-1/2")*
Actual mowing area on full battery charge	*w/ BL4080F: 780 m^2*	*w/ BL4080F: 830 m^2*
Continuous run time on full battery charge	*w/ BL4080F: 49 min*	*w/ BL4080F: 52 min*
Grass catcher capacity	*40 L (1,353 oz)*	*50 L (1,691 oz)*
Vibration Level	*2.5 m/s^2 or less*	*2.5 m/s^2 or less*
Measured sound power level	*90 dB(A)*	*90 dB(A)*
Guaranteed sound power level	*93 dB(A)*	*93 dB(A)*
Sound pressure level	*83 dB(A)*	*81 dB(A)*
Dimensions (L x W x H)	*During operation:* *1,370 - 1,420 x 450 x 990 - 1,020 mm* *(54 - 56 x 17-3/4 x 39 - 40-1/4")* *When stored (w/o Grass box):* *520 x 450 x 880 mm (20-1/2 x 17-3/4 x 34-3/4")*	*During operation:* *1,390 - 1,440 x 460 x 990 - 1,020 mm* *(54-3/4 - 56-3/4 x 18-1/8 x 39 - 40-1/4")* *When stored (w/o Grass box):* *520 x 460 x 885 mm (20-1/2 x 18-1/8 x 34-3/4")*
Net weight	*14.9 - 17.3 kg (32.8 - 38.1 lbs.)*	*15.6 - 18.2 kg (34.4 - 40.1 lbs.)*

Standard Equipment :
Socket wrench, Blade, Mulching plug, Grass catcher, Battery, Charger

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.
Items of standard equipment and specifications may vary by country or area.

Makita Corporation
3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202309