Accessories

Adapter pipe 85-72 set
Part No. 191L96-5



Flat nozzle set
Part No. 197889-6

Narrow profile improves air speed for removing heavier debris such as wet leaves





Portable Power Pack

Portable Power Pack

PDC1500 **PDC1200**



Charger
DC4001
Charging time
PDC1500: 450 min.
PDC1200: 360 min.



PDC01



Powered by up to four 18V LXT batteries



Battery Powered

Blower
UB003C



Grass Trimmer
UR101C
UR201C
UR202C



Backpack Blower
UB002C



Lawn mower
LM001C



Adapter set

40Vmax
Part No.
191N62-4



Adapter between Battery box of Portable power pack and Product on 40Vmax XGT platform

18Vx2
Part No.
191J51-5



Adapter between Battery box of Portable power pack and Product on 18Vx2 LXT platform

18V
Part No.
191J50-7



Adapter between Battery box of Portable power pack and Product on 18V LXT platform
*PDC01 only

Battery Powered Blower
UB003C

Variable Speed	
Anti-restart function	
Electronic 3-Speed	
Constant Speed	
Max air volume	w/ End nozzle, w/ PDC1500, Max speed mode: 2.9 - 17.2 m^3/min
Max air velocity	w/ End nozzle, w/ PDC1500, Max speed mode: 86.0 m/s
Avg. air velocity	w/ End nozzle, w/ PDC1500, Max speed mode: 11.7 - 71.9 m/s
Blowing force	w/ End nozzle, w/ PDC1500, Max speed mode: 0.7 - 24 N
No load speed	Mode1 / Mode2 / Mode3: 4,000-10,600 / 17,700 / 22,100 min^{-1}
Continuous use (approx.) on a full battery charge	w/ End nozzle, w/ PDC1500, Max speed mode: 60 min
Sound pressure level	82.2 dB(A)
Sound power level	92.4 dB(A)
Vibration level	2.5 m/s^2 or less
Dimensions (L x W x H)	w/ Nozzle: 913 - 1,013 x 178 x 298 mm (36 - 40 x 7 x 11-3/4")
	w/o Nozzle: 662 x 178 x 298 mm (26 x 7 x 11-3/4")
Net weight	2.8 - 3.1 kg (6.2 - 6.8 lbs.)

Standard Equipment : End nozzle, Band assembly

Portable Power Pack
PDC1500

Capacity	43.55 Ah
Energy capacity	1,567.8 Wh
Number of cells	130
Charging time	450 min.
Dimensions (L x W x H)	w/o Harness: 369 x 312 x 131 mm (14-1/2 x 12-1/4 x 5-1/8")
Net weight	10.9 - 12.9 kg (24.0 - 28.4 lbs.)*
Power supply cord	Battery side: 1.2 m (3.9 ft)
	Adapter side: 0.6 m (2.0 ft)

*not covered by EPTA-Procedure

Standard Equipment : Harness, Charger

Weight according to EPTA-Procedure 01/2014
Items of standard equipment and specifications may vary by country or area.

Makita Corporation
3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan
PRINTED IN JAPAN 202312

Satisfy Professional's Needs

Battery Powered Blower
UB003C
Portable Power Pack
PDC1500







UB003C

Average blowing force	Max air volume	Max air velocity
24 N	17.6 m^3/min	86.0 m/s

Maximum speed mode or maximum speed with the cruise control lever, with PDC1500 / With standard nozzle attached

BL MOTOR ▲ UB003C
XPT ▲ UB003C
WG WET GUARD ▲ PDC1500



1,500Wh-class high capacity

Portable Power Pack
PDC1500

WG WET GUARD

Charging time
450 min.
with DC4001



Battery fuel gauge





More robust appearance and increased strength

Achieved by:
- New stand with increased strength obtained by using a larger diameter metal pipe
- Metalized junctions between battery and harness

Reflectors



Quickly removable harness



3 Speed mode button



Variable control trigger + Cruise control lever



Battery Powered Blower
UB003C

BL MOTOR XPT

Best grip-to-frame angle



Hole on the bottom of housing for hanging the machine on a wall-mounted hook for storage

Easy-to-hold machine bottom design for added comfort and control in double handed operation

Height-adjustable waist belt

The position of the waist belt can be adjusted for personal fit and comfort.



Compatible with a wide range of applications
(both in backpack and stationary styles)



Improvements for more comfortable backpacking experience



Plastic back plates have been extended up to the rear of user's shoulders to distribute the pressure on the shoulders.



Chest belt added to minimize the chance that both shoulder belts might slip outward.



Swivel mechanism on waist belt reduces user's fatigue

The waist belt section swivels around the fulcrum to adapt to the user's working posture.



Nozzle reducing reaction force

The recoil of the machine tilting is reduced with the grip as the fulcrum since the reaction force is directed toward the grip by tilting the nozzle tip downward, therefore, the burden on the user's arm is reduced.



3-stage telescopic long nozzle



Harness can be attached

The machine can be hanged by connecting the band to the harness of PDC1500, therefore, the burden on the user's hand can be reduced.

