Makita®

Cordless Impact Driver TD111D



Ultra compact and slim design

Max Fastening Torque

135 N·m

10.8V LITHIUM-ION

BL MOTOR

Powered by Slide Li-ion Battery of Makita's New 10.8V Platform



BL1015 **1.5Ah**



BL1020B **2.0Ah**



BL1040B **4.0Ah**





DC10SA



DC10WC

CXT

Ultra compact and slim design for easy handling

Single LED job light
with preglow and afterglow functions





Best possible ergonomic handle for screwing applications



A In order to provide maximum thrust to the bit, the top back of the handle is ergonomically contoured and widened to perfectly fit the U-shape formed between user's thumb and index finger.

B Ribbed soft grip enables all finger tips to hold the handle securely against the strong rotational force of counter torque even in single-handed operation.

Li-ion Battery & Charger Time Reference,Compatibility Chart

*with Battery fuel gauge

CXT	BL1015 10.8V 1.5Ah	*BL1020B 10.8V 2.0Ah	*BL1040B 10.8V 4.0Ah
DC10SA for 10.8V	22min	30min	60min
DC10WC for 10.8V	50min	70min	130min



Cordless Impact Driver — TD111D

- Variable Speed
- Brake
- Reversing
- Electronic 2-Speed
- Built-in Job Light
- Carrying Case

Hex Shank	*6.35 mm (1/4")*
No Load Speed (RPM)	*High / Low: 0 - 3,000 / 0 - 1,300*
Impacts Per Minute (IPM)	*High / Low: 0 - 3,900 / 0 - 1,600*
Max Tightening Torque	*135 N·m (1,200 in·lbs)*
Capacity	*Machine screw : M4 - M8mm (5/32" - 5/16")*
	Standard bolt : M5 - M14 (3/16" - 9/16")
	High strength bolt : M5 - M12 (3/16" - 1/2")
	Coarse thread (in length): 22 - 90mm (7/8" - 3-1/2")
Vibration Level	*12.5 m/s²*
Sound Pressure Level	*94 dB(A)*
Sound Power Level	*105 dB(A)*
¥Dimensions (L x W x H)	*135x66x210mm (5-5/16"x2-5/8"x8-1/4")*
Net weight	*BL1015: 0.97 kg (2.1 lbs)*
	BL1040: 1.1 kg (2.5 lbs)

Standard Equipment : Battery, Charger, Belt Clip, Phillips Bit

weight according to EPTA-Procedure 01/ver.2.1
Items of standard equipment and specifications may vary by country or area.

Makita Corporation
3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 201612