Technical data

Pump name AGA 1.50 T

Customer	Date 14-May-2020	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail

Requested data

1	Pump type	CENTRIFUGAL PUMPS	Fluid		Water, clean
2	Number of pumps / Reserve	1 / 0	Liquid temperature	K	293
3	Flow l/min	0	Kin. viscosity	mm²/s	1
4	Head m	0	Vapour pressure	kPa	2.2
5	Geodetic head m	0	PH value		7
6	Inlet pressure (pin) kPa	10	Density	kg/m³	1000
7	Available system NPSH	0	Solids	Weight %	0
8	Ambient temperature K	290			

Pump

9	Pump name	AGA 1.50 T	Frequency		Hz	50
10	Design	CENTRIFUGAL PUMPS	Installation type			STANDARD
11	Manufacturer	EPE	Impeller Diameter	Max.	mm	143
12	Speed 1/min	2850		Designed	mm	143
13	No. of Stage	1		Min.	mm	143
14	Connection Suction side	UNI ISO 228	Flow	Operating	l/min	
15	Connection Discharge side	UNI ISO 228		Max-	l/min	100
16	Max Working Pressure kPa	1000		Min-	l/min	10
17	Shut-off head kPa	499.54	Head	Operating	m	
18	Total weight kg	See the table of "Dimensions".		- (Qmax.)	m	27.0
19	Shaft power kW			- (Qmin.)	m	48.0
20			Max. Shaft Power at max. impeller		kW	1.30
21	Required pump NPSH m		Efficiency		%	

Materials

22	Impeller	Brass		
23	Casing	Cast iron		
24	Shaft	AISI 303 (wet extension)		
25				
26				
27				

Motor

28	Manufacturer	EPE Standard	Insulation class		F
29	Type	TEFC_AGA 1.50 T_230_Three Phase	Phases		3~
30	Specific design	IE3 / 50 Hz / Pole pairs 1	Frame size		
31	Rated power kW	1.1	Weight	kg	0
32	Number of poles	2	Electric voltage	V	230
33	Speed 1/min	2800	Electric current	A	5.8
34	Degree of protection	IP 44			
35					

Remarks

EBARA

Performance curve **Pump name** AGA 1.50 T

Customer	Date 14-May-2020	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail

Requested data


1	Flow	l/min	0
2	Head	m	0
3	Geodetic head	m	0

Pump

Operating Flow	l/min		Frequency	Hz	50
Operating Head	m		Number of poles		2
Impeller Diameter	Designed mm	143	Speed	1/min	

Test standard: ISO 9906:2012 - Grade3B

Water, clean [100%] ; 293K; 998.3kg/m³; 1mm²/s




EBARA

Dimensions

Pump name AGA 1.50 T

Customer	Date 14-May-2020	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail




Dimensions in mm								
1	]E	157	N1	220				
2	A	220	R	167.5				
3	B	520	S	9				
4	C	244	V	M20X1.5				
5	D	D	W	15.5				
6	DNA	G 1 1/2	Weight P&M	26.5 kg				
7	F	10						
8	H	223						
9	H1	170						
10	H2	53						
11	H3	229						
12	M	48						
13	N	175						

EBARA

(1/3)
Construction

Pump name AGA 1.50 T

Customer	Date 14-May-2020	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail



(2/3)
Construction

Pump name AGA 1.50 T

Customer	Date 14-May -2020	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail


N°	PART NAME		MATERIAL	Q.TY
1	Casing		Cast iron	1
3	Motor bracket	[1]	-	1
4	Casing cover	[2]	AISI 304	1
6	Shaft with rotor		AISI 303 (wet extension)	1
7	Impeller	[3]		1
9	Diffuser + Venturi tube		PPE+PS glass fibre reinforced	1
10	Venturi nozzle		PPE+PS glass fibre reinforced	1
11	Mechanical seal	[4]	Carbon/Ceramic/NBR	1
12	Motor frame with stator		-	1
13	Motor cover		Aluminium	1
14	Fan		PA	1
15	Fan cover		Fe P04 Zincate	1
16	Terminal board		-	1
17	Terminal box cover	[5]	Aluminium	1
18	Splash ring		NBR	1
19	Pump side ball bearing		-	1
20	Fan side ball bearing		-	1
21	Adjusting ring		Steel C70	1
22	Tie rod		Fe 42 Zincate	4
23	Capacitor	[6]	-	1
24	Priming plug		Brass	1
25	Drain plug		Brass	1
26	O-ring		NBR	1
27	O-ring		NBR	1
28	O-ring		NBR	1
32	Key		AISI 316	1
34	Impeller nut	[7]	AISI 304	1
42	Foot		PP	1
52	Capacitor box	[8]	ABS class V-0	1
53	Capacitor box cover	[9]	ABS class V-0	1
75	Washer		Aluminium	1
76	Washer		Aluminium	1
110	Protector	[8]	-	1
200	Screw		Zn Steel Cl. 8.8 ISO 898-1	4

[1] Material : Cast iron for version AGA 1.50 - AGA 2.00 - AGA 3.00 - AGC 1.50 - AGC 2.00 - AGC 3.00
Aluminium for version AGA 0.60 - AGA 0.75 - AGA 1.00
[2] Only for version AGA 0.60 - AGA 0.75 - AGA 1.00
[3] Material : PPE+PS glass fibre reinforced for version AGA 0.60 - AGA 0.75 - AGA 1.00
Brass for version AGA 1.50 - AGA 2.00 - AGA 3.00 - AGC 1.50 - AGC 2.00 - AGC 3.00
[4] See **CONSTRUCTION 3**
[5] Only for three phase
[6] Only for single phase
[7] Only for version with impeller in Brass
[8] Only for version single phase AGA 1.50 - AGA 2.00 - AGC 1.50 - AGC 2.00
[9] With gasket in NBR only for version single phase AGA 0.60 - AGA 0.75 – AGA 1.00

(3/3)
Construction

Pump name AGA 1.50 T

Customer	Date 14-May-2020	Company
Contact	Item no.	Issued by
Phone	Project	Phone
E-mail	Project ID	E-mail



REF	PART NAME	MATERIAL
A	Rotary seal ring	Ceramic
B	Stationary seal ring	Carbon graphite
C	O-Ring	NBR
D	O-Ring	NBR
E	O-Ring	NBR
F	Self-driving spring	AISI 316
G	Frame	AISI 304