

POWER TOOLS & ABRASIVES

MAKITA POWER TOOLS เครื่องมือไฟฟ้า “มาคิต้า”

XGT**40V^{Li-ion} max****XGT****40V^{Li-ion} max****XGT X2^{Li-ion} 80V^{max}****Makita**

มาคิต้า

DF002G

Cordless Driver Drill

40V max

40Vmax XGT BL Brushless Cordless
13 mm (1/2") 65 N-m (580 in.lbs.)
Driver Drill

**XGT BL XPT**

Capacity	Steel / Wood (Auger Bit) / Wood (Self-Feed Bit) / Wood (Hole Saw): 13 / 38 / 38 / 51 mm (1/2" / 1-1/2" / 1-1/2" / 2")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High / Low: 2,200 / 0 - 600
Max Fastening Torque	Hard / Soft: 64 / 30 N-m (570 / 270 in.lbs.)
Max Lock Torque	65 N-m (580 in.lbs.)
Dimensions (L x W x H)	w/ BL4020 / BL4025: 164 x 86 x 265 mm (6-1/2 x 3-3/8 x 10-3/8") w/ BL4040: 164 x 86 x 272 mm (6-1/2 x 3-3/8 x 10-3/4") w/ BL4050F: 164 x 86 x 294 mm (6-1/2 x 3-3/8 x 11-5/8")
Net weight	1.9 - 2.5 kg (4.2 - 5.5 lbs.)

DA001G

Cordless Angle Drill

40V max

40Vmax XGT BL ADT Cordless
13 mm (1/2") Angle Drill
with Keyed Chuck

**XGT BL ADT XPT**

Capacity	Steel: 13 mm (1/2") Wood (Self-Feed Bit) Hi: 65 mm (2-9/16") Wood (Self-Feed Bit) Lo: 118 mm (4-5/8") Wood (Hole Saw) Hi: 105 mm (4-1/8") Wood (Hole Saw) Lo: 159 mm (6-1/4") Wood (Auger-Bit): 50 mm (2")
Chuck Capacity	2 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High / Low: 0 - 1,500 / 0 - 400
Max Fastening Torque	High: 55 N-m (487 in.lbs.) Low: 136 N-m (1,210 in.lbs.)
Dimensions (L x W x H)	w/ BL4020 / BL4025: 339 x 128 x 199 mm (21-1/4 x 5 x 7-7/8") w/ BL4040: 345 x 128 x 199 mm (21-1/2 x 5 x 7-7/8") w/ BL4050F: 366 x 128 x 199 mm (22-1/4 x 5 x 7-7/8")
Net weight	5.3 - 6.2 kg (11.7 - 13.7 lbs.)

DG001G

Cordless Earth Auger

40V max

40Vmax XGT BL ADT Cordless Earth Auger

**XGT BL ADT XPT**

Capacity	Clay Soil: 150 mm Sandy Soil: 200 mm
Chuck Capacity	2 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High / Low: 0 - 1,500 / 0 - 400
Max Fastening Torque	High: 55 N-m (487 in.lbs.) Low: 136 N-m (1,210 in.lbs.)
Dimensions (L x W x H)	w/ BL4020 / BL4025: 836 x 605 x 199 mm (33 x 23-3/4 x 7-7/8") w/ BL4050F: 863 x 605 x 199 mm (34 x 23-3/4 x 7-7/8") 7.2 - 8.1 kg (15.9 - 17.9 lbs.)
Net weight	

TD001G

Cordless Impact Driver

40V max

40Vmax XGT BL Brushless Cordless
Wood/Bolt/T-Mode 220 N-m Impact Driver

**XGT BL XPT**

Capacity	Machine Screw: M4 - M8 (5/32 - 5/16") Standard Bolt: M5 - M16 (3/16 - 5/8") High Strength Bolt: M5 - M14 (3/16 - 9/16") Coarse thread (in length): 22 - 125 mm (7/8 - 4-7/8") 6.35 mm (1/4")
Hex Shank	
No Load Speed (RPM)	Max / Hard / Mid / Soft / Wood / Bolt (1) / Bolt (2) / Bolt (3) / T (1) / T (2) mode 0 - 3,700 / 3,200 / 2,100 / 1,100 / 1,800 / 2,500 / 3,700 / 3,700 / 2,400 / 3,700
Impacts Per Minute (IPM)	Max / Hard / Mid / Soft / Wood / Bolt (1) / Bolt (2) / Bolt (3) / T (2) mode 0 - 4,400 / 3,600 / 2,600 / 1,100 / 1,400 / 4,400 / 4,400 / 4,400 / 2,600
Max Fastening Torque	220 N-m (1,950 in.lbs.)
Fastening Torque	Hard / Mid / Soft: 170 / 50 / 20 N-m (1,510 / 440 / 180 in.lbs.)
Dimensions (L x W x H)	w/ BL4020 / BL4025: 120 x 86 x 245 mm (4-3/4 x 3-3/8 x 9-5/8") w/ BL4040: 120 x 86 x 250 mm (4-3/4 x 3-3/8 x 9-7/8")
Net weight	1.7 - 2.0 kg (3.7 - 4.4 lbs.)

TW004G

Cordless Impact Wrench

40V max

40Vmax XGT BL Cordless 1/2" (12.7 mm) 350 N-m (260 ft.lbs.)
Impact Wrench, Forward/Reverse Rotation Auto Stop Mode

**XGT BL XPT**

Fastening Capacities	Standard Bolt: M10 - M20 (3/8 - 3/4") High Strength Bolt: M10 - M16 (3/8 - 5/8")
Square Drive	12.7 mm (1/2")
Impacts Per Minute (IPM)	Max / Hard / Mid / Soft 0 - 4,000 / 3,400 / 2,600 / 1,800
No Load Speed (RPM)	Max / Hard / Mid / Soft 0 - 3,200 / 2,600 / 1,800 / 1,000
Max Fastening Torque	350 N-m (260 ft.lbs.)
Dimensions (L x W x H)	w/ BL4020 / BL4025: 144 x 86 x 248 mm (5-5/8 x 3-3/8 x 9-3/4") w/ BL4040: 144 x 86 x 253 mm (5-5/8 x 3-3/8 x 10")
Net weight	1.9 - 2.2 kg (4.2 - 4.9 lbs.)

TW007G

Cordless Impact Wrench

40V max

40Vmax XGT BL Cordless 1/2" (12.7 mm) 760 N-m (560 ft.lbs.)
Impact Wrench, Forward/Reverse Rotation Auto Stop Mode

**XGT BL XPT**

Fastening Capacities	Standard Bolt: M10 - M24 (3/8 - 1") High Strength Bolt (Grade 10.9): M10 - M16 (3/8 - 5/8") High Strength Bolt (Grade F10T): M12, M16 (7/16, 5/8")
Square Drive	12.7 mm (1/2")
Impacts Per Minute (IPM)	Max / Hard / Mid / Soft: 0 - 2,900 / 2,700 / 1,900 / 1,200
No Load Speed (RPM)	Max / Hard / Mid / Soft: 0 - 2,300 / 1,900 / 1,200 / 600
Max Fastening Torque	760 N-m (560 ft.lbs.)
Dimensions (L x W x H)	w/ BL4020 / BL4025: 170 x 86 x 285 mm (6-11/16 x 3-3/8 x 11-1/4") w/ BL4040: 170 x 86 x 291 mm (6-11/16 x 3-3/8 x 11-1/2") w/ BL4050F: 170 x 86 x 312 mm (6-11/16 x 3-3/8 x 12-1/4")
Net weight	2.7 - 3.3 kg (6.0 - 7.3 lbs.)

TW001G

Cordless Impact Wrench

40V max

40Vmax XGT BL Cordless 3/4" (19 mm) 1,800 N-m (1,330 ft.lbs.)
Impact Wrench, Reverse Rotation Auto Stop Mode

**XGT BL XPT**

Fastening Capacities	Standard Bolt: M12 - M36 (1/2 - 1-7/16") High Strength Bolt: M10 - M27 (3/8 - 1-1/16") 19 mm (3/4")
Square Drive	Max / Hard / Mid / Soft 0 - 2,500 / 2,400 / 2,200 / 1,900
Impacts Per Minute (IPM)	Max / Hard / Mid / Soft 0 - 1,800 / 1,400 / 1,150 / 950
No Load Speed (RPM)	1,800 N-m (1,330 ft.lbs.)
Max Fastening Torque	w/ BL4020 / BL4025: 217 x 94 x 297 mm (8-1/2 x 3-11/16 x 11-3/4") w/ BL4040: 217 x 94 x 303 mm (8-1/2 x 3-11/16 x 11-7/8") w/ BL4050F: 217 x 94 x 312 mm (8-1/2 x 3-11/16 x 11-7/8")
Dimensions (L x W x H)	
Net weight	3.9 - 4.2 kg (8.6 - 9.3 lbs.)

GA038G

Cordless Angle Grinder

40V max

40Vmax XGT BL AWS AFT Cordless Angle Grinder, Anti-Restart Function,
Electric Brake, Large Trigger Switch

**XGT BL AFT****AWS XPT**

Wheel Diameter	230 mm (9")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	6,600
Circumference of Grip Portion	154 mm (6-1/16")
Dimensions (L x W x H)	w/ BL4025: 497 x 250 x 156 mm (19-1/2 x 9-7/8 x 6-1/8") w/ BL4040: 509 x 250 x 164 mm (20 x 9-7/8 x 6-1/2") w/ BL4050F: 535 x 250 x 180 mm (21 x 9-7/8 x 7-1/8") 4.6 - 7.4 kg (10.1 - 16.3 lbs.)

GA037G

Cordless Angle Grinder

40V max

40Vmax XGT BL AWS AFT Cordless Angle Grinder, Anti-Restart Function,
Electric Brake, Large Trigger Switch

**XGT BL AFT****AWS XPT**

Wheel Diameter	180 mm (7")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	7,800
Circumference of Grip Portion	154 mm (6-1/16")
Dimensions (L x W x H)	w/ BL4025: 497 x 200 x 156 mm (19-1/2 x 7-7/8 x 6-1/8") w/ BL4040: 509 x 200 x 164 mm (20 x 7-7/8 x 6-1/2") w/ BL4050F: 535 x 200 x 180 mm (21 x 7-7/8 x 7-1/8") 4.4 - 5.4 kg (9.7 - 11.9 lbs.)

GA003G

Cordless Angle Grinder

40V max

40Vmax XGT BL AFT Cordless Angle Grinder, Anti-Restart Function,
Electric Brake, Slide Switch Lock-On

**XGT BL AFT****XPT**

Wheel Diameter	180 mm (7")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	7,800
Dimensions (L x W x H)	154 mm (6-1/16") w/ BL4025: 497 x 200 x 156 mm (19-1/2 x 7-7/8 x 6-1/8") w/ BL4040: 509 x 200 x 164 mm (20 x 7-7/8 x 6-1/2") w/ BL4050F: 535 x 200 x 180 mm (21 x 7-7/8 x 7-1/8") 4.4 - 5.4 kg (9.7 - 11.9 lbs.)

GA006G

Cordless Angle Grinder

40V max

40Vmax XGT BL AFT Cordless Angle Grinder, Anti-Restart Function,
Slide Switch Lock-On

**XGT BL AFT XPT**

Wheel Diameter	100 mm (4")
Hole Diameter	16 mm (5/8")
No Load Speed (RPM)	8,500
Dimensions (L x W x H)	w/ BL4040: 410 x 117 x 158 mm (16-1/8 x 4-5/8 x 6-1/4") w/ BL4020 / BL4025: 398 x 117 x 146 mm (15-5/8 x 4-5/8 x 5-3/4") 2.7 - 3.3 kg (6.0 - 7.3 lbs.)
Net weight	

GA011G

Cordless Angle Grinder

40V max

40Vmax XGT BL AFT Cordless Angle Grinder, Anti-Restart Function,
Electric Brake, Paddle Switch

**XGT BL AFT****XPT**

Wheel Diameter	100 mm (4")
Hole Diameter	16 mm (5/8")
No Load Speed (RPM)	8,500
Dimensions (L x W x H)	w/ BL4040: 410 x 117 x 162 mm (16-1/8 x 4-5/8 x 6-3/8") w/ BL4020 / BL4025: 398 x 117 x 150 mm (15-5/8 x 4-5/8 x 5-7/8") 2.8 - 3.4 kg (6.2 - 7.5 lbs.)
Net weight	