

CUTTING TOOLS & PRECISION TOOLS

Straight Shank Long Drill

ดอกสว่านพิเศษ HSS ก้านตรง ยาวพิเศษ


NACHI

นาชิ

List 550



- Designed for drilling deep holes or wherever the location of the hole is such as to require the additional overall and flute length of this type.



KT Code NA0550_(O.A.L x Dia.) เช่น 600 mm X 13.0 mm : NA0550_600X1300

Unit : mm

ขนาด Dia. (mm)	ความยาวรวม O.A.L. (Over All Length)													
	150 mm		200 mm		250 mm		300 mm		400 mm		500 mm		600 mm	
	Flute Length	S1A1	Flute Length	S1A1	Flute Length	S1A1	Flute Length	S1A1	Flute Length	S1A1	Flute Length	S1A1	Flute Length	S1A1
5.0	75		100		120		130		150		-		-	
5.1	100		100		120		130		150		-		-	
5.2	100		100		120		130		150		-		-	
5.3	100		100		120		130		150		-		-	
5.4	100		100		120		130		150		-		-	
5.5	100		100		120		130		150		-		-	
5.6	100		100		120		150		180		180		-	
5.7	100		100		120		150		180		180		-	
5.8	100		100		120		150		180		180		-	
5.9	100		100		120		150		180		180		-	
6.0	100		100		120		150		180		180		200	
6.1	100		100		120		150		-		-		-	
6.2	100		100		120		150		-		-		-	
6.3	100		100		120		150		-		-		-	
6.4	100		100		120		150		-		-		-	
6.5	-		100		120		150		200		200		200	
6.6	-		100		120		150		-		-		-	
6.7	-		100		120		150		-		-		-	
6.8	-		100		120		150		-		-		-	
6.9	-		100		120		150		-		-		-	
7.0	-		100		120		150		200		200		200	
7.1	-		100		120		150		-		-		-	
7.2	-		100		120		150		-		-		-	
7.3	-		100		120		150		-		-		-	
7.4	-		100		120		150		-		-		-	
7.5	-		100		120		150		200		200		200	
7.6	-		100		120		150		-		-		-	
7.7	-		100		120		150		-		-		-	
7.8	-		100		120		150		-		-		-	
7.9	-		100		120		150		-		-		-	
8.0	-		100		120		150		200		200		200	
8.1	-		100		120		150		-		-		-	
8.2	-		100		120		150		-		-		-	
8.3	-		100		120		150		-		-		-	
8.4	-		100		120		150		-		-		-	
8.5	-		100		120		150		200		200		200	
8.6	-		100		120		150		-		-		-	
8.7	-		100		120		150		-		-		-	
8.8	-		100		120		150		-		-		-	
8.9	-		100		120		150		-		-		-	
9.0	-		100		120		150		200		200		200	
9.1	-		100		120		150		-		-		-	
9.2	-		100		120		150		-		-		-	
9.3	-		100		120		150		-		-		-	
9.4	-		100		120		150		-		-		-	
9.5	-		100		120		150		200		200		200	
9.6	-		100		120		150		-		-		-	
9.7	-		100		120		150		-		-		-	
9.8	-		100		120		150		-		-		-	
9.9	-		100		120		150		-		-		-	
10.0	-		100		120		150		200		250		300	
10.1	-		100		120		150		-		-		-	
10.2	-		100		120		150		-		-		-	
10.3	-		100		120		150		-		-		-	
10.4	-		100		120		150		-		-		-	
10.5	-		125		120		150		200		250		300	
10.6	-		-		120		150		-		-		-	
10.7	-		-		120		150		-		-		-	
10.8	-		-		120		150		-		-		-	
10.9	-		-		120		150		-		-		-	
11.0	-		-		120		150		200		250		300	
11.1	-		-		120		150		-		-		-	
11.2	-		-		120		150		-		-		-	
11.3	-		-		120		150		-		-		-	
11.4	-		-		120		150		-		-		-	
11.5	-		-		120		150		200		250		300	
11.6	-		-		120		150		-		-		-	
11.7	-		-		120		150		-		-		-	
11.8	-		-		120		150		-		-		-	
11.9	-		-		120		150		-		-		-	
12.0	-		-		120		150		200		250		300	
12.1	-		-		120		150		-		-		-	
12.2	-		-		120		150		-		-		-	
12.3	-		-		120		150		-		-		-	
12.4	-		-		120		150		-		-		-	
12.5	-		-		120		150		200		250		300	
12.6	-		-		120		150		-		-		-	
12.7	-		-		120		150		-		-		-	
12.8	-		-		120		150		-		-		-	
12.9	-		-		120		150		-		-		-	
13.0	-		-		120		150		200		250		300	

Cutting Condition : B33