AA CHIPPING HAMMER

AA CHIPPING HAMMER

- Precision valve allows excellent control during operation.
- Replaceable bushing
- 2 types of bushing ,round or hex, are available.
- Anti-vibration handle is available for AA-1.3B.



AA-0B



AA-1.3B



AA-3B



TYC-6B

MODEL NO.	PISTON DIAMETER mm	PISTON STROKE mm	BLOW PER MIN. b.p.m.	NET WEIGHT kg	NET WEIGHT lb	OVERALL LENGTH mm	AIR CONSUMPTION m^3/min	AIR CONSUMPTION c.f.m.	HOSE SIZE mm	SHANK SIZE ROUND OR HEX	AIR INLET SIZE PT
AA-0B	20	50	3,600	2	4.4	254	0.35	12.4	12.7	R15/12H×53	3/8
AA-1.3B	24	58	2,800	4.5	9.9	320	0.45	15.9	12.7	R18/15H×60	3/8
AA-3B	28	79	2,400	5.8	13.9	330	0.45	15.9	12.7	R18/15H×60	3/8
TYC-6B	28.54	75	1,800	6.7	14.8	430	0.8	28.2	12.7	R18/15H×60	3/8

CHIPPING HAMMER

CHIPPING HAMMER

- Available in 1"to 4"stroke for wide selection to suit variety of applications.
- Replacebale bushing
- 2types of bushing, round or hex, are available.
- 2types of retainer, cup and spring, are available.(THA-4B)
- Four bolt handle for excellent durability and maintenance.(TCH-3&4)

Goose Neck Handle



THA-2B



THA-3B



THA-4B



THA-4S

4-Bolt Handle



TCH-3



TCH-4

MODEL NO.	PISTON DIAMETER mm	PISTON STROKE mm	BLOW PER MIN. b.p.m.	NET WEIGHT kg	NET WEIGHT lb	OVERALL LENGTH mm	AIR CONSUMPTION m^3/min	AIR CONSUMPTION c.f.m.	HOSE SIZE mm	SHANK SIZE ROUND OR HEX	AIR INLET SIZE PT
THA-2B	28.54	51	2,300	6.2	13.6	413	0.85	30	12.7	R18/15H×60	3/8
THA-3B	28.54	64	2,200	6.8	15	450	0.9	31.8	12.7	R18/15H×60	3/8
THA-4B(S)	28.54	102	1,800	7	16.1	480	0.95	33.5	12.7	R18/15H×60	3/8
TCH-3	28.54	63.5	2,200	8.6	19	406	0.89	31.5	12.7	R18/15H×60	3/8
TCH-4	28.54	101.6	1,800	9	20	432	0.95	33	12.7	R18/15H×60	3/8

SINKER ROCK DRILL

SINKER ROCK DRILL

- Multiposition throttle for smooth start up in drilling.
- Well balanced body for efficient operation.
- Each component is carefully heat treated to maxiumize durability.
- Anti-vibration model is available on request.



TJ-15



TJ-15SV



TJ-20



TJ-20SV



TS-55

MODEL NO.	PISTON DIAMETER mm	PISTON STROKE mm	BLOW PER MIN. b.p.m.	ROTARY SPEED r.p.m.	NET WEIGHT kg	NET WEIGHT lb	OVERALL LENGTH mm	AIR CONSUMPTION m^3/min	AIR CONSUMPTION c.f.m.	HOSE SIZE mm
TJ-15	54	45	2,450	250	14	31	504	1.6	56.5	19
TJ-15SV	54	45	2,450	250	17.8	39	567	1.6	56.5	19
TJ-20	68	49	2,400	200	18.5	41	610	2.5	88.3	19
TJ-20SV	68	49	2,400	200	22.5	50	583	2.5	88.3	19
TS-55	66.6	64	1,800	200	27	60	581-S 606-L	2.6	91.8	19

ROTARY HAMMER

ROTARY HAMMER

- TH5-S is designed for a wide variety of construction and maintenance applications
- 15T and 19T taper rods are available.
- Insert bit is available.

INSERT BIT FOR ROTARY HAMMER



TH5-S

- INSERT BIT



SIZE G	SHANK SIZE	OVERALL LENGTH
13	R 3/4•5/8H	250, 350
14	R 3/4•5/8H	230, 250, 400
14.5	R 3/4•5/8H	250, 300
15	R 3/4•5/8H	300
16	R 3/4•5/8H	250,280,400,500,600,700
17.5	R 3/4•5/8H	300


SIZE G	SHANK SIZE	OVERALL LENGTH
18	R 3/4•5/8H	280, 400, 500, 600, 700
19	R 3/4•5/8H	300, 400, 500, 600, 700
20	R 3/4•5/8H	280, 400, 500, 600, 700
21.5	R 3/4•5/8H	300
22	R 3/4•5/8H	280, 400, 500, 600, 700

- 15T TAPER ROD



- 19T TAPER ROD





19X22 ADAPTER FOR ROTARY HAMMER

Bits for 22 taper rods can be used by 19 taper rods and this adapter.



SOCKET ADAPTER FOR ROTARY HAMMER

Mounting chemical anchor.

MODEL	ROTARY SPEED r.p.m.	BLOW PER MIN. b.p.m.	NET WEIGHT kg	NET WEIGHT lb	OVERALL LENGTH mm	AIR CONSUMPTION m^3/min	AIR CONSUMPTION c.f.m.	HOSE SIZE mm	SHANK SIZE PT
TH5-S	420	3,400	5.8	12.8	425	0.85	30	12.7	R3/4•5/8H