TIG/MMA Welder : TIG-200S / TIG-200ST / TIG-200T / TIG-200MT

เครื่องเชื่อม TIG/MMA พร้อมระบบ HF Arc-Starting

JASIC เจสิค

Features

- Single DC TIG function
- High frequency ignition
- Post-flow function
- Superior arc performance
- Light and compact, easy to carry and use
- Economizes tungsten use with a stable output & high duty cycle

Standard:
- HF/ Scratch TIG
  - Current knob
  - Postflow time switch (R20, R107)
  - Postflow time knob (R79)
- O.C. LED light (O.C & O.H alarm)



TIG-200S



TIG-200ST

Standard:
- HF/ Scratch TIG
  - Current knob
  - TIG200AII Postflow knob 0~10s
  - TIG200AIII Postflow 2.5s
- MMA
- O.C. LED light (O.C & O.H alarm)
- Power Indicator

TIG HF Post-Flow



TIG-200T



TIG-200MT

Accessories



TIG Torch Set
TIG-200S / TIG-200ST : SR26 4m
TIG-200T / TIG-200MT : SR26 7.6m



Electrode Holder Set 300A 10mm² 5m



Earth Clamp Set 300A 10mm² 5m



Alumina Cup No.4 / No.5



Collect 1.6 / 2.4 / 3.2



Collect Body 2.4

Long Cap



Short Cap

Tungsten Electrode



Argon Regulator

รุ่น (Model)	TIG-200S	TIG-200ST	TIG-200T	TIG-200MT (2 ระบบ)
KT Code	KT-J019-TIG200S	KT-J019-TIG200ST	KT-J019-TIG200T	KT-J019-TIG200MT
แรงดันไฟเข้า (Input power voltage)	1 เฟส 220V ±15%, 50/60HZ	1 เฟส 220V ±15%, 50/60HZ	1 เฟส 220V ±15%, 50/60HZ	1 เฟส 220V ±15%, 50/60HZ
กำลังไฟเข้า (Input power capacity)	5.2KVA	6.16KVA	4.5KVA	5.2KVA
แรงดันไฟขณะไร้ภาระ (No-Load Voltage)	50V	56V	42V	55V
กระแสไฟเชื่อม (Output current range)	200A	TIG : 200A / MMA : 180A	10 - 200A	10 - 200A
แรงดันไฟในการเชื่อม (Rated output voltage)	17.2V	TIG : 17.2A / MMA : 26A	18V	TIG : 17V / MMA : 26V
ความสามารถในการทำงาน (Duty cycle)	100%=100A / 60%=130A	100%=100A / 60%=130A	100%=155A / 60%=200A	100%=138A / 60%=180A
แก๊สปกป้องการเชื่อม (Flow time)	ก่อนเชื่อม 1-10 Sec	ก่อนเชื่อม 1-10 Sec	ก่อนเชื่อม 1-10 Sec	ก่อนเชื่อม 1-10 Sec
ประสิทธิภาพ (Efficiency)	85%	85%	85%	85%
พาวเวอร์แฟคเตอร์ (Power factor COSΘ)	0.7	0.68	0.93	0.93
ระดับความเป็นฉนวน (Insulation class)	F	F	B	B
น้ำหนัก (Weight)	7.15kg	7.15kg	9kg	9kg
ขนาดเครื่อง (Dimension)	430x168x312mm	430x168x312mm	371x153x234mm	375x172x305mm
ระดับฉนวนป้องกัน (Protection Class)	IP21S	IP21S	IP23	IP23
ความหนาของชิ้นงานเชื่อม (Welding Thickness)	0.3-8.0mm	0.3-8.0mm	0.3-8.0mm	0.3-8.0mm
ราคา				