LIVE CENTERS "IIDA" MODEL HD-S

ปั้นจี้ศูนย์เป็น (แบบลูกปืน) "IIDA" รุ่น HD-S


"Unique Head-Driving Mechanism".....100% Preventing Dusts and chips coming inside. ensuring long life and excellent accuracy.

HD-S TYPE

This standard type is built in special bearing with an unique head-driving mechanism, useful for high-speed R.P.M. (6,000 r.p.m.) and guaranteed within 0.003 mm. Unique bearings increase the general-load approx 75% up in comparision with the other conventional Live Center.
The price reasonable for the standard market.

TRADE MARK

อีด้า





Dimension : mm

KT Code	รุ่น	Size	A	B	C	D	E	L	Weight (g)	ราคา
I012-0120	HD-2S	M.T. No.2	24	37	69	40	18	130	500	
I012-0130	HD-3S	M.T. No.3	32	44	85	45	25	161	850	
I012-0140	HD-4S	M.T. No.4	32	44	108	45	25	184	1160	
I012-0150	HD-5S	M.T. No.5	49	70	136	78	38	255	4080	

ยันศูนย์ LIVE CENTERS "HS" (ไต้หวัน)

- ยันศูนย์ลูกปืนหัวเป็น

TRADE MARK

เอช เอส

KT Code	รุ่น	TAPER เบอร์	ราคา
KT-B011-0360	HS-208	MT-2	
KT-B011-0370	HS-208	MT-3	



3-JAW SELF-CENTERING SCROLL CHUCKS

หัวจับแท่นกลึงชนิด 3 จับ เข้าพร้อม "LS"

Victor

วิคเตอร์



LS

KT Code	เทียบรุ่นใหม่	รุ่น/ขนาด	ความกว้างฐานล่าง (mm)	ขนาดรูกลาง (mm)	ความสามารถปากจับ		ราคา
					ปากใน(mm)	ปากนอก(mm)	
V031-0050	SC 190F	LS-7 (7")	192	54	52	152	

(อุปกรณ์ติดตัว : ปากจับในและปากจับนอก อย่างละ 1 ชุด)

ข้อดี

- ตัวเรือนทำจากเหล็ก "SEMI STEEL" แข็งแรง ทนทาน และเที่ยงตรงได้รับมาตรฐานรับรองคุณภาพ J.I.S. จากกระทรวงอุตสาหกรรมญี่ปุ่น

4-JAW SELF-CENTERING SCROLL CHUCKS

หัวจับแท่นกลึงชนิด 4 จับ เข้าพร้อม "LS"

Victor

วิคเตอร์



LS

KT Code	รุ่น/ขนาด	ความกว้างฐานล่าง (mm)	ขนาดรูกลาง (mm)	ความสามารถปากจับ		ราคา
				ปากใน(mm)	ปากนอก(mm)	
V031-0190	LS4J-7 (7")	192	54	52	152	
V031-0200	LS4J-9 (9")	233	70	68	186	
V031-0210	LS4J-10 (10")	274	90	88	220	
V031-0220	LS4J-12 (12")	310	110	108	250	

4-JAW INDEPENDENT CHUCKS

หัวจับแท่นกลึงชนิด 4 จับอิสระ "LI"

Victor

วิคเตอร์



- SOLID REVERSIBLE JAWS
- SEMI STEEL BODIES

KT Code	รุ่น/ขนาด	ความกว้างฐานล่าง (mm)	ขนาดรูกลาง (mm)	ราคา
V031-0100	LI-8 (8")	200	50	
V031-0120	LI-12 (12")	300	70	
V031-0180	LI-24 (24")	600	130	