MAKITA POWER TOOLS
เครื่องมือไฟฟ้า "มากีต้า"

18V + 18V = 36V LXT

มากีต้า

DHR400 40mm (1-9/16") Cordless Rotary Hammer 18Vx2

High Power similar to AC Tool



Impact Energy	EPTA-Procedure 05/2009: 8.0 J
experimental conditions	11.4 J
Capacity	Concrete (w/ T.C.T. bit) : 40 mm
	Concrete (w/ Core bit) : 105 mm
Blows Per Minute (BPM)	1,450 - 2,900
No Load Speed (RPM)	250 - 500
Sound Power Level	102 dB(A)
Dimensions	473x120x285 mm
(L x W x H)	(18-5/8"x4-3/4"x11-1/4")
Net weight	7.3 - 8.1 kg (16.1 - 17.9 lbs)

DHR281 28mm (1-1/8") Cordless Combination Hammer 18Vx2

High speed drilling and great work volume





Impact Energy	EPTA-Procedure 05/2009: 2.8 J
Capacity	Concrete/Steel/Wood/Core Bit / Diamond Core Bit (Dry Type): 28/13/32/54/65 mm
	(1-1/8"/1/2"/1-1/4"/2-1/8"/2-9/16")
Blows Per Minute (BPM)	0 - 5,000
No Load Speed (RPM)	0 - 980
Sound Power Level	103 dB(A)
Dimensions	404x134x232 mm
(LxWxH)	(15-7/8"x5-1/4"x9-1/8")
Net weight	4.0-5.1kg (8.8-11.2lbs.)

DHR280 28mm (1-1/8") Cordless Combination Hammer 18Vx2

High speed drilling and great work volume



Impact Energy	EPTA-Procedure 05/2009: 2.8 J
Capacity	Concrete/Steel/Wood/Core Bit / Diamond Core Bit (Dry Type): 28/13/32/54/65 mm
	(1-1/8"/1/2"/1-1/4"/2-1/8"/2-9/16")
Blows Per Minute (BPM)	0 - 5,000
No Load Speed (RPM)	0 - 980
Sound Power Level	104 dB(A)
Dimensions	373x134x232 mm
(LxWxH)	(14-3/4"x5-1/4"x9-1/8")
Net weight	3.9-4.9kg (8.6-10.8lbs.)

DHR263RF 26mm (1") Cordless Combination Hammer 18Vx2

Rotary hammer - Powered by 18Vx2 (36V) Li-ion batteries in series



Impact Energy	EPTA-Procedure 05/2009: 2.5 J
	Our experimental conditions: 3.0 J
Capacity	Concrete / Steel / Wood: 26 / 13 / 32 mm
	(1" / 1/2" / 1-1/4")
Impacts Per Minute (BPM)	0 - 5,000
No Load Speed (RPM)	0 - 1,250
Sound Power Level	105 dB(A)
Dimensions	350x116x232mm
(L x W x H)	(13-3/4"x4-9/16"x9-1/8")
Net weight	4.1 kg (9.0 lbs)

DDG460ZX Cordless Earth Auger 18Vx2

Battery powered and powerful



Capacity	Sandy Soil: 200 mm
	Clay Soil: 150 mm
No Load Speed (RPM)	High / Low: 0-1,400/0-350
Max Fastening Torque	High: 48 N.m (430 in.lbs.)
	Low: 136 N.m (1,210 in.lbs.)
Vibration Level	2.5 m/s² or less
Sound Pressure Level	85 dB(A)
Sound Power Level	96 dB(A)
Dimensions	840 x 607 x 223 mm
(L x W x H)	(33 x 23-7/8 x 8-3/4")
Net weight	7.3 - 8.2 kg (16.1 - 18.1 lbs.)

DDA460Z Cordless Angle Drill 18Vx2

18V X2 LXT BL ADT Cordless 13 mm (1/2") Angle Drill with Keyed Chuck



Capacity	Steel: 13 mm (1/2")
	Wood (Self-Feed Bit)
	Hi: 65 mm (2-9/16")
	Wood (Self-Feed Bit)
	Lo: 118 mm (4-5/8")
	Wood (Hole Saw) Hi: 105 mm (4-1/8")
	Wood (Hole Saw) Lo: 159 mm (6-1/4")
	Wood (Auger-Bit): 50 mm (2")
No Load Speed (RPM)	High / Low: 0 - 1,400 / 0 - 350
Max Output	1,350 W
Dimensions	538x128x223 mm
(L x W x H)	(21-1/4"x5"x8-3/4")
	w/ Front Handle Extended: 608x128x193 mm (24"x5"x7-5/8")
Net weight	5.7 - 6.4 kg (12.6 - 14.0 lbs.)

DWT310 Cordless Shear Wrench 18Vx2

High-speed fastening beyond AC tool



Capacity	Bolt : M16, M20, M22 (5/8", 3/4", 7/8")
No Load Speed (RPM)	14
Max Fastening Torque	804 N·m (593 ft.lbs.)
Sound Power Level	94 dB(A)
Dimensions	296x130x377 mm
(L x W x H)	(11-5/8"x5-1/8"x14-7/8")
Net weight	6.5 - 7.1 kg (14.3 - 15.7 lbs.)

DLW140 355mm (14") Portable Cut-off 18Vx2

18V X2 (36V) LXT BL 355 mm (14") Toolless Portable Cut-Off



Wheel Diameter	355 mm (14")
Hole Diameter	25.4 mm (1")
No Load Speed (RPM)	3,800
Max Output	1,300 W
Sound Power Level	115dB
Dimensions	537x290x640 mm
(L x W x H)	(21-1/8"x11-3/8"x25-1/4")
Net weight	17.2 - 17.8 kg (37.9 - 39.3 lbs.)

DGA900 230mm (9") Cordless Angle Grinder 18Vx2

High power Cordless Angle Grinder



Wheel Diameter	230 mm (9")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	6,000
Max Output	-
Sound Power Level	-
Dimensions	499x250x158 mm
(L x W x H)	(19-5/8x9-7/8x6-1/4")
Net weight	5.2 - 8 kg (11.46 - 17.64 lbs.)

DGA700Z 180mm (7") Cordless Angle Grinder 18Vx2

High power Cordless Angle Grinder



Wheel Diameter	180 mm (7")
No Load Speed (RPM)	7,800
Sound Power Level	99 dB(A)
Dimensions	499x200x158 mm
(L x W x H)	(19-5/8"x7-7/8"x6-1/4")
Net weight	5.0-6.0kg (11.0 - 13.2 lbs)

DLS211Z 305mm (12") Cordless Slide Compound Miter Saw 18Vx2

Rail-forward design enables to be placed against a wall for maximizing work space



Blade Diameter	305 mm (12")
Miter Angle	60°L/60°R
Bevel Angle	48°L/48°R
Max Cutting Capacity	90° Miter: 107 x 363 mm
	90° Miter: 92 x 382 mm
	45° Miter, L/R: 107 x 255 mm
	45° Miter, L/R: 92 x 268 mm
No Load Speed (RPM)	4,400
Dimensions	898x664x725mm
(L x W x H)	(35-1/4"x27-1/8"x28-1/2")
Net weight	30.7 - 31.3 kg (67.6 - 69.1 lbs.)

DLS111ZU 305mm (12") Cordless Slide Compound Miter Saw 18Vx2

Rail-forward design enables to be placed against a wall for maximizing work space



Blade Diameter	260 mm
Miter Angle	60°L/60°R
Bevel Angle	48°L/48°R
Max Cutting Capacity	90° Miter: 91 x279 mm
	90° Miter: 68 x310 mm
No Load Speed (RPM)	4,400
Dimensions	805x644x660mm
(L x W x H)	(31-3/4x25-3/8x26")
Net weight	26.6 - 27.3 kg