MAKITA POWER TOOLS
เครื่องมือไฟฟ้า "มากีต้า"

มากีต้า

GA021G — Cordless Angle Grinder — 40V max

40Vmax XGT BL AWS AFT Cordless Angle Grinder, Anti-Restart Function, Electric Brake, Slide Switch Lock-On



Wheel Diameter	100 mm (4")
Hole Diameter	16 mm (5/8")
No Load Speed (RPM)	3,000 - 8,500
Dimensions (L x W x H)	w/ BL4040: 425 x 117 x 162 mm (16-3/4 x 4-5/8 x 6-3/8") w/ BL4020 / BL4025: 413 x 117 x 150 mm (16-1/4 x 4-5/8 x 5-7/8")
Net weight	2.8 - 3.4 kg (6.2 - 7.5 lbs.)

GA027G — Cordless Angle Grinder — 40V max

40Vmax XGT BL AWS AFT Cordless Angle Grinder, Anti-Restart Function, Electric Brake, Paddle Switch



Wheel Diameter	100 mm (4")
Hole Diameter	16 mm (5/8")
No Load Speed (RPM)	3,000 - 8,500
Dimensions (L x W x H)	w/ BL4040 : 425 x 117 x 162 mm (16-3/4 x 4-5/8 x 6-3/8") w/ BL4020 / BL4025 : 413 x 117 x 150 mm (16-1/4 x 4-5/8 x 5-7/8")
Net weight	2.9 - 3.4 kg (6.4 - 7.5 lbs.)

GA005G — Cordless Angle Grinder — 40V max

40Vmax XGT BL AFT Cordless Angle Grinder, Anti-Restart Function, Electric Brake, Slide Switch Lock-On



Wheel Diameter	125 mm (5")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	8,500
Dimensions (L x W x H)	w/ BL4040: 410 x 140 x 168 mm (16-1/8 x 5-1/2 x 6-5/8") w/ BL4020 / BL4025: 398 x 140 x 156 mm (15-5/8 x 5-1/2 x 6-1/8")
Net weight	2.9 - 3.6 kg (6.4 - 7.9 lbs.)

GA008G — Cordless Angle Grinder — 40V max

40Vmax XGT BL AFT Cordless Angle Grinder, Anti-Restart Function, Slide Switch Lock-On



Wheel Diameter	125 mm (5")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	8,500
Dimensions (L x W x H)	w/ BL4040: 410 x 140 x 165 mm (16-1/8 x 5-1/2 x 6-1/2") w/ BL4020 / BL4025: 398 x 140 x 152 mm (15-5/8 x 5-1/2 x 6")
Net weight	2.9 - 3.5 kg (6.4 - 7.7 lbs.)

GA013G — Cordless Angle Grinder — 40V max

40Vmax XGT BL AFT Cordless Angle Grinder, Anti-Restart Function, Electric Brake, Paddle Switch



Wheel Diameter	125 mm (5")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	8,500
Dimensions (L x W x H)	w/ BL4040: 410 x 140 x 168 mm (16-1/8 x 5-1/2 x 6-5/8") w/ BL4020 / BL4025: 398 x 140 x 156 mm (15-5/8 x 5-1/2 x 6-1/8")
Net weight	3.0 - 3.6 kg (6.6 - 7.9 lbs.)

GA023G — Cordless Angle Grinder — 40V max

40Vmax XGT BL AWS AFT Cordless Angle Grinder, Anti-Restart Function, Electric Brake, Slide Switch Lock-On



Wheel Diameter	125 mm (5")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	3,000 - 8,500
Dimensions (L x W x H)	w/ BL4040: 425 x 140 x 168 mm (16-3/4 x 5-1/2 x 6-5/8") w/ BL4020 / BL4025: 413 x 140 x 156 mm (16-1/4 x 5-1/2 x 6-1/8")
Net weight	3.0 - 4.4 kg (6.6 - 9.7 lbs.)

GA029G — Cordless Angle Grinder — 40V max

40Vmax XGT BL AWS AFT Cordless Angle Grinder, Anti-Restart Function, Electric Brake, Paddle Switch



Wheel Diameter	125 mm (5")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	3,000 - 8,500
Dimensions (L x W x H)	w/ BL4040 : 425 x 140 x 168 mm (16-3/4 x 5-1/2 x 6-5/8") w/ BL4020 / BL4025 : 413 x 140 x 156 mm (16-1/4 x 5-1/2 x 6-1/8")
Net weight	3.0 - 4.5 kg (6.6 - 9.9 lbs.)

LS003G — Cordless Slide Compound Miter Saw — 40V max

40Vmax XGT BL AWS Cordless 305 mm (12") Slide Compound Miter Saw, LED Light



Blade Diameter	305 mm (12")
Hole Diameter	25.4, 30 mm (1, 1-3/16")
Miter Angle	60° L 60° R
Bevel Angle	48° L 48° R
Max Cutting Capacity	0° Miter: 107 x 363 mm (4-1/4 x 14-1/4") 45° Miter, L/R: 107 x 255 mm (4-1/4 x 10")
No Load Speed (RPM)	3,600
Dimensions (L x W x H)	898 x 690 x 725 mm (35-1/4 x 27-1/4 x 28-1/2")
Net weight	30.5 - 31.1 kg (67.2 - 68.6 lbs.)

LS004G — Cordless Slide Compound Miter Saw — 40V max

40Vmax XGT BL AWS Cordless 260 mm (10-1/4") Slide Compound Miter Saw, LED Light



Blade Diameter	260 mm (10-1/4")
Hole Diameter	25.4, 30 mm (1, 1-3/16")
Miter Angle	60° L 60° R
Bevel Angle	48° L 48° R
Max Cutting Capacity	0° Miter: 91 x 279 mm (3-5/8 x 11") 45° Miter, L/R: 91 x 197 mm (3-5/8 x 7-3/4")
No Load Speed (RPM)	3,600
Dimensions (L x W x H)	805 x 644 x 660 mm (35-1/4 x 25-3/8 x 26")
Net weight	26.6 - 27.2 kg (58.6 - 60.0 lbs.)

LS002G — Cordless Slide Compound Miter Saw — 40V max

40Vmax XGT BL AWS Cordless 216 mm (8-1/2") Slide Compound Miter Saw, LED Light



Blade Diameter	216 mm (8-1/2")
Hole Diameter	25.4, 30 mm (1, 1-3/16")
Miter Angle	60 / 60° L 60, 60° R
Bevel Angle	48 / 48° L 48, 48° R
Max Cutting Capacity	0° Miter: 70 x 312 mm (2-3/4 x 12-1/4") 45° Miter, L/R: 70 x 220 mm (2-3/4 x 8-5/8")
No Load Speed (RPM)	4,800
Dimensions (L x W x H)	702 x 551 x 557 mm (27-5/8 x 21-3/4 x 22")
Net weight	16.4 - 17.0 kg (36.2 - 37.6 lbs.)

RS002G — Cordless Rear Handle Saw — 40V max

40Vmax XGT BL AWS Cordless 260 mm (10-1/4") Magnesium Rear Handle Saw, Electric Brake, Soft Start



Blade Diameter	260 mm (10-1/4")
Hole Diameter	15.88, 25, 25.4, 30 mm (5/8, 1, 1, 1-3/16")
Max Cutting Capacity	0°: 95 mm (3-3/4") 45°: 70 mm (2-3/4") 56°: 54.5 mm (2-1/8")
No Load Speed (RPM)	4,000
Dimensions (L x W x H)	489 x 193 x 309 mm (19-1/4 x 7-5/8 x 12-1/8")
Net weight	5.7 - 6.3 kg (12.6 - 13.9 lbs.)

RS001G — Cordless Rear Handle Saw — 40V max

40Vmax XGT BL ADT Cordless 185 mm (7-1/4") Magnesium Rear Handle Saw, Electric Brake, Soft Start



Blade Diameter	185 mm (7-1/4")
Hole Diameter	15.88, 19, 20, 30 mm (5/8, 3/4, 13/16, 1-3/16")
Max Cutting Capacity	0°: 65 mm (2-9/16") 45°: 45 mm (1-3/4") 53°: 38 mm (1-1/2")
No Load Speed (RPM)	6,400
Dimensions (L x W x H)	446 x 196 x 270 mm (17-1/2 x 7-3/4 x 10-5/8")
Net weight	5.0 - 5.6 kg (11.0 - 12.3 lbs.)