MAKITA POWER TOOLS
เครื่องมือไฟฟ้า "มากีต้า"

18V LITHIUM-ION LXT

Makita มากีต้า

DTW181 Cordless Impact Wrench 18V

18V LXT BL Brushless Cordless 1/2" (12.7 mm) 210 N·m (155 ft.lbs.) Impact Wrench, Reverse Rotation Auto Stop Mode



LXT BL MOTOR XPT

Fastening Capacities	Standard Bolt: M8 - M16 (5/16 - 5/8")
	High Strength Bolt: M6 - M12 (1/4 - 1/2")
Square Drive	12.7 mm (1/2")
No Load Speed (RPM)	Hard / Soft: 0 - 2,400 / 0 - 1,300
Impacts Per Minute (IPM)	Hard / Soft: 0 - 3,600 / 0 - 2,000
Max Fastening Torque	210 N·m (155 ft.lbs.)
Dimensions (L x W x H)	w/ BL1830B / BL1840B / BL1850B / BL1860B
	: 151 x 79 x 235 mm (5-15/16 x 3-1/8 x 9-1/4")
Net weight	1.2 - 1.5 kg (2.7 - 3.4 lbs.)

DTW190 Cordless Impact Wrench 18V

18V LXT Li-Ion Cordless 1/2" (12.7 mm) 190 N·m (140 ft.lbs.) Impact Wrench



LXT

Fastening Capacities	Standard Bolt: M8 - M16 (5/16 - 5/8")
	High Strength Bolt: M8 - M12 (5/16 - 1/2")
Square Drive	12.7 mm (1/2")
No Load Speed (RPM)	0 - 2,300
Impacts Per Minute (IPM)	0 - 3,000
Max Fastening Torque	190 N·m (140 ft.lbs.)
Overall Length	176 mm (6-15/16")
Net weight	1.4 - 1.8 kg (3.2 - 3.9 lbs.)

DTW180 Cordless Impact Wrench 18V

18V LXT BL Brushless Cordless 3/8" (9.5 mm) 180 N·m (130 ft.lbs.) Impact Wrench, Reverse Rotation Auto Stop Mode



LXT BL MOTOR XPT

Fastening Capacities	Standard Bolt: M8 - M16 (5/16" - 5/8")
	High Strength Bolt: M6 - M12 (1/4" - 1/2")
Square Drive	9.5 mm (3/8")
No Load Speed (RPM)	Hard / Soft: 0 - 2,400 / 0 - 1,300
Impacts Per Minute (IPM)	Hard / Soft: 0 - 3,600 / 0 - 2,000
Max Fastening Torque	180 N·m (130 ft.lbs.)
Vibration Level	Impact tightening of fasteners of the maximum capacity of the tool: 9.0 m/s²
Sound Pressure Level	89 dB(A)
Sound Power Level	100 dB(A)
Dimensions (L x W x H)	w/ BL1830B / BL1840B / BL1850B / BL1860B
	: 144x79x235 mm (5-5/8"x3-1/8"x9-1/4")
Net weight	1.2 - 1.5 kg (2.7 - 3.4 lbs.)

DDA450 Cordless Angle Drill 18V

18V LXT BL ADT Cordless 13 mm (1/2") Angle Drill with Keyed Chuck



LXT BL MOTOR ADT XPT

Capacity	Steel: 13 mm (1/2")
	Wood (Self-Feed Bit) Hi: 50 mm (2")
	Wood (Self-Feed Bit) Lo: 65 mm (2-9/16")
	Wood (Hole Saw) Hi: 101 mm (4")
	Wood (Hole Saw) Lo: 127 mm (5")
	Wood (Auger-Bit): 38 mm (1-1/2")
No Load Speed (RPM)	High / Low: 0 - 1,400 / 0 - 450
Max Fastening Torque	High: 48 N·m (430 in.lbs.), Low: 136 N·m (1,210 in.lbs.)
Dimensions (L x W x H)	434 x 85 x 193 mm (17-1/8 x 3-3/8 x 7-5/8")
Net weight	3.1 - 3.5 kg (6.8 - 7.7 lbs.)

DDA350 Cordless Angle Drill 18V

18V LXT Li-Ion Cordless 10 mm (3/8") Angle Drill, Keyless Chuck



LXT

Capacity	Steel: 10 mm (3/8")
	Wood: 25 mm (1")
No Load Speed (RPM)	0 - 1,800
Dimensions (L x W x H)	314 x 79 x 115 mm (12-3/8 x 3-1/8 x 4-1/2")
Net weight	1.5 - 1.8 kg (4.1 - 3.4 lbs.)

DDA351 Cordless Angle Drill 18V

18V LXT Li-Ion Cordless 10 mm (3/8") Angle Drill, Keyless Chuck



LXT

Capacity	Steel: 10 mm (3/8")
	Wood: 25 mm (1")
No Load Speed (RPM)	0 - 1,800
Dimensions (L x W x H)	326 x 79 x 115 mm (12-7/8 x 3-1/8 x 4-1/2")
Net weight	1.6 - 1.9 kg (4.2 - 3.5 lbs.)

DWR180 Cordless Ratchet Wrench 18V

18V LXT Li-Ion Cordless 47.5 N·m (420 in.lbs.) Ratchet



LXT XPT

Capacity	Standard Bolt: M5 - M12 (3/16 - 1/2")
	High Strength Bolt
	: M5 - M10 (3/16 - 3/8")
Square Drive	9.5 / 6.35 mm (3/8 / 1/4")
No Load Speed (RPM)	0 - 800
Max Fastening Torque	47.5 N·m (420 in.lbs.)
Dimensions (L x W x H)	w/ BL1830B / BL1840B / BL1850B / BL1860B
	: 369 x 79 x 87 mm (14-1/2 x 3-1/8 x 3-7/16")
Net weight	1.2 - 1.6 kg (2.6 - 3.5 lbs.)

DTL061 Cordless Angle Impact Driver 18V

18V LXT Li-Ion Cordless 60 N·m (530 in.lbs.) Angle Impact Driver



LXT

Capacity	Machine Screw: M4 - M8 (5/32 - 5/16")
	Standard Bolt: M4 - M12 (5/32 - 1/2")
	High Strength Bolt: M4 - M8 (5/32 - 5/16")
	Coarse thread (in length)
	: 22 - 75 mm (7/8 - 2-31/32")
Hex Shank	6.35 mm (1/4")
No Load Speed (RPM)	0 - 2,000
Impacts Per Minute (IPM)	0 - 3,000
Max Fastening Torque	60 N·m (530 in.lbs.)
Dimensions (L x W x H)	387 x 78 x 116 mm (15-1/4 x 3-1/16 x 4-9/16")
Net weight	1.4 - 2 kg (3.1 - 4.3 lbs.)

DTL063Z Cordless Angle Impact Driver 18V

18V LXT Li-Ion Cordless 3/8" (9.5 mm) 60 N·m Angle Impact Wrench



LXT

Fastening Capacities	Standard Bolt: M4 - M12 (5/32 - 1/2")
	High Strength Bolt: M4 - M8 (5/32 - 5/16")
Square Drive	9.5 mm (3/8")
No Load Speed (RPM)	0 - 2,000
Impacts Per Minute (IPM)	0 - 3,000
Max Fastening Torque	60 N·m
Dimensions (L x W x H)	387 x 78 x 116 mm (15-1/4 x 3-1/16 x 4-9/16")
Net weight	1.4 - 2.0 kg (3.1 - 4.3 lbs.)

DFS452 Cordless Screwdriver 18V

18V LXT BL Brushless Cordless 0-4,000 RPM Push Drive Technology Screwdriver, LED Light, Silent Clutch



LXT BL MOTOR XPT

Capacity	Self-Drilling Screw: 6 mm (1/4")
	Drywall Screw: 5 mm (3/16")
Driving Shank (Hex)	6.35 mm (1/4")
No Load Speed (RPM)	0 - 4,000
Dimensions (L x W x H)	251 x 79 x 259 mm (10 x 3-1/8 x 11-1/4")
Net weight	1.5 - 1.8 kg (3.2 - 3.9 lbs.)

DFS250 Cordless Screwdriver 18V

18V LXT BL Brushless Cordless 0-4,000 RPM Push Drive Technology Screwdriver, LED Light, Silent Clutch



LXT BL MOTOR

Capacity	Coarse Thread: 4.5 x 90 mm (3/16 x 3-1/2")
	Self-Drilling Screw: 6 mm (1/4")
	Drywall Screw: 5 mm (3/16")
Driving Shank (Hex)	6.35 mm (1/4")
No Load Speed (RPM)	0 - 2,500
Dimensions (L x W x H)	259 x 79 x 259 mm (10-1/4 x 3-1/8 x 10-1/4")
Net weight	1.5 - 1.9 kg (3.4 - 4.1 lbs.)

DUT130 Cordless Mixer 18V

18V LXT BL Brushless 165 mm (6-1/2") Variable 2-Speed Mixer



LXT BL MOTOR XPT

Blade Diameter	165 mm (6-1/2")
Shank size of tool holder portion	M12 or M14
No Load Speed (RPM)	High / Low: 0 - 1,300 / 0 - 350
Dimensions (L x W x H)	w/ Mixing Blade
	: 916 x 89 x 231 mm (36 x 3-1/2 x 9-1/8")
	w/o Mixing Blade
	: 320 x 89 x 231 mm (12-5/8 x 3-1/2 x 9-1/8")
Net weight	2.5 - 2.8 kg (5.6 - 6.3 lbs.)