MAKITA POWER TOOLS
เครื่องมือไฟฟ้า “มากีต้า”

18V LITHIUM-ION LXT

makita มากีต้า

DDF486 Cordless Driver Drill 18V

18V LXT BL Brushless Cordless
13 mm (1/2") 125 N·m (1,100 in.lbs.)
Driver Drill



LXT BL MOTOR XPT

Capacity	Steel: 13 mm (1/2"), Wood (Auger-Bit): 50 mm (2")
	Wood (Self-Feed Bit): 76 mm (3")
	Wood (Hole Saw): 152 mm (6")
	Siding Board: 170 mm (6-11/16")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High / Low: 0 - 2,100 / 0 - 550
Max Fastening Torque	Hard / Soft: 130 / 65 N·m (1,150 / 580 in.lbs.)
Max Lock Torque	125 N·m (1,100 in.lbs.)
Dimensions (L x W x H)	w/ BL1830B / BL1840B / BL1850B / BL1860B
	: 178 x 81 x 265 mm (7 x 3-3/16 x 10-3/8")
Net weight	2.3 - 2.6 kg (5.1 - 5.7 lbs.)

DDF484 Cordless Driver Drill 40V

18V LXT BL Brushless Cordless
13 mm (1/2") 60 N·m (530 in.lbs.)
Driver Drill



LXT BL MOTOR XPT

Capacity	Steel / Wood: 13 / 38 mm (1/2 / 1-1/2")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High / Low: 0 - 2,000 / 0 - 500
Max Fastening Torque	Hard / Soft: 54 / 30 N·m (480 / 270 in.lbs.)
Max Lock Torque	60 N·m (530 in.lbs.)
Dimensions (L x W x H)	172 x 79 x 261 mm
	(6-3/4 x 3-1/8 x 10-1/4")
Net weight	1.5 - 1.8 kg (3.3 - 4.0 lbs.)

DDF487 Cordless Driver Drill 18V

18V LXT BL Brushless Cordless
13 mm (1/2") 40 N·m (350 in.lbs.)
Driver Drill



LXT BL MOTOR XPT

Capacity	Steel / Wood: 13 / 36 mm (1/2 / 1-7/16")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High / Low: 0 - 1,700 / 0 - 500
Max Fastening Torque	Hard / Soft: 40 / 23 N·m (350 / 210 in.lbs.)
Max Lock Torque	40 N·m (350 in.lbs.)
Dimensions (L x W x H)	w/ BL1830B / BL1840B / BL1850B / BL1860B
	: 157 x 81 x 248 mm (6-3/16 x 3-3/16 x 9-3/4")
Net weight	1.3 - 1.6 kg (2.9 - 3.5 lbs.)

DDF458 Cordless Driver Drill 18V

18V LXT Li-Ion Cordless
13 mm (1/2") 84 N·m (750 in.lbs.)
Driver Drill



LXT XPT

Capacity	Steel: 13 mm (1/2")
	Wood: 76 mm (3")
	Masonry: 16 mm (5/8")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High: 0 - 2,000, Low: 0 - 400
Impacts Per Minute (IPM)	High: 0 - 30,000, Low: 0 - 6,000
Max Fastening Torque	Hard / Soft: 91 / 58 N·m
Max Lock Torque	84 N·m (750 in.lbs.)
Dimensions (L x W x H)	225 x 79 x 259 mm (8-7/8 x 3-1/8 x 10-1/4")
Net weight	2.2 - 2.6 kg (4.9 - 5.7 lbs.)

DDF482 Cordless Driver Drill 18V

18V LXT Li-Ion Cordless
13 mm (1/2") 54 N·m (480 in.lbs.)
Driver Drill



LXT XPT

Capacity	Steel / Wood: 13 / 36 mm (1/2" / 1-7/16")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High / Low: 0 - 1,700 / 0 - 500
Max Fastening Torque	Hard / Soft: 40 / 23 N·m (350 / 210 in.lbs.)
Max lock torque	40 N·m (350 in.lbs.)
Vibration Level	Drilling into Metal: 2.5 m/s² or less
Sound Pressure Level	77 dB(A)
Dimensions (L x W x H)	162x79x247 mm (6-3/8"x3-1/8"x9-3/4")
Net weight	1.2 - 1.6 kg (2.7 - 3.4 lbs.)

DDF453 Cordless Driver Drill 18V

18V LXT Li-Ion Cordless
13 mm (1/2") 38 N·m (340 in.lbs.)
Driver Drill



LXT

Capacity	Steel: 13 mm (1/2")
	Wood: 36 mm (1-7/16")
No Load Speed (RPM)	High: 0 - 1,300
	Low: 0 - 400
Max Fastening Torque	Hard / Soft: 42 / 27 N·m
Max Lock Torque	38 N·m (340 in.lbs.)
Dimensions (L x W x H)	222 x 79 x 244 mm (8-3/4 x 3-1/8 x 9-5/8")
Net weight	1.7 - 2 kg (3.7 - 4.4 lbs.)

DHP486 Cordless Driver Drill 18V

18V LXT BL Brushless Cordless
13 mm (1/2") 125 N·m (1,100 in.lbs.)
Hammer Driver Drill



LXT BL MOTOR XPT

Capacity	Steel: 13 mm (1/2")
	Wood (Auger-Bit): 50 mm (2")
	Wood (Self-Feed Bit): 76 mm (3")
	Siding Board: 170 mm (6-11/16")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Impacts Per Minute (IPM)	High / Low: 0 - 31,500 / 0 - 8,250
No Load Speed (RPM)	High / Low: 0 - 2,100 / 0 - 550
Max Fastening Torque	Hard / Soft: 130 / 65 N·m (1,150 / 580 in.lbs.)
Max Lock Torque	125 N·m (1,100 in.lbs.)
Dimensions (L x W x H)	w/ BL1830B / BL1840B / BL1850B / BL1860B: 178 x 81 x 265 mm (7 x 3-3/16 x 10-3/8")
Net weight	2.3 - 2.7 kg (5.1 - 6.0 lbs.)

DHP487 Cordless Driver Drill 18V

18V LXT BL Brushless Cordless
13 mm (1/2") 40 N·m (350 in.lbs.)
Hammer Driver Drill



LXT BL MOTOR XPT

Capacity	Steel / Wood / Masonry
	: 13 / 36 / 13 mm (1/2 / 1-7/16 / 1/2")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Impacts Per Minute (IPM)	High / Low: 0 - 25,500 / 0 - 7,500
No Load Speed (RPM)	High / Low: 0 - 1,700 / 0 - 500
Max Fastening Torque	Hard / Soft: 40 / 23 N·m (350 / 210 in.lbs.)
Max Lock Torque	40 N·m (350 in.lbs.)
Dimensions (L x W x H)	w/ BL1830B / BL1840B / BL1850B / BL1860B
	: 164 x 81 x 248 mm (6-1/2 x 3-3/16 x 9-3/4")
Net weight	1.4 - 1.7 kg (3.1 - 3.8 lbs.)

DHP458 Cordless Driver Drill 18V

18V LXT Li-Ion Cordless
13 mm (1/2") 84 N·m (750 in.lbs.)
Hammer Driver Drill



LXT XPT

Capacity	Steel: 13 mm (1/2")
	Wood: 76 mm (3")
	Masonry: 16 mm (5/8")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
No Load Speed (RPM)	High: 0 - 2,000, Low: 0 - 400
Impacts Per Minute (IPM)	High: 0 - 30,000, Low: 0 - 6,000
Max Fastening Torque	Hard / Soft: 91 / 58 N·m
Max Lock Torque	84 N·m (750 in.lbs.)
Dimensions (L x W x H)	225 x 79 x 259 mm (8-7/8 x 3-1/8 x 10-1/4")
Net weight	2.2 - 2.6 kg (4.9 - 5.7 lbs.)

DHP482 Cordless Driver Drill 18V

18V LXT Li-Ion Cordless
13 mm (1/2") 54 N·m (480 in.lbs.)
Hammer Driver Drill



LXT XPT

Capacity	Steel / Wood / Masonry
	: 13 / 38 / 13 mm (1/2 / 1-1/2 / 1/2")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Impacts Per Minute (IPM)	High / Low: 0 - 28,500 / 0 - 9,000
No Load Speed (RPM)	High / Low: 0 - 1,900 / 0 - 600
Max Fastening Torque	Hard / Soft: 62 / 36 N·m (550 / 320 in.lbs.)
Max Lock Torque	54 N·m (480 in.lbs.)
Dimensions (L x W x H)	198 x 79 x 249 mm (7-3/4 x 3-1/8 x 9-3/4")
Net weight	1.5 - 1.8 kg (3.4 - 4.1 lbs.)

DHP453 Cordless Hammer Driver Drill 18V

18V LXT BL Brushless Cordless
13 mm (1/2") 38 N·m (340 in.lbs.)
Hammer Driver Drill I



LXT

Capacity	Steel / Wood / Masonry
	: 13 / 36 / 13 mm (1/2" / 1-7/16" / 1/2")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Impacts Per Minute (IPM)	High: 0 - 19,500
	Low: 0 - 6,000
No Load Speed (RPM)	High: 0 - 1,300
	Low: 0 - 400
Max Fastening Torque	Hard / Soft: 42 / 27 N·m
Max Lock Torque	38 N·m (340 in.lbs.)
Dimensions (L x W x H)	240 x 79 x 244 mm (9-7/16 x 3-1/8 x 9-5/8")
Net weight	1.7 - 2 kg (3.6 - 4.4 lbs.)

DDF083 Cordless Driver Drill 18V

18V LXT BL Brushless Cordless
6.35 mm (1/4") Hex 40 N·m (350 in.lbs.)
Driver Drill



LXT BL MOTOR XPT

Capacity	Steel / Wood: 13 / 36 mm (1/2 / 1-7/16")
Chuck Capacity	6.35 mm (1/4")
No Load Speed (RPM)	High / Low: 0 - 1,700 / 0 - 500
Max Fastening Torque	Hard / Soft: 40 / 23 N·m (350 / 210 in.lbs.)
Max Lock Torque	40 N·m (350 in.lbs.)
Dimensions (L x W x H)	124 x 79 x 247 mm (4-7/8 x 3-1/8 x 9-3/4")
Net weight	1.1 - 1.4 kg (2.4 - 3.0 lbs.)