MAKITA POWER TOOLS
เครื่องมือไฟฟ้า “มากีต้า”

มากีต้า

HS7010 Circular Saw

185 mm (7-1/4") / 190 mm (7-1/2") 1,600 W Circular Saw



Continuous rating Input	1,600W
Blade Diameter	185 / 190 mm (7-1/4 / 7-1/2")
Hole Diameter	15.88, 20, 30 mm (5/8, 13/16, 1-3/16")
Max Cutting Capacity	0° : 65, 67 mm (2-9/16, 2-5/8")
	45° : 44, 45 mm (1-3/4, 1-3/4")
No Load Speed (RPM)	5,500
Dimensions (L x W x H)	300 x 240 x 261 mm
	(11-3/4 x 9-1/2 x 10-1/4")
Net weight	4 kg (8.9 lbs.)
Power supply cord	2.5 m (8.2 ft)

5007NF Circular Saw

185 mm (7-1/4") 1,800 W Circular Saw with Dual LED Lights



Continuous rating Input	1,800W
Blade Diameter	185 mm (7-1/4")
Hole Diameter	15.88, 20, 30 mm (5/8, 13/16, 1-3/16")
Max Cutting Capacity	0° : 63.5 mm (2-1/2")
	45° : 45 mm (1-3/4")
	50° : 35 mm (1-3/8")
No Load Speed (RPM)	5,800
Dimensions (L x W x H)	317 x 240 x 265 mm
	(12-1/2 x 9-1/2 x 10-3/8")
Net weight	5 kg (11 lbs.)
Power supply cord	2.5 m (8.2 ft)

5008MG Circular Saw

210 mm (8-1/4") 1,800 W Magnesium Circular Saw with Dual LED Lights



Continuous rating Input	1,800W
Blade Diameter	210 mm (8-1/4")
Hole Diameter	15.88, 20, 25, 25.4, 30 mm
	(5/8, 13/16, 1, 1-3/16")
Max Cutting Capacity	0°: 75.5 mm (3")
	45°: 57 mm (2-1/4")
	50°: 51.5 mm (2")
No Load Speed (RPM)	5,200
Dimensions (L x W x H)	332 x 243 x 277 mm
	(13-1/8 x 9-9/16 x 10-7/8")
Net weight	4.8 kg (10.6 lbs.)
Power supply cord	2.5 m (8.2 ft)

N5900B Circular Saw

235 mm (9-1/4") 2,000 W Circular Saw



Continuous rating Input	2,000W
Blade Diameter	235 mm (9-1/4")
Hole Diameter	25 mm (1")
Max Cutting Capacity	0° : 85 mm (3-3/8")
	45° : 60 mm (2-3/8")
	50° : 53 mm (2-1/16")
No Load Speed (RPM)	4,100
Overall Length	380 mm (15")
Net weight	6.8 kg (14.8 lbs.)
Power supply cord	2.5 m (8.2 ft)

HS0600 Circular Saw

260 mm (10-1/4") / 270 mm (10-5/8") 2,000 W Circular Saw



Continuous rating Input	2,000W
Blade Diameter	260 / 270 mm (10-1/4 / 10-5/8")
Hole Diameter	15.88, 25, 25.4, 30 mm (5/8, 1, 1-3/16")
Max Cutting Capacity	0° : 97, 101 mm (3-13/16, 4")
	45° : 68, 71 mm (2-11/16, 2-13/16")
	50° : 61, 63 mm (2-3/8, 2-1/2")
No Load Speed (RPM)	4,300
Dimensions (L x W x H)	418 x 273 x 324 mm
	(16-1/2 x 10-3/4 x 12-3/4")
Net weight	6.9 kg (15.2 lbs.)
Power supply cord	2.5 m (8.2 ft)

5103N Circular Saw

335 mm (13-1/8") 1,750 W Circular Saw



Continuous rating Input	1,750W
Blade Diameter	335 mm (13-1/8")
Hole Diameter	25, 25.4 mm (1")
Max Cutting Capacity	0° : 128 mm (5")
	45° : 91 mm (3-5/8")
No Load Speed (RPM)	2,900
Overall Length	505 mm (19-7/8")
Net weight	8.9 kg (19.6 lbs.)
Power supply cord	5.0 m (16.4 ft)

5402 Circular Saw

415 mm (16-5/16") Circular Saw



Continuous Rating Input	1,450W
Blade Diameter	415 mm (16-5/16")
Hole Diameter	25, 25.4 mm (1")
Max Cutting Capacity	0° : 157 mm (6-3/16")
	45° : 106 mm (4-3/16")
No Load Speed (RPM)	2,200
Overall Length	615 mm (24-1/4")
Net weight	12.9 kg (28.4 lbs.)
Power supply cord	5.0 m (16.4 ft)

LS1440 Miter Saw

355 mm (14") 1,380 W Miter Saw



Continuous rating Input	1,380W
Blade Diameter	355 mm (14")
Hole Diameter	25, 25.4 mm (1")
Max Cutting Capacity	0° : 122 x 152 mm (4-13/16 x 6")
	45° : 122 x 115 mm (4-13/16 x 4-1/2")
No Load Speed (RPM)	3,200
Dimensions (L x W x H)	530 x 596 x 435 mm
	(20-7/8 x 23-1/2 x 17-1/8")
Hole Diameter	25, 25.4 mm (1")
Net weight	34.2 kg (75.4 lbs.)
Power supply cord	2.5 m (8.2 ft)

2712 Table Saw

315 mm (12-3/8") Table Saw



Blade Diameter	315 mm (12-3/8")
Hole Diameter	30.0 mm (1-3/16")
Max Cutting Capacity	0° : 85 mm (3-3/8")
	45° : 58 mm (2-1/4")
No Load Speed (RPM)	2,950, 3,400
Bevel Capacity	0 - 45°
Dimensions (L x W x H)	1,670 x 700 x 810 mm
	(65-3/4 x 27-1/2 x 32")
Net weight	54 kg (118.9 lbs.)
Power supply cord	3.0 m (9.8 ft)

MLT100/MLT100S Table Saw

260 mm (10-1/4") 1,500 W Table Saw



Continuous rating Input	1,500W
Blade Diameter	260 mm (10-1/4")
Hole Diameter	25.4, 30 mm (1, 1-3/16")
Max Cutting Capacity	0° : 93 mm (3-5/8") /
No Load Speed (RPM)	4,300
Bevel Capacity	0 - 45° 45° : 64 mm (2-1/2")
Max Cutting Width	on the right side of blade: 630 mm (24-3/4")
Distance from blade to the left end of table	530 mm (20-7/8")
Table Size (L x W)	Main table: 620 x 610 mm (24-3/8 x 24")
	Sub table (right extension): 620 x 150 mm (24-3/8 x 5-7/8")
	Sub table (left extension): 620 x 200 mm (24-3/8 x 7-7/8")
Net weight	34.8 - 35.1 kg (76.7 - 77.4 lbs.)
Power supply cord	2.5 m (8.2 ft)

LS0815FL Slide Compound Miter Saw

216 mm (8-1/2") 1,400 W Slide Compound Miter Saw, Laser, LED Light



Continuous rating Input	1,400W
Blade Diameter	216 mm (8-1/2")
Bevel Angle	48 / 5° L 48, 5° R
Miter Angle	50 / 60° L 50, 60° R
Max Cutting Capacity	0° Miter : 65 x 305 mm (2-9/16 x 12")
	45° Miter, L/R: 65 x 215 mm
	(2-9/16 x 8-1/2")
No Load Speed (RPM)	5,000
Dimensions (L x W x H)	755 x 450 x 488 mm
	(29-3/4 x 17-3/4 x 19-1/4")
Net weight	14.1 kg (31.1 lbs.)
Power supply cord	2.5 m (8.2 ft)

LS1017L Slide Compound Saw

260 mm (10-1/4") 1,430 W Slide Compound Miter Saw, Laser



Continuous rating Input	1,430W
Blade Diameter	260 mm (10-1/4")
Miter Angle	47 / 60° L 47, 60° R
Bevel Angle	45 / 5° L 45, 5° R
Max Cutting Capacity	0°: 91 x 305 mm (3-5/8 x 12")
	45°: 91 x 215 mm (3-5/8 x 8-1/2")
No Load Speed (RPM)	4,200
Dimensions (L x W x H)	825 x 536 x 581 mm
	(32-1/2 x 21-1/8 x 22-7/8")
Net weight	19.5 kg (43 lbs.)
Power supply cord	2.5 m (8.2 ft)