# MAKITA POWER TOOLS
# เครื่องมือไฟฟ้า "มากีต้า"

มากีต้า

## DA4000LR Angle Drill

**13 mm (1/2") 710 W Angle Drill with Keyed Chuck**



303

| | |
|---|---|
| Continuous rating Input | 710W |
| Capacity | Steel: 13 mm (1/2") |
| | Wood (Self-Feed Bit): 118 mm (4-5/8") |
| | Wood (Self-Feed Bit) Hi: 65 mm (2-9/16") |
| | Wood (Self-Feed Bit) Lo: 118 mm (4-5/8") |
| | Wood (Hole Saw) Hi: 114 mm (4-1/2") |
| | Wood (Hole Saw) Lo: 152 mm (6") |
| Chuck Capacity | 2 - 13 mm (1/16 - 1/2") |
| No Load Speed (RPM) | High: 0 - 900 |
| | Low: 0 - 400 |
| Overall Length | 413 mm (16-1/4") |
| Net weight | 4 kg (8.9 lbs.) |
| Power supply cord | 2.5 m (8.2 ft) |

## DF0300 Driver Drill

**10 mm (3/8") 320 W Driver Drill with Keyless Chuck**



411

| | |
|---|---|
| Continuous rating Input | 320W |
| Capacity | Steel: 10 mm (3/8") |
| | Wood: 28 mm (1-1/8") |
| Chuck Capacity | 1.0 - 10 mm (1/32 - 3/8") |
| No Load Speed (RPM) | High: 0 - 1,500 |
| | Low: 0 - 450 |
| Max Fastening Torque | Hard / Soft: 56.0 / 21.0 N·m (500 / 190 in.lbs.) |
| Max Lock Torque | 42.0 N·m (370 in.lbs.) |
| Dimensions (L x W x H) | 220 x 67 x 206 mm (8-5/8 x 2-5/8 x 8-1/8") |
| Net weight | 1.2 kg (2.7 lbs.) |
| Power supply cord | 2.5 m (8.2 ft) |

## DP2010 High Speed Drill

**6.5 mm (1/4") 370 W High Speed Variable Speed Reversing Drill with Keyed Chuck**



419

| | |
|---|---|
| Continuous rating Input | 370W |
| Capacity | Steel: 6.5 mm (1/4") |
| | Wood: 15 mm (9/16") |
| | Wood (Self-Feed Bit): 30 mm (1-3/16") |
| Chuck Capacity | 0.5 - 6.5mm (1/64 - 1/4") |
| No Load Speed (RPM) | 0 - 4,200 |
| Dimensions (L x W x H) | 209 x 64 x 175 mm (8-1/4 x 2-1/2 x 6-7/8") |
| Net weight | 1 kg (2.2 lbs.) |
| Power supply cord | 2.0 m (6.6 ft) |

## 6412 Drill

**10 mm (3/8") 450 W Variable Speed Reversing Drill with Keyed Chuck**



64

| | |
|---|---|
| Continuous rating Input | 450W |
| Capacity | Steel: 10 mm (3/8") |
| | Wood: 25 mm (1") |
| | Wood (Self-Feed Bit): 50 mm (2") |
| Chuck Capacity | 1.5 - 10 mm (1/16 - 3/8") |
| No Load Speed (RPM) | 0 - 3,400 |
| Dimensions (L x W x H) | 228 x 64 x 183 mm (9 x 2-1/2 x 7-1/4") |
| Net weight | 1.3 kg (2.9 lbs.) |
| Power supply cord | 2.0 m (6.6 ft) |

## 6413 Drill

**10 mm (3/8") 450 W Variable Speed Reversing Drill with Keyless Chuck**



64

| | |
|---|---|
| Continuous rating Input | 450W |
| Capacity | Steel: 10 mm (3/8") |
| | Wood: 25 mm (1") |
| | Wood (Self-Feed Bit): 50 mm (2") |
| Chuck Capacity | 1.5 - 10 mm (1/16 - 3/8") |
| No Load Speed (RPM) | 0 - 3,400 |
| Dimensions (L x W x H) | 234 x 64 x 183 mm (9-1/4 x 2-1/2 x 7-1/4") |
| Net weight | 1.3 kg (2.9 lbs.) |
| Power supply cord | 2.0 m (6.6 ft) |

## DA3010 Angle Drill

**10 mm (3/8") 450 W Angle Drill with Keyed Chuck**



419

| | |
|---|---|
| Continuous rating Input | 450W |
| Capacity | Steel: 10 mm (3/8") |
| | Wood: 25 mm (1") |
| | Wood (Self-Feed Bit): 50 mm (2") |
| Chuck Capacity | 1.5 - 10 mm (1/16 - 3/8") |
| No Load Speed (RPM) | 0 - 2,400 |
| Overall Length | 270 mm (10-5/8") |
| Net weight | 1.6 kg (3.5 lbs.) |
| Power supply cord | 2.5 m (8.2 ft) |

## DP4010 2-Speed Drill

**13 mm (1/2") 720 W Variable 2-Speed Reversing Drill with Keyed Chuck**



419

| | |
|---|---|
| Continuous rating Input | 720W |
| Capacity | Steel: 13 mm (1/2") |
| | Steel Hi: 8 mm (5/16") |
| | Steel Lo: 13 mm (1/2") |
| | Wood Hi: 25 mm (1") |
| | Wood Lo: 40 mm (1-9/16") |
| | Wood (Self-Feed Bit): 90 mm (3-1/2") |
| Chuck Capacity | 1.5 - 13.0 mm (1/16 - 1/2") |
| No Load Speed (RPM) | High: 0 - 2,900 |
| | Low: 0 - 1,200 |
| Dimensions (L x W x H) | 347 x 70 x 220 mm (13-5/8 x 2-3/4 x 8-5/8") |
| Net weight | 2.3 kg (5 lbs.) |
| Power supply cord | 2.5 m (8.2 ft) |

## DP4011 2-Speed Drill

**13 mm (1/2") 720 W Variable 2-Speed Reversing Drill with Keyless Chuck**



419

| | |
|---|---|
| Continuous rating Input | 720W |
| Capacity | Steel: 13 mm (1/2") |
| | Steel Hi: 8 mm (5/16") |
| | Steel Lo: 13 mm (1/2") |
| | Wood Hi: 25 mm (1") |
| | Wood Lo: 40 mm (1-9/16") |
| | Wood (Self-Feed Bit): 90 mm (90") |
| Chuck Capacity | 1.5 - 13.0 mm (1/16 - 1/2") |
| No Load Speed (RPM) | High: 0 - 2,900 |
| | Low: 0 - 1,200 |
| Dimensions (L x W x H) | 347 x 70 x 220 mm (13-5/8 x 2-3/4 x 8-5/8") |
| Net weight | 2.3 kg (5 lbs.) |
| Power supply cord | 2.5 m (8.2 ft) |

## DP4700 Drill

**13 mm (1/2")**



64

| | |
|---|---|
| Continuous rating input | 510W |
| Capacity | Steel: 13 mm (1/2") |
| | Wood: 36 mm (1-3/8") |
| No Load Speed (RPM) | 0-550 |
| Overall Length | 275 mm (10-7/8") |
| Net weight | 2.2 kg (4.8 lbs.) |
| Power supply cord | 2.5 m (8.2 ft) |

## HP0300 Hammer Driver Drill

**10 mm (3/8") 320 W Hammer Driver Drill with Keyless Chuck**



411

| | |
|---|---|
| Continuous rating Input | 320W |
| Capacity | Concrete: 8 mm (5/16") |
| | Steel: 10 mm (3/8") |
| | Wood: 28 mm (1-1/8") |
| Chuck Capacity | 1.0 - 10 mm (1/32 - 3/8") |
| Blows Per Minute (BPM) | High: 0 - 22,500 |
| | Low: 0 - 6,750 |
| No Load Speed (RPM) | High: 0 - 1,500 |
| | Low: 0 - 450 |
| Max Fastening Torque | Hard / Soft: 56.0 / 21.0 N·m (500 / 190 in.lbs.) |
| Max Lock Torque | 42.0 N·m (370 in.lbs.) |
| Dimensions (L x W x H) | 235 x 67 x 206 mm (9-1/4 x 2-5/8 x 8-1/8") |
| Net weight | 1.3 kg (2.8 lbs.) |
| Power supply cord | 2.5 m (8.2 ft) |

## HP1230 Hammer Drill

**12 mm (15/32") 400 W Hammer Drill with Keyed Chuck**



419

| | |
|---|---|
| Continuous rating Input | 400W |
| Capacity | Concrete: 12 mm (15/32") |
| | Steel: 10 mm (3/8") |
| | Wood: 15 mm (9/16") |
| | Wood (Self-Feed Bit): 30 mm (1-3/16") |
| | Masonry: 12 mm (15/32") |
| Chuck Capacity | 1.5 - 10 mm (1/16 - 3/8") |
| Blows Per Minute (BPM) | 0 - 31,900 |
| No Load Speed (RPM) | 0 - 2,900 |
| Dimensions (L x W x H) | 239 x 67 x 188 mm |
| | (9-3/8 x 2-5/8 x 7-3/8") |
| Net weight | 1.7 kg (3.7 lbs.) |
| Power supply cord | 2.0 m (6.6 ft) |

## HP1630 Hammer Drill

**16 mm (5/8") 710 W Hammer Drill with Keyed Chuck**



85

| | |
|---|---|
| Continuous rating Input | 710W |
| Capacity | Concrete: 16 mm (5/8") |
| | Steel: 13 mm (1/2") |
| | Wood: 30 mm (1-3/16") |
| | Wood (Self-Feed Bit): 60 mm (2-3/8") |
| | Masonry: 16 mm (5/8") |
| Chuck Capacity | 1.5 - 13 mm (1/16 - 1/2") |
| Blows Per Minute (BPM) | 0 - 48,000 |
| No Load Speed (RPM) | 0 - 3,200 |
| Dimensions (L x W x H) | 296 x 75 x 204 mm (11-5/8 x 2-15/16 x 8") |
| Net weight | 2.1 kg (4.6 lbs.) |
| Power supply cord | 2.0 m (6.6 ft) |