MAKITA POWER TOOLS
เครื่องมือไฟฟ้า "มากีต้า"

มากีต้า

HP2050 2-Speed Hammer Drill

20 mm (3/4") 720 W 2-Speed Hammer Drill with Keyed Chuck



419

Continuous rating Input	720W
Capacity	Concrete: 20 mm (3/4")
	Steel Hi: 8 mm (5/16")
	Steel Lo: 13 mm (1/2")
	Wood Hi: 25 mm (1")
	Wood Lo: 40 mm (1-9/16")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Impacts Per Minute (IPM)	High: 0 - 58,000
	Low: 0 - 24,000
No Load Speed (RPM)	High: 0 - 2,900
Overall Length	362 mm (14-1/4")
Net weight	2.5 kg (5.6 lbs.)
Power supply cord	2.5 m (8.2 ft)

HP2051 2-Speed Hammer Drill

20 mm (3/4") 720 W 2-Speed Hammer Drill with Keyless Chuck



419

Continuous rating Input	720W
Capacity	Concrete: 20 mm (3/4")
	Steel Hi: 8 mm (5/16")
	Steel Lo: 13 mm (1/2")
	Wood Hi: 25 mm (1")
	Wood Lo: 40 mm (1-9/16")
Chuck Capacity	1.5 - 13 mm (1/16 - 1/2")
Impacts Per Minute (IPM)	High: 0 - 58,000
	Low: 0 - 24,000
No Load Speed (RPM)	High: 0 - 2,900
Overall Length	360 mm (14-1/8")
Net weight	2.5 kg (5.6 lbs.)
Power supply cord	2.5 m (8.2 ft)

FS4200 Drywall Screwdriver

570 W 0-4,000 RPM Drywall Screwdriver with LED Light



419

Dimensions: for countries providing noise suppressor and connect bit 60

Continuous rating Input	570W
Capacity	Drywall Screw: 5 mm (3/16")
	Self-Drilling Screw: 6 mm (1/4")
Driving Shank (Hex)	6.35 mm (1/4")
No Load Speed (RPM)	0 - 4,000
Dimensions (L x W x H)	269 x 65 x 207 mm
	(10-5/8 x 2-9/16 x 8-1/8")
Net weight	1.4 kg (3 lbs.)
Power supply cord	2.5 m (8.2 ft)

FS6300 Drywall Screwdriver

570 W 0-6,000 RPM Drywall Screwdriver with LED Light, Silent Clutch



419

Dimensions: for countries providing noise suppressor and connect bit 60

Continuous rating Input	570W
Capacity	Drywall Screw: 4 mm (5/32")
Driving Shank (Hex)	6.35 mm (1/4")
No Load Speed (RPM)	0 - 6,000
Dimensions (L x W x H)	279 x 65 x 207 mm (11 x 2-9/16 x 8-1/8")
Net weight	1.4 kg (3.1 lbs.)
Power supply cord	2.5 m (8.2 ft)

TD0100 Impact Driver

100 N·m (74 ft.lbs.) Impact Driver



419

Continuous rating Input	230W
Capacity	Machine Screw: M4 - M8 (5/32 - 5/16")
	Standard Bolt: M5 - M14 (3/16 - 9/16")
	High Strength Bolt: M5 - M10 (3/16 - 3/8")
	Coarse thread (in length)
	: 22 - 90 mm (7/8 - 3-1/2")
Driving Shank (Hex)	6.35 mm (1/4")
No Load Speed (RPM)	0 - 3,600
Impacts Per Minute (IPM)	0 - 3,200
Max Fastening Torque	100 N·m (74 ft.lbs.)
Dimensions (L x W x H)	218 x 60 x 180 mm (8-5/8 x 2-3/8 x 7-1/8")
Net weight	0.96 kg (2.1 lbs.)
Power supply cord	2.5 m (8.2 ft)

TD0101F Impact Driver

100 N·m (74 ft.lbs.) Impact Driver with LED Light



411

Continuous rating Input	230W
Capacity	Machine Screw: M4 - M8 (5/32 - 5/16")
	Standard Bolt: M5 - M14 (3/16 - 9/16")
	High Strength Bolt: M5 - M10 (3/16 - 3/8")
	Coarse thread (in length)
	: 22 - 90 mm (7/8 - 3-1/2")
Driving Shank (Hex)	6.35 mm (1/4")
No Load Speed (RPM)	0 - 3,600
Impacts Per Minute (IPM)	0 - 3,200
Max Fastening Torque	100 N·m (74 ft.lbs.)
Dimensions (L x W x H)	184 x 67 x 192 mm (7-1/4 x 2-5/8 x 7-9/16")
Net weight	0.99 kg (2.2 lbs.)
Power supply cord	2.5 m (8.2 ft)

6952 Impact Driver

120 N·m (88.5 ft.lbs.) Impact Driver



411

Continuous rating Input	270W
Capacity	Machine Screw: M4 - M10 (5/32 - 3/8")
	Standard Bolt: M6 - M14 (7/32 - 9/16")
	High Strength Bolt: M6 - M10 (7/32 - 3/8")
Driving Shank (Hex)	6.35 mm (1/4")
No Load Speed (RPM)	0 - 3,200
Impacts Per Minute (IPM)	0 - 3,100
Max Fastening Torque	120 N·m (88.5 ft.lbs.)
Overall Length	229 mm (9")
Net weight	1.4 kg (3.1 lbs.)
Power supply cord	2.5 m (8.2 ft)

6905H Impact Wrench

1/2" (12.7 mm) 294 N·m (217 ft.lbs.) Impact Wrench



415

Continuous rating Input	470W
Fastening Capacities	Standard Bolt: M12 - M20 (1/2 - 3/4")
	High Strength Bolt: M12 - M16 (1/2 - 5/8")
Square Drive	12.7 mm (1/2")
No Load Speed (RPM)	2,200
Impacts Per Minute (IPM)	2,600
Max Fastening Torque	294 N·m (217 ft.lbs.)
Dimensions (L x W x H)	275 x 86 x 197 mm (10-7/8 x 3-3/8 x 7-3/4")
Net weight	2.4 kg (5.2 lbs.)
Power supply cord	2.5 m (8.2 ft)

6906 Impact Wrench

3/4" (19 mm) 588 N·m (441 ft.lbs.) Impact Wrench



100

Continuous rating Input	850W
Capacity	Standard Bolt: M16 - M22 (5/8 - 7/8")
	High Strength Bolt: M16 - M20 (5/8 - 3/4")
Square Drive	19 mm (3/4")
No Load Speed (RPM)	1,700
Impacts Per Minute (IPM)	1,600
Max Fastening Torque	588 N·m (441 ft.lbs.)
Overall Length	327 mm (12-7/8")
Net weight	5.6 kg (12.2 lbs.)
Power supply cord	2.5 m (8.2 ft)

TW0200 Impact Wrench

1/2" (12.7 mm) 200 N·m (150 ft.lbs.) Impact Wrench



411

Continuous rating Input	380W
Fastening Capacities	Standard Bolt: M10 - M16 (3/8 - 5/8")
	High Strength Bolt: M10 - M12 (3/8 - 1/2")
Square Drive	12.7 mm (1/2")
No Load Speed (RPM)	0 - 2,200
Impacts Per Minute (IPM)	0 - 2,200
Max Fastening Torque	200 N·m (150 ft.lbs.)
Dimensions (L x W x H)	251 x 72 x 220 mm
	(9-7/8 x 2-13/16 x 8-5/8")
Net weight	2.1 kg (4.7 lbs.)
Power supply cord	2.5 m (8.2 ft)

TW0350 Impact Wrench

1/2" (12.7 mm) 350 N·m (260 ft.lbs.) Impact Wrench



411

Continuous rating Input	400W
Fastening Capacities	Standard Bolt: M12 - M22 (1/2 - 7/8")
	High Strength Bolt: M12 - M16 (1/2 - 5/8")
Square Drive	12.7 mm (1/2")
No Load Speed (RPM)	2,000
Impacts Per Minute (IPM)	2,000
Max Fastening Torque	350 N·m (260 ft.lbs.)
Dimensions (L x W x H)	283 x 87 x 233 mm
	(11-1/8 x 3-7/16 x 9-1/8")
Net weight	3 kg (6.6 lbs.)
Power supply cord	2.5 m (8.2 ft)

TW1000 Impact Wrench

1" (25.4 mm) 1,000 N·m (738 ft.lbs.) Impact Wrench



153

Continuous rating Input	1,200W
Fastening Capacities	Standard Bolt: M24 - M30 (15/16 - 1-3/16")
	High Strength Bolt: M22 - M24 (7/8 - 15/16")
Square Drive	25.4 mm (1")
No Load Speed (RPM)	1,400
Impacts Per Minute (IPM)	1,500
Max Fastening Torque	1,000 N·m (738 ft.lbs.)
Dimensions (L x W x H)	382 x 110 x 290 mm (15 x 4-5/16 x 11-3/8")
Net weight	8.8 kg (19.4 lbs.)
Power supply cord	2.5 m (8.2 ft)