MAKITA POWER TOOLS
เครื่องมือไฟฟ้า “มากีต้า”

มากีต้า

M4000B Blower 530W

In-line grip for higher maneuverability



Continuous Rating Input	530W
Air Volume	1.2-2.9 m3/min
No Load Speed (RPM)	8,500 - 16,000
Sound Power Level	101 dB(A)
Dimensions	427x161x212 mm
(L x W x H)	(16-3/4"x6-3/8"x8-3/8")
Net Weight	1.5 kg (3.4 lbs)
Power Supply Cord	2.0 m (6.6 ft)

M4001B Blower 600W

600 W Variable Speed Blower



Continuous Rating Input	600W
Max Air Volume	0 - 4.1 m3/min
Max Air Velocity	0 - 91 m/s
Air Pressure	0 - 5.7 kPa
No Load Speed (RPM)	0 - 16,000
Sound Power Level	93 dB(A)
Dimensions	480x185x178 mm
(L x W x H)	(18-7/8"x7-1/4"x7")
Net Weight	1.9 - 2.0 kg (4.3 - 4.5 lbs)
Power Supply Cord	2.0 m (6.6 ft.)

M4100B 110mm (4-3/8") Cutter 1,200W

Redesigned base with grooved back surface for smoother operation



Continuous Rating Input	1,200W
Blade Diameter	110 mm (4-3/8")
Max Cutting Capacity	90°: 32 mm (1-1/4")
No Load Speed (RPM)	13,000
Sound Power Level	111 dB(A)
Dimensions	227x209x166 mm
(L x W x H)	(8-15/16"x8-1/4"x6-1/2")
Net Weight	2.9 kg (6.4 lbs)
Power Supply Cord	2.0 m (6.6 ft.)

M4101B 125 mm (5") 1,250 W Cutter 1,250W

Redesigned base with grooved back surface for smoother operation



Continuous rating input	1,250W
Blade Diameter	125 mm (5")
Max Cutting Capacity	90°: 40 mm (1-9/16")
No Load Speed (RPM)	12,000
Vibration Level	Concrete Cutting: 5.0 m/s2
Sound Pressure Level	98 dB(A)
Sound Power Level	109 dB(A)
Dimensions	233x216x166 mm
(L x W x H)	(9-1/8"x8-1/2"x6-1/2")
Net weight	3.0 kg (6.7 lbs.)
Power supply cord	2.0 m (6.6 ft.)

M4301B Jig Saw 450W

450 W Top Handle Jig Saw, 3 Orbital Settings Plus Straight Cutting



Continuous rating input	450W
Max Cutting Capacity at 90°	Wood: 65 mm (2-9/16")
	Steel: 6 mm (1/4")
Length of Stroke	18 mm (11/16")
Strokes Per Minute (SPM)	0 - 3,100
Vibration Level	Cutting Wood: 8.0 m/s2
	Cutting Sheet Metal: 5.0 m/s2
Sound Pressure Level	82 dB(A)
Sound Power Level	93 dB(A)
Dimensions	214x75x202 mm
(L x W x H)	(8-3/8"x2-15/16"x8")
Net weight	1.9 kg (4.1 lbs)
Power supply cord	2.0 m (6.6 ft)

M4302B Jig Saw 450W

450 W Top Handle Variable Speed Jig Saw



Continuous rating input	450W
Max Cutting Capacity at 90°	Wood: 55 mm (2-3/16")
	Steel: 6 mm (1/4")
Length of Stroke	26 mm (1")
Strokes Per Minute (SPM)	0 - 3,100
Vibration Level	Cutting Boards: 6.5 m/s2
	Cutting Sheet Metal: 7.5 m/s2
Sound Pressure Level	88 dB(A)
Sound Power Level	99 dB(A)
Dimensions	219x85x191 mm
(L x W x H)	(8-5/8"x3-3/8"x7-1/2")
Net weight	2.5 kg (5.5 lbs.)
Power supply cord	2.0 m (6.6 ft.)

M4501KB Recipro Saw 1,010W

Toolless blade clamp



Continuous rating input	1,010W
Length of Stroke	28 mm
Strokes Per Minute (s/min)	0 - 2,800
Capacity	Pipe : 130 mm
	Wood: 255 mm
Vibration Level	Cutting Boards: 19.5 m/s2
Vibration K factor	Cutting Boards: 1.5 m/s2
Vibration Level	Cutting Wooden beams: 22.0 m/s2
Vibration K factor	Cutting Wooden beams: 2.0 m/s2
Sound Pressure Level	87 dB(A)
Sound Power Level	98 dB(A)
Noise K factor	3 dB(A)
Dimensions (L x W x H)	457x98x170mm
Net weight	3.2 kg
Power supply cord	2.0 m

M5801B 185mm (7-1/4") Circular Saw 1,050W

Well-balanced and Lightweight for superior handling and performance



Continuous Rating Input	1,050W
Blade Diameter	185 mm (7-1/4")
Max Cutting Capacity	90°: 66 mm (2-5/8")
	45°: 44 mm (1-3/4")
No Load Speed (RPM)	4,900
Dimensions	284x231x243 mm
(L x W x H)	(11-1/8"x9-1/8"x9-9/16")
Net Weight	3.5 kg (7.7 lbs)
Power Supply Cord	2.0 m (6.6 ft.)

M5802B 190 mm / 185 mm 1,050W Circular Saw 1,050W



Continuous rating input	1,050W
Blade Diameter	190 / 185 mm
Max Cutting Capacity	at 90°: 68 / 66 mm
	at 45°: 46 / 44 mm
No Load Speed (r/min)	4,900
Vibration K factor	Cutting Wood: 1.5 m/s2
Sound Pressure Level	85 dB(A)
Sound Power Level	96 dB(A)
Noise K factor	3 dB(A)
Overall Length	297 mm
Net weight	4.0 kg
Power supply cord	2.0 m

M0600B 10mm (3/8") Drill 350W

Powerful 350 W motor for continuous operation



Continuous Rating Input	350W
Capacity	Steel: 10 mm (3/8")
No Load Speed (RPM)	Wood: 20 mm (13/16") 0 - 3,000
Sound Pressure Level	77 dB(A)
Dimensions	230x66x176 mm
(L x W x H)	(9"x2-5/8"x6-15/16")
Net Weight	1.2 kg (2.6 lbs)
Power Supply Cord	2.0 m (6.6 ft)

M0801B 16mm (5/8") Hammer Drill 500W

High performance and durability at less expense



Continuous Rating Input	500W
Capacity	Concrete: 16 mm (5/8")
	Steel: 13 mm (1/2")
	Wood: 20 mm (13/16")
Blows Per Minute (BPM)	0 - 48,000
No Load Speed (RPM)	0 - 3,200
Sound Pressure Level	94 dB(A)
Sound Power Level	105 dB(A)
Dimensions	261x69x195 mm
(L x W x H)	(10-1/4"x2-3/4"x7-5/8")
Net Weight	1.7 kg (3.7 lbs)
Power Supply Cord	2.0 m (6.6 ft)

M0801KX3B 16mm (5/8") Hammer Drill 500W

High performance and durability at less expense



Continuous Rating Input	500W
Capacity	Concrete: 16 mm (5/8")
	Steel: 13 mm (1/2")
	Wood: 20 mm (13/16")
Blows Per Minute (BPM)	0 - 48,000
No Load Speed (RPM)	0 - 3,200
Sound Pressure Level	94 dB(A)
Sound Power Level	105 dB(A)
Dimensions	261x69x195 mm
(L x W x H)	(10-1/4"x2-3/4"x7-5/8")
Net Weight	1.7 kg (3.7 lbs)
Power Supply Cord	2.0 m (6.6 ft)