MAKITA POWER TOOLS
เครื่องมือไฟฟ้า “มากีต้า”

มากีต้า

6922NB Shear Wrench

M16 (5/8") / M20 (3/4") / M22 (7/8") 804 N·m (593 ft.lbs.) Shear Wrench



411

Continuous rating Input	1,330W
No Load Speed (RPM)	18
Max Fastening Torque	804 N·m (593 ft.lbs.)
Dimensions (L x W x H)	249 x 84 x 252 mm (9-13/16 x 3-5/16 x 9-15/16")
Net weight	4.9 kg (10.8 lbs.)
Power supply cord	2.5 m (8.2 ft)

6924N Shear Wrench

M22 (7/8") / M24 (1") / SHTB22 1,100 N·m (810 ft.lbs.) Shear Wrench



303

Continuous rating Input	1,050W
Capacity	Super high tensile bolt: M22
No Load Speed (RPM)	19
Max Fastening Torque	1,100 N·m (810 ft.lbs.)
Dimensions (L x W x H)	330 x 104 x 257 mm (13 x 4-1/8 x 10-1/8")
Net weight	7.5 kg (16.6 lbs.)
Power supply cord	2.5 m (8.2 ft)

UT1305 Mixer

165 mm (6-1/2") 850 W Mixer



303

Continuous rating Input	850W
Blade Diameter	165 mm (6-1/2")
No Load Speed (RPM)	1,300
Dimensions (L x W x H)	942 x 87 x 152 mm (37 x 3-7/16 x 6")
Net weight	2.6 kg (5.7 lbs.)
Power supply cord	2.5 m (8.2 ft)

UT2204 Mixer

220 mm (8-5/8") 850 W Mixer



303

Continuous rating Input	850W
Blade Diameter	220 mm (8-5/8")
No Load Speed (RPM)	550
Dimensions (L x W x H)	929 x 89 x 152 mm (36-1/2 x 3-1/2 x 6")
Net weight	2.7 kg (5.9 lbs.)
Power supply cord	2.5 m (8.2 ft)

JN1601 Nibbler

1.6 mm (16 Ga) Nibbler



411

Continuous rating Input	550W
Capacity	Steel up to 400 N/mm²: 1.6 mm Steel up to 600 N/mm²: 1.2 mm Steel up to 800 N/mm²: 0.8 mm Aluminum up to 200 N/mm²: 2.5 mm
Min. cutting radius	Outside edge: 50 mm (2") Inside edge: 45 mm (1-3/4")
Strokes Per Minute (SPM)	2,200
Overall Length	261 mm (10-1/4")
Net weight	1.6 kg (3.6 lbs.)
Power supply cord	2.0 m (6.6 ft)

JN3201 Nibbler

3.2 mm (10 Ga) Nibbler



303

Continuous rating Input	710W
Capacity	Steel up to 400 N/mm²: 3.2 mm Steel up to 600 N/mm²: 2.5 mm Steel up to 800 N/mm²: 1.0 mm Aluminum up to 200 N/mm²: 3.5 mm
Min. cutting radius	Outside edge: 128 mm (5-1/16") Inside edge: 120 mm (4-3/4")
Strokes Per Minute (SPM)	1,300
Dimensions(L x W x H)	225 x 90 x 254 mm (8-7/8 x -1/2 x 10")
Net weight	3.4 kg (7.4 lbs.)
Power supply cord	2.5 m (8.2 ft)

JS3201 Metal Shear

3.2 mm (10 Ga) Metal Shear



303

Continuous rating Input	710W
Capacity	Steel up to 400 N/mm²: 3.2 mm Steel up to 600 N/mm²: 2.5 mm Steel up to 800 N/mm²: 1.5 mm Aluminum up to 200 N/mm²: 4.0 mm
Min. cutting radius	50 mm (2")
Strokes Per Minute (SPM)	1,600
Dimensions (L x W x H)	213 x 90 x 239 mm (8-3/8 x 3-1/2 x 9-3/8")
Net weight	3.4 kg (7.5 lbs.)
Power supply cord	2.5 m (8.2 ft)

JS1000 Metal Shear

1.0 mm (20 Ga) Metal Shear



459

Continuous rating Input	380W
Capacity	Steel up to 400 N/mm²: 1.0 mm Steel up to 600 N/mm²: 0.7 mm Steel up to 800 N/mm²: 0.5 mm Aluminum up to 200 N/mm²: 2.5 mm
Min. cutting radius	30 mm (1-3/16")
Strokes Per Minute (SPM)	4,500
Dimensions (L x W x H)	322 x 70 x 78 mm (12-5/8 x 2-3/4 x 3-1/16")
Net weight	1.4 kg (3.2 lbs.)
Power supply cord	2.5 m (8.2 ft)

JS1602 Metal Shear

1.6 mm (16 Ga) Metal Shear



459

Continuous rating Input	380W
Capacity	Steel up to 400 N/mm²: 1.6 mm Steel up to 600 N/mm²: 1.2 mm Steel up to 800 N/mm²: 0.8 mm Aluminum up to 200 N/mm²: 2.5 mm
Min. cutting radius	30 mm (1-3/16")
Strokes Per Minute (SPM)	4,000
Dimensions (L x W x H)	255 x 74 x 146 mm (10 x 2-15/16 x 5-3/4")
Net weight	1.6 kg (3.4 lbs.)
Power supply cord	2.5 m (8.2 ft)

JS1601 Straight Metal Shear

1.6 mm (16 Ga) Straight Metal Shear



459

Continuous rating Input	380W
Capacity	Steel up to 400 N/mm²: 1.6 mm Steel up to 600 N/mm²: 1.2 mm Steel up to 800 N/mm²: 0.8 mm Aluminum up to 200 N/mm²: 2.5 mm
Min. cutting radius	250 mm (9-7/8")
Strokes Per Minute (SPM)	4,500
Dimensions (L x W x H)	320 x 70 x 78 mm (12-5/8 x 2-3/4 x 3-1/16")
Net weight	1.4 kg (3.2 lbs.)
Power supply cord	2.5 m (8.2 ft)

JR1000FT Recipro Saw

340 W Recipro Saw



419

Continuous rating Input	340W
Length of Stroke	14 mm (9/16")
Strokes Per Minute (SPM)	0 - 4,800
Capacity	Pipe: 25.4 mm (1") Wood: 55 mm (2-3/16")
Dimensions (L x W x H)	345 x 65 x 96 mm (13-5/8 x 2-9/16 x 3-3/4")
Net weight	1.6 kg (3.5 lbs.)
Power supply cord	2.5 m (8.2 ft)

JR3051T Recipro Saw

1,200 W Recipro Saw



303

Continuous rating Input	1,200W
Length of Stroke	30 mm (1-3/16")
Strokes Per Minute (SPM)	0 - 3,000
Capacity	Pipe: 130 mm (5-1/8") Wood: 255 mm (10")
Dimensions (L x W x H)	447 x 97 x 176 mm (17-5/8 x 3-13/16 x 6-15/16")
Net weight	3.2 - 3.3 kg (7.1 - 7.3 lbs.)
Power supply cord	2.5 m (8.2 ft)