








BIM-Tech IGBT Module



Synergic MIG


Dust-Free Air Passage Design


Smart Gas


On-demand Fan



Fast Wire Feeding

ฟังก์ชั่นพิเศษ

SMART GAS

ปรับเวลาการไหลของแก๊สหลังการเชื่อมอัตโนมัติ MIG/MAG/TIG ตามกระแสเชื่อมและเวลาเชื่อมจริง ประหยัดโดยรวม **40%**

Synergic MMA/MIG

ปรับกระแสเชื่อมอัตโนมัติ ตามขนาดของลวดเชื่อม





- โหมดเชื่อม (MIG/MMA/LIFT-TIG (ทิกเขี่ย))
- ทิกเขี่ย เชื่อมง่ายไม่สะดุด
- ได้รับสิทธิบัตรการออกแบบ BIM-Tech IGBT เพื่อเพิ่มความน่าเชื่อถือ
- Dust Free การออกแบบช่องระบายอากาศ พร้อมความสามารถในการป้องกันฝุ่น และการกระจายความร้อนดีเยี่ยม
- พัดลมจะทำงานเมื่อเริ่มใช้งาน ประหยัดพลังงาน ลดเสียงรบกวน มีระบบกันฝุ่นที่ประสิทธิภาพสูง ดูดซับฝุ่นน้อย ยืดอายุการใช้งาน

เชื่อมโลหะได้ทุกชนิด

เหล็ก สเตนเลส อลูมิเนียม ทองแดง

MIG200 N214II **MIG270** N248II

อุปกรณ์มาตรฐาน

1. **PANA200**
   สายเชื่อม MIG 3 m
2. **สายดิน 3 m**
   300A 25 mm²
3. เหล็กรัดท่อ
4. สายแก๊ส
5. CONTACT TIP

		MIG200 N214II	MIG270 N248II
Input	Input voltage (V)	1ph AC220 ±15%	3ph AC380 ±15%
	Rated input power capacity (kVA)	7.7	10.6
	Power factor	0.75	0.85
Output	Rated no-load voltage (V)	56	62
MIG	Welding current (A)	50~200	50~270
	Welding voltage (V)	13~26	13~32
	Regulator heater voltage (V)	36 (AC)	36 (AC)
	Wire feeding range(m/min)	2~24	2~24
Lift TIG	Welding current(A)	50~200	50~270
	Arc starting	contact arc ignition	contact arc ignition
MMA	Welding current(A)	50~160	50~220
Others	Rated duty cycle @ 40°C	30%	30%
	Efficiency	81%	80%
	Protection class	IP21S	IP21S
	Insulation class	H	H
	Dimensions (mm)	597*298*503	597*298*503
	Weight (kg)	22.6	23.6