CUT

Mesh Cutting

Plasma Gouging

BIM-Tech IGBT Module

Dust-Free Air Passage Design

On-demand Fan

ฟังก์ชั่นพิเศษ

2T/4T

2T คือ การตัดทั่วไป
โดยการกดสวิตช์ค้างไว้

4T คือ การตัดต่อเนื่อง
แบบอัตโนมัติเพียง
กดสวิตช์ เปิด/ปิด

Energy-saving

ประหยัดพลังงานลม เสียงเงียบ
ยืดอายุการใช้งาน



- สามารถใช้งานกับเครื่อง CNC ในอุตสาหกรรมได้
- รองรับการตัดตาข่าย
- รองรับการตัดแบบเซาะร่อง
- สามารถทำงานได้ในสภาวะแรงดันไฟที่ต่ำกว่าได้ถึง 3 เฟส 323V
- สามารถปรับการหน่วงของลมได้ ช่วยให้วัสดุสิ้นเปลืองของหัวตัดมีอายุการใช้งานยาวนานขึ้น
- พัดลมจะทำงานเมื่อเริ่มใช้งาน ประหยัดพลังงาน ลดเสียงรบกวน มีระบบกันฝุ่นที่ประสิทธิภาพสูง ดูดซับฝุ่นน้อย ยืดอายุการใช้งาน

3ph



CUT100 L221II

3ph



CUT80 L225II

ออฟชั่นเสริม

- สามารถตัดแบบเซาะร่อง หัวทิพเซาะร่อง 2.5 mm (เฉพาะ CUT100L221 J072-10078649)



อุปกรณ์มาตรฐาน

1. **สายตัดพลาสม่า P80** ด้ามตัดพร้อมสาย 5 m
2. **สายดิน 3 m** 300A 16 mm²
3. เหล็กรัดท่อ
4. สายแก๊ส
5. P80 ทิพ
6. P80 อิเลคโทรด

		CUT80 L225II	CUT100 L221II
Input	Input voltage (V)	3ph AC380 ±15%	3ph AC380 ±15%
	Rated input power capacity (kVA)	15	20
	Power factor	≥0.70	≥0.70
Output	Rated no-load voltage (V)	300	320
	Cutting current (A)	20~80	20~100
Others	Clean cut thickness (mm) @ speed: 400 mm/min	20	25
	Severance cut thickness (mm)	35	40
	Arc starting	HF arc ignition	HF arc ignition
	Rated duty cycle @ 40°C	30%	50%
	Efficiency	≥85%	≥85%
	Protection class	IP21S	IP21S
	Insulation class	H	H
	Dimensions (mm)	549.5*219*414	636.5*255*457
	Weight (kg)	20	25