

AS-90 WELDERS ANTI-SPATTER SPRAY

AS-90 is a practical and affordable 3-in-1 solvent based welders' fluid: anti-spatter, wire feed lubricant, and post-weld corrosion inhibitor.

Anti-Spatter: A light spray applied before welding to areas subject to weld spatter, will prevent build-up on the metal surface. It dramatically reduces time spent scraping, sanding, and chipping during clean up.

Wire Feed Lubricant: Lubricates new or rusty welding wire creating a smooth feed to the welding torch.

Post Weld Anti-Corrosion: When sprayed on welded joints and parent metal, it provides a protective surface coating which minimises flash rusting.

Does not contain silicone, will not interfere with subsequent painting.

The advanced formulation uses non-flammable CO_2 propellant.

KEY FEATURES

- 3-in-1 welders fluid: anti-spatter, wire feed lubricant and post-weld corrosion inhibitor
- Non-flammable CO_2 propellant
- Easy "wipe off" removal
- Does not contain silicone
- Highly economical in use

NEVER ASK A PROFESSIONAL TO USE ANYTHING ELSE!

MARKET SECTORS:

FASTENERS & FIXINGS
INDUSTRIAL MRO
AGRICULTURE

CODE	FILL SIZE/PRODUCT
1843	400g aerosol (CO_2)

APPLICATION AREAS

Prevents spatter adhesion to equipment and surfaces. Use on resistance welding tips, Mig and Tig tips, weldments, electrode holders, contact tips, tools, metal moulds and bench top splash guards. Also works as an effective wire lubricant and anti-corrosion treatment.

DIRECTIONS FOR USE

- Shake can before use.
- Apply to the welding wire and to the surfaces to be welded together, avoiding the join.
- After welding, brush off spatter.
- For corrosion protection, reapply after welding by spraying over the parts to be protected.
- Repeated application prolongs the protection period.
- For best results let the solvent evaporate before handling.
- AS-90 should be removed with TF-90 solvent cleaner before painting/ galvanising.
- Avoid contact with plastics, rubbers and painted surfaces.

Action Can,
Wylds Road, Bridgwater,
Somerset, TA6 4DD, England

Phone: +44 (0)1942 713667
Fax: +44 (0)1942 716235
Email: sales@actioncan.com

TECHNICAL DATA

ACTION CAN®

APPEARANCE:	Pale amber liquid
ODOUR:	Sweet ethereal
SPECIFIC GRAVITY AT 20˚C:	1.295
SOLUBILITY:	Insoluble in water
FLASH POINT:	Non-flammable

(All values apply to product without aerosol propellant)

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) is available from https://www.actioncan.com/product/as-90/ or from info@actioncan.com

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 72 months with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

MISREPRESENTATION ACT 1967 & TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

TECHNICAL SERVICE

CRC Industries UK Ltd provides a technical support service and maintains a constant programme of research and development. Should you have a technically complex enquiry, please email us for specialist/laboratory support.

Action Can,
Wylds Road, Bridgwater,
Somerset, TA6 4DD, England
Registered in England & Wales: 4910479

Phone: +44 (0)1942 713667
Fax: +44 (0)1942 716235
Email: sales@actioncan.com

WWW.ACTIONCAN.COM

Version Number: 2.0 Date of Issue: 16/01/2019 Date of Update: 16/01/2019