


Idler Sprockets


● Order Product Code
ID 40C 15 D15

TYPE No. No. of Teeth
Sprocket No. D



<KANA Idler Sprocket Features>

- 1. Double snap rings used
(No.25C is a one-sided snap ring specification)
(Can be easily extracted or pressed in without damaging the bearings, convenient for plating or other surface processing.)
- 2. Snap rings used that do not interfere with stepped shaft



m Carbon Structural Steel
h No. 35C ~ 80C

High-frequency Hardened Teeth
(Only No. 25C is without High-frequency Hardened Teeth)

TYPE	No.	No. of Teeth	D	Do	Dp	T	BD	BL	Bearing No.	Weight kg
ID	25C	17	6	38	34.558	2.8	27	12	606ZZ	0.05
		19	8	42	38.580		31	13	608ZZ	0.05
		20	10	44	40.592				6900ZZ	0.06
			12	44	40.592		33	13	6901ZZ	0.08
	35C	16	10	54	48.824	4.3	38	14	6000ZZ	0.11
			12	54	48.824				6001ZZ	0.10
		18	15	60	54.852		44	17	6202ZZ	0.16
		21	17	69	63.908		53	19	6203ZZ	0.24
		25	20	81	75.997		60	21	6204ZZ	0.33
	40C	13	10	59	53.068	7.2	38	14	6000ZZ	0.15
			12	59	53.068				6001ZZ	0.14
		15	15	67	61.084		44	17	6202ZZ	0.19
		17	17	76	69.116		53	19	6203ZZ	0.30
	50C		20	84	77.159	8.7	60	21	6204ZZ	0.40
		12	12	69	61.336		43	16	6201ZZ	0.21
		13	15	74	66.335		44	17	6202ZZ	0.23
		15	17	84	76.355		53	19	6203ZZ	0.37
	60C	17	20	94	86.395	11.7	60	21	6204ZZ	0.49
		11	12	76	67.617		44	16	6201ZZ	0.26
			15	76	67.617			17	6202ZZ	0.27
		13	17	89	79.602		53	19	6203ZZ	0.46
	80C	14	20	95	85.610		60	21	6204ZZ	0.56
		9	15	85	74.265	14.6	44	17	6202ZZ	0.38
		10	17	93	82.196		52	19	6203ZZ	0.57
		11	20	102	90.156		60	21	6204ZZ	0.69



* The bearing is located in the center of the sprocket.

Caution