



NK35-2B

Standard Sprocket Two-row B-type

Order Product Code

NK35-2B 15

TYPE No. of Teeth
Sprocket No.



Use together with the KANA machine key. Refer to P.334 to P.335

- ChainNo.35-2
- Chain Pitch(P) 9.525 mm
- Bushing Link Inner Width(W) 4.78 mm
- Bushing Outside Diameter(Dr) 5.08 mm
- Tooth Width(T) 4.1 mm
- Complete Tooth Width(M) 14.2 mm

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d			BD	BL	Shape	Tooth Section	Weight kg
				Prepared Hole	Minimum	Maximum					
NK35-2B	10	35	30.824	10	11	12	20	30	Ground Specification	 Carbon Structural Steel  High-frequency Hardened Teeth	0.10
	11	38	33.809	10	11	12	23	30			0.11
	12	41	36.802	10	11	14	26	30			0.14
	13	44	39.801	10	11	14	27	30			0.17
	14	47	42.805	10	11	18	32	30			0.21
	15	51	45.813	10	11	20	35	30			0.25
	16	54	48.824	10	11	20	38	30			0.29
	17	57	51.837	10	11	22	41	30			0.34
	18	60	54.852	10	11	25	44	35			0.45
	19	63	57.869	10	11	28	47	35			0.51
	20	66	60.888	12	13	30	50	40			0.64
	21	69	63.908	12	13	30	50	40			0.64
	22	72	66.929	12	13	32	55	40			0.67
	24	78	72.974	15	16	38	60	40			0.82
	25	81	75.997	15	16	38	60	40			0.92
	28	90	85.072	15	16	42	65	45			1.26
	30	96	91.124	15	16	42	65	45			1.34
	32	102	97.177	15	16	42	65	45			1.43
	40	127	121.401	15	16	42	65	45			2.30
	45	142	136.546	19	20	55	83	45			2.84
	50	157	151.695	19	20	55	83	45			3.22
	60	187	181.997	19	20	63	93	50			4.70