


SUS50B

SUS Stainless Steel Sprocket B-type


Order Product Code

SUS50B 20

TYPE No. of Teeth
Sprocket No.



- Chain **No.50**
- Chain Pitch **(P) 15.875mm**
- Roller Link Inner Width ... **(W) 9.53 mm**
- Roller Outside Diameter ... **(Dr) 10.16 mm**
- Tooth Width **(T) 8.7 mm**



Use together with the KANA machine key. Refer to P.334 to P.335

m Stainless Steel **GB** 304

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d			BD	BL	Shape	Weight kg
				Prepared Hole	Minimum	Maximum				
SUS50B	10	58	51.373	10	11	22	★40	25	Ground Specification	0.27
	11	64	56.348	12	13	28	★45.5	25		0.33
	12	69	61.336	12	13	30	★50	25		0.41
	13	74	66.335	12	13	32	★51	25		0.46
	14	79	71.342	12	13	32	52	25		0.52
	15	84	76.355	12	13	35	57	25		0.62
	16	89	81.373	14	15	40	62	25		0.72
	17	94	86.395	14	15	45	67	25		0.83
	18	100	91.420	14	15	48	72	28		1.00
	19	105	96.449	14	15	48	73	28		1.10
	20	110	101.480	14	15	48	73	28		1.20
	21	115	106.513	14	15	48	73	28		1.20
	22	120	111.548	16	17	48	73	28		1.30
	23	125	116.585	16	17	48	73	28		1.30
	24	130	121.623	16	17	48	73	28		1.40
	25	135	126.662	16	17	48	73	28		1.50
	26	140	131.703	16	17	48	73	28		1.50
	27	145	136.744	16	17	48	73	28		1.50
	28	150	141.786	16	17	48	73	28		1.60
	30	161	151.873	16	17	48	73	28		1.80
	32	171	161.961	16	17	48	73	28	Welded Specification	1.90
	34	181	172.052	16	17	48	73	28		2.10
	35	186	177.099	16	17	48	73	28		2.20
	36	191	182.145	19	20	55	83	35		2.85
	38	201	192.239	19	20	55	83	35		3.05
	40	211	202.335	19	20	55	83	35		3.25

! Sprockets with a ★ symbol for BD have a channel in the boss exterior.

No. of Teeth	S	GD
10	6.4	34
11		39
12	6.4	44
13		49



Caution

*Because teeth number 36 to 40 are being shifted from welding specification to grinding specification, the inventory is currently mixed.