


HG60A

Order Product Code

HG60A 20H

TYPE No. of Teeth
Sprocket No.



- Chain **No.60**
- Chain Pitch **(P) 19.05 mm**
- Roller Link Inner Width **(W) 12.70 mm**
- Roller Outside Diameter **(Dr) 11.91 mm**
- Tooth Width **(T) 11.7 mm**

m Carbon Structural Steel
h High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
HG60A	10H	70	61.647	14	15	0.27
	11H	76	67.617	14	15	0.30
	12H	83	73.604	14	15	0.38
	13H	89	79.602	14	15	0.45
	14H	95	85.610	16	17	0.50
	15H	101	91.625	16	17	0.60
	16H	107	97.647	16	17	0.65
	17H	113	103.674	16	17	0.75
	18H	119	109.705	16	17	0.84
	19H	126	115.739	16	17	0.93
	20H	132	121.776	16	17	1.05
	21H	138	127.816	16	17	1.15
	22H	144	133.858	16	17	1.25
	23H	150	139.902	16	17	1.40
	24H	156	145.948	18	19	1.50
	25H	162	151.995	18	19	1.62
	26H	168	158.043	18	19	1.78
	27H	174	164.093	18	19	1.90
	28H	180	170.143	18	19	2.05
	29H	187	176.195	18	19	2.20
	30H	193	182.247	18	19	2.35
	32H	205	194.354	20	21	2.68
	34H	217	206.463	20	21	3.02
	35H	223	212.518	20	21	3.25
	36H	229	218.574	20	21	3.40

HG High-grade Sprocket with Hardened Teeth A-type

m Carbon Structural Steel
h High-frequency Hardened Teeth

TYPE	No. of Teeth	Do	Dp	Shaft Hole Diameter d		Weight kg
				Prepared Hole	Minimum	
HG60A	38H	241	230.687	20	21	3.80
	39H	247	236.744	20	21	4.00
	40H	253	242.802	20	21	4.20
	42H	266	254.917	20	21	4.63
	44H	278	267.034	20	21	5.10
	45H	284	273.093	20	21	5.30
	46H	290	279.152	20	21	5.59
	47H	296	285.211	20	21	5.83
	48H	302	291.270	20	21	6.10
	49H	308	297.330	20	21	6.34
	50H	314	303.390	20	21	6.60
	52H	326	315.510	20	21	7.15
	54H	338	327.630	20	21	7.70
	55H	345	333.691	20	21	8.00
	60H	375	363.994	20	21	9.50
	65H	405	394.301	26	27	11.20
	70H	436	424.609	26	27	13.00
	75H	466	454.918	26	27	14.90