KOBE

CE

# Product Datasheet

## GA1211L 115mm (4½") Air Angle Grinder

KOBE RED LINE professional air tool offering a high standard and superb value combined with the design elements of a modern industrial classic.

### Features and Benefits:

- Compact lightweight design, well suited to working in confined spaces
- 3-in-1 tool suitable for cutting, grinding and sanding
- Front exhaust for user comfort and clearance of dust
- Safety release throttle prevents accidental start-ups
- Fully adjustable safety guard that locks into position
- Supplied with auxiliary side handle, flanges and spanners




### Typical Applications:

- For use on grinding, sanding, polishing and deburring applications
- Ideal for cleaning, Smoothing welds seams and castings

### Specifications:

| | | | |
|---|---|---|---|
| Order Code | **KBE2702060Q** | Minimum Hose Size | 3/8" (10mm) |
| Max. Disc Size | 115 x 7 x 22 mm | Sound Pressure Level | 89 dBA |
| Free Speed | 11,000 rpm | Sound Power Level | 96 dBA |
| Spindle Size | 3/8" - 24 | Vibration Level | 4.0 $m/s^2$ |
| Recommended Air Pressure | 6.2 bar (90psi) | Vibration uncertainty k | 2.4 $m/s^2$ |
| Air Consumption | 6 cfm (170 L/min) | Overall Length | 223 mm |
| Air Inlet Thread | ¼" NPT | Weight | 1.8Kg |

### Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)
- EN ISO 11148-7:2012 / Hand-held non-electric power tools - Safety requirements Part 7: Grinders (ISO 11148-7:2012)
- EN ISO 28927-1:2009 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 1: Angle and vertical grinders (ISO 28927-1:2009)
- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT
©Copyright 2020 – The Kennedy Group Ltd