Product Datasheet

FSR375 - 3/8" Composite Air Speed Ratchet

KOBE GREEN LINE professional air tool ergonomically designed with operator friendly features for improved comfort throughout longer periods of use

Features and Benefits:

- 3/8” reversable hardened steel square drive
- Rubber handle provides grip and operator comfort with reduced hand chill
- Three planetary gears for longer tool life and smoother running
- Rubber cover protects the ratchet head and the workpiece
- Short body length allows access into hard to reach areas
- Low profile teasing throttle for precise speed control
- Rotating rear exhaust with baffle to reduce noise
- Rotating air inlet to prevent the air hose tangling
- Adjustable air regulator



Typical Applications:

- Suitable for the removal and installation of threaded fasteners during automotive and light assembly work
- General maintenance applications

Specifications:

Order Code	**KBE2702360K**	Sound Pressure Level	84 dBA
Square Drive	3/8”	Sound Power Level	88 dBA
Free Speed	200 rpm	Vibration Level	1.8 m/s^2
Working Torque Range	7-41 Nm (5-30 ft-lb)	Vibration Uncertainty K	1.08 m/s^2
Recommended Air Pressure	6.2 bar (90psi)	Overall Length	205 mm
Air Consumption	4.0 cfm (113 L/min)	Weight	0.64 kg
Air Inlet Thread	¼” NPT		
Minimum Hose Size	3/8” (10mm)		

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design
  Risk assessment and risk reduction (ISO 12100:2010)

- EN ISO 11148-9:2011 / Hand-held non-electric power tools - Safety requirements
  Part 6: Assembly power tools for threaded fasteners (ISO 11148-6:2010)

- EN ISO 28927-2:2009 / Hand-held portable power tools - Test methods for evaluation of vibration emission
  Part 2: Wrenches, nut runners and screwdrivers (ISO 28927-2:2009)

- EN ISO 15744:2008 / Hand-held non-electric power tools
  Noise measurement code - Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT
©Copyright 2020 – The Kennedy Group Ltd