# Product Datasheet

## SR375 3/8” Air Ratchet Wrench

KOBE RED LINE professional air tool offering a high standard and superb value combined with the design elements of a modern industrial classic.




### Features and Benefits:

- 3/8” drive
- Ball type retainer
- Compact lightweight design for ease of use
- Disc type reversing action
- Front exhaust for user comfort and clearance of dust

### Typical Applications:

- Suitable for the removal and installation of threaded fasteners during automotive and light assembly work
- General maintenance applications

### Specifications:

| | | | |
|---|---|---|---|
| Order Code | **KBE2702375K** | Sound Pressure Level | 95.88 dBA |
| Drive Size | 3/8” | Sound Power Level | |
| Free Speed | 200 rpm | Vibration Level | 11.33 m/s² |
| Recommended Air Pressure | 6.2 bar (90psi) | Vibration Level Uncertainty K | 1.385 m/s² |
| Air Consumption | 4 cfm (113 L/min) | Overall Length | 255 mm |
| Air Inlet Thread | ¼” NPT | Weight | 1.1 Kg |
| Minimum Hose Size | 3/8” (10mm) | | |

### Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design
  Risk assessment and risk reduction (ISO 12100:2010)

- EN ISO 11148-9:2011 / Hand-held non-electric power tools - Safety requirements
  Part 6: Assembly power tools for threaded fasteners (ISO 11148-6:2010)

- EN ISO 28927-2:2009 / Hand-held portable power tools - Test methods for evaluation of vibration emission
  Part 2: Wrenches, nut runners and screwdrivers (ISO 28927-2:2009)

- EN ISO 15744:2008 / Hand-held non-electric power tools
  Noise measurement code - Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT
©Copyright 2020 – The Kennedy Group Ltd