Product Datasheet

G7321 3/8” Air Impact Wench

KOBE GREEN LINE professional air tool ergonomically designed with operator friendly features for improved comfort throughout longer periods of use



Features and Benefits:

- Twin hammer mechanism
- Maximum bolt capacity M14 (9/16”)
- One finger start/stop trigger operation
- 4 point adjustable air (speed) regulator
- Forward/reverse speed regulator
- Lightweight composite body reduces the effects of vibration and hand chill
- Downward facing external exhaust in handle

FORWARD
Position 1: 8000 rpm
Position 2: 9100 rpm
Position 3: 10,100 rpm
REVERSE
10,200 rpm

Typical Applications:

- Suitable for light workshop and garage use

Specifications:

Order Code	**KBE2705820K**	Air Inlet Thread	¼” NPT
Drive Size	3/8”	Minimum Hose Size	3/8” (10mm)
Max. Free Speed	10,200 rpm	Sound Pressure Level	88 dBA
Max. Torque (10 Sec)	393 Nm	Vibration Level	4.9 m/s²
Working Torque (5 sec)	339 Nm	Overall Length	165 mm
Recommended Air Pressure	6.2 bar (90psi)	Weight	1.3 Kg
Air Consumption	3 cfm (85 L/min)		

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)

- EN ISO 11148-9:2011 / Hand-held non-electric power tools - Safety requirements Part 6: Assembly power tools for threaded fasteners

- ISO 28927-12:2012 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 7: Wrenches, screwdrivers and nut runners with impact, impulse or ratchet action

- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT
©Copyright 2020 – The Kennedy Group Ltd