KOBE

CE

Product Datasheet

90° Air Angle grinder with Surface Conditioning / Finishing kit

Features and Benefits:

- 90° angle head for flexibility in tight areas
- Safety Lever throttle prevents accidental start-ups
- Rear exhaust directs air away from the workpiece
- Ball bearing construction for a long service life and smoother running
- Robust and durable single piece aluminium body
- Speed regulator for precise speed control
- Kit contains: 2x each preparation discs (fine, medium & coarse), 2x each abrasive discs (P36, P60, P80 & P120), 1x backing pad (30,000rpm), 1x long shank collect, 2x collet spanners. Supplied in a sturdy plastic carry case





Typical Applications:

- Multi-purpose surface conditioning and finishing kit
- Ideal for polishing, grinding and buffing

Specifications:

Order Code	**KBE2707000K**	Minimum Hose Size	3/8" (10mm)
Collet Size	6 mm	Sound Pressure Level	85 dBA
Free Speed	22,000 rpm	Sound Power Level	99 dBA
Recommended Air Pressure	6.2 bar (90psi)	Vibration Level	7.0 m/s²
Air Consumption	4 cfm (113 L/min)	Overall Length	160 mm
Air Inlet Thread	¼" NPT	Weight	0.5 Kg

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)
- EN ISO 11148-9:2011 / Hand-held non-electric power tools - Safety requirements Part 9: Die grinders (ISO 11148-9:2011)
- EN ISO 28927-12:2012 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 12: Die grinders
- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT

©Copyright 2020 – The Kennedy Group Ltd