KOBE

CE

Product Datasheet

GD2806L High Speed Mini Air Die Grinder

KOBE RED LINE professional air tool offering a high standard and superb value combined with the design elements of a modern industrial classic

Features and Benefits:

- Compact design it is well suited to working in confined spaces
- Lightweight and durable single piece aluminium body
- Safety release throttle prevents accidental start-ups
- Front exhaust blows away dust and debris
- Precision balanced bearings provide reliability in the most demanding of industrial/automotive applications
- Supplied with two collet spanners and a comprehensive instruction manual



Typical Applications:

- For use on grinding, polishing, buffing and deburring
- Ideal for cleaning, Smoothing welds seams and castings
- Maintenance applications

Specifications:

Order Code	**KBE2702035M**	Sound Pressure Level	94 dBA
Collet Size	6 mm	Sound Power Level	106 dBA
Free Speed	25,000 rpm	Vibration Level	5.0 m/s^2
Recommended Air Pressure	6.2 bar (90psi)	Vibration Uncertainty K	3.0 m/s^2
Air Consumption	4 cfm (113 L/min)	Overall Length	121 mm
Air Inlet Thread	¼" NPT	Weight	0.3Kg
Minimum Hose Size	3/8" (10mm)		

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)
- EN ISO 11148-9:2011 / Hand-held non-electric power tools - Safety requirements Part 9: Die grinders (ISO 11148-9:2011)
- EN ISO 28927-12:2012 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 12: Die grinders
- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT

©Copyright 2020 – The Kennedy Group Ltd