THE ENVIRONMENT

Always dispose of unwanted tools, accessories and packaging materials in an environmentally friendly manner.

This product does not contain any restricted substances in concentrations and applications which are banned by the European RoHS2 Directive.

DECLARATION OF CONFORMITY

We hereby certify that 1/2" REVERSIBLE PISTOL DRILL

(ORDER CODE: KBE-270-2142K)

complies with all the relevant provisions of the

EMC Electromagnetic Compatibility Directive 2006/42/EC

Standards Applied:

EN ISO 12100:2010, EN ISO 15744:2008, EN ISO 28927-5:2009, EN ISO 11148-3:2012

Date: 17th Febuary 2022

Name: Toni Johonson

Position: Compliance Director

KOBE TOOLS
Cromwell Group (Holdings) Limited.
65 Chartwell Drive, Wigston, Leicestershire,
England, LE18 2FS
Contact Us: contactus@cromwell.co.uk
Country of Origin :Taiwan

CE UKCA

QUALITY GUARANTEE & WARRANTY

KOBE INDUSTRIAL POWER TOOLS carry a one year manufacturer's warranty.

KOBE INDUSTRIAL POWER TOOLS are designed & manufactured to the highest standards & specifications

Assuring the quality and performance required by all sectors of industry.

KOBE INDUSTRIAL POWER TOOLS are fully guaranteed against faulty materials & workmanship.

Should they be found to be defective, they will either be repaired or replaced free of charge (fair wear and tear and/or misuse excepted).

Please retain supplier invoice as proof of purchase.

Cromwell Group (Holdings) Limited.
65 Chartwell Drive, Wigston, Leicestershire, England, LE18 2FS
© The Kennedy Group Ltd. 12/21

KOBE™
INDUSTRIAL AIR TOOLS

1/2" REVERSIBLE PISTOL DRILL

MODEL
FPD500

ORDER CODE
KBE-270-2142K



- Suitable for high torque drilling applications, as well as screwdriving, hole sawing and cylinder honing
- Rubber handle provides grip and operator comfort
- 500rpm
- 1/2" Jacobs™ industrial chuck
- Adjustable side handle
- Short gear case design
- Heavy duty gearing system with oiless bushing
- Spring loaded rotor vanes
- Rear exhaust
- Ball bearing construction for a long tool life

CE UKCA

OPERATOR FRIENDLY

WARNING: THE SAFETY INFORMATION GIVEN INSIDE MUST BE READ AND UNDERSTOOD BY ANY PERSON USING, INSTALLING, REPAIRING OR MAINTAINING THESE PRODUCTS.

OPERATOR'S MANUAL

Please retain this information for future reference.

SAFETY INSTRUCTIONS

You have purchased a quality industrial product that is designed for high performance and long service life. If correct use, safety and maintenance procedures are observed this machine will last for many years.

KOBE INDUSTRIAL AIR TOOLS have been specifically designed to help you work **SAFELY** and **EFFICIENTLY**. Your care and good judgement are the best protection against injury, but always ensure that the appropriate safety equipment is worn. All possible hazards cannot be covered here, but the most important ones have been highlighted.

GENERAL OPERATING HAZARDS

- Keep clear from all rotating spindles and moving parts
- Ensure that all long hair and loose clothing, ties, scarves, jewellry, etc., are secured or removed
- Always wear approved eye protection during operation, repair or maintenance of the tool, or whilst changing accessories. The operator of the tool is responsible for following accepted eye, face, respiratory, hearing and body protection.
- Ensure that all others in the area are wearing approved eye, face, respiratory, hearing and body protection. Even small projectiles can injure eyes and cause blindness.
- Wear gloves to protect hands from cuts and burns.
- Do not touch accessories during or after use.
- Never disable the safety lever throttle.
- Do not modify tools or accessories and only use for the task for which they have been designed.
- Ensure that all accessories are rated to the "Free" speed of the tool and intact before fitting or using.
- All users must be physically able and competent to handle the size, weight and power of the tools and have received appropriate training to perform the task.
- Note the tool rundown time. Control the tool as if it were under power.

SPECIFIC OPERATING HAZARDS

- Only use abrasives that are designed for the tool.
- Do not use cut off wheels or router bits in this tool.
- An abrasive fitted to a tool that is not designed for its use may cause serious injury or death.
- Make sure that insert tools have the correct shaft size for the collet.
- Protect abrasive accessories from exposure to water, solvents, high humidity, freezing temperature and extreme temperature changes.
- Store accessories in protective racks or compartments to prevent damage.
- The user is responsible for making sure that the specification label on the air tool is kept legible, indicating the model number, serial number and rpm. If not, reorder and replace.

WORKPLACE HAZARDS

- Slip/Trip/Fall is a major cause of serious injury or death. Be aware of excess hose around the work place.
- Maintain a balanced body position and secure footing.
- High sound levels can cause permanent hearing loss. Use approved hearing protection.
- Repetitive work motions, awkward positions and exposure to vibration can cause "Repetitive Strain Injuries". If numbness, tingling, pain or whitening of the skin occurs consult a doctor.
- Avoid inhaling dust or handling debris from work process which can be harmful to your health.
- This tool is not intended for use in a flammable or combustible atmosphere and is not insulated for contact with electric power sources.
- Use a vice or clamping device to hold the work piece firmly in place.

AIR SUPPLY AND CONNECTION HAZARDS

- Air under pressure can cause severe injury.
- Always shut off air supply, drain hose of air pressure and disconnect tools from air supply when not in use, before changing accessories or when making repairs.
- Never direct air at yourself or anyone else.
- Whipping hoses can cause serious injury. Always check for damaged or loose hoses and fittings.
- Do not use quick disconnect couplings at tool. See instructions for suggested air supply.
- Whenever universal twist couplings are used, lock pins must be installed.
- Do not exceed maximum air pressure of 90psi/6.2bar.
- Do not carry the tool by the air hose.

SPECIFICATIONS


MODEL NUMBER	**FPD500**	**AIR HOSE SIZE (ID)**	3/8" 10mm
FREE SPEED	500rpm	**AIR PRESSURE**	90PSI/6.2BAR
CHUCK SIZE	1/2" (13mm)	**AIR CONSUMPTION**	4CFM*
SPINDLE	3/8" - 24	**OVERALL LENGTH**	240mm
AIR INLET THREAD	1/4" NPT	**WEIGHT**	1.77 kg

*Based on 15 second cycle per minute average use.


SPARE PARTS BREAKDOWN

No.	Order Code	Description
1	KBE-298-9357S	Motor Housing
2	KBE-298-9358S	Pin (2.5x25.8)
3	KBE-298-9359S	Air Inlet
4	KBE-298-9360S	Trigger
5	KBE-298-9361S	Valve Stem Set
6	KBE-298-9362S	Reverse Bushing
7	KBE-298-9363S	Spring (4)
8	KBE-298-9364S	Valve Spring
9	KBE-298-9365S	"O" Ring (14x1)
10	KBE-298-9366S	Reverse Lever
11	KBE-298-9367S	Tapping Screw (2) (TS2.9)
12	KBE-298-9368S	Exhaust Diffuser
13	KBE-298-9369S	Ball Bearing (6001zz)
14	KBE-298-9370S	Rear Plate
15	KBE-298-9371S	Rotor (11T)
16	KBE-298-9372S	Rotor Blade (4)
17	KBE-298-9373S	Spring Pin (2.5x16)
18	KBE-298-9374S	Cylinder
19	KBE-298-9375S	Front End Plate
20	KBE-298-9376S	Ball Bearing (607zz)
21	KBE-298-9377S	Ball Bearing (609zz)
22	KBE-298-9378S	Internal Gear (2) (46T)
23	KBE-298-9379S	Planet Gear (6) (17T)
24	KBE-298-9380S	Oilless Bearing (6) (4x6x8)
25	KBE-298-9381S	Pin (6) (3.97x19.8)
26	KBE-298-9382S	Work Spindle (11T)
27	KBE-298-9383S	Work Spindle
28	KBE-298-9384S	Ball Bearing (2) (6202zz)
29	KBE-298-9385S	Washer
30	KBE-298-9386S	Screw (L M5x35L)
31	KBE-298-9387S	Washer
32	KBE-298-9388S	Clamp Nut
33	KBE-298-9389S	Industrial Key Chuck (1/2")
34	KBE-298-9390S	Washer
35	KBE-298-9391S	Retainer
36	KBE-298-9392S	Handle
37	KBE-298-9393S	Detent
38	KBE-298-9394S	Set Screw (M5x8L)
39	KBE-298-9395S	"O" Ring (13.5x1.5)
40	KBE-298-9396S	Bolt ((M6x30L)
41	KBE-298-9397S	Rubber Grip
42	KEN-988-5004K	Specification Label
	KBE-280-0128A	Chuck Key (Not Shown)

SPARE PARTS BREAKDOWN



SUGGESTED AIR SUPPLY



Connect tools to the air line using pipe, hose and fitting sizes listed in the specifications.
Supply tools with 90psi/6.2bar of clean, dry air. A higher pressure will reduce the tool life.
Requirements for Quick Acting Couplings connected to Air Tools:
A leader hose of minimum length 500mm between the tool and the coupling is required in order to comply with Health and Safety Executive Guide **HS(G) 39, BS4575:2, ISO 15744:2002 and ISO 28927-10:2011.**

LUBRICATION

Air tools require lubrication throughout the life of the tool otherwise moisture in the compressed air will rust the air motor. Correct lubrication is vital for the maximum performance of the drill and an airline lubricator should be fitted into the system down stream of the filter. Failure tolubricate the tool at the air inlet will void your warranty.

Either use an air line lubricator with air tool oil adjusted to two drops per minute, or if an air line lubricator cannot be used, add air motor oil to the inlet once a day (See fig 1). ISO Grade VG22 oil is recommended.

Any excess oil in the motor is expelled immediately from the exhaust port. Always direct the exhaust port away from people or objects.

Do not lubricate the drill with flammable or volatile liquids such as kerosene, diesel or jet fuel.




Fig. 1

OPERATION

1. Remove the plastic dust cap using a pair of pliers (See fig. 2).
2. Always disconnect the drill from the air supply before changing the bits.
3. If the support handle is used, it can be positioned to give maximum comfort to the operator (See fig. 3).
4. Use the chuck key to open and close the chuck.
5. The amount the trigger is squeezed will determine the speed of the tool.
6. Use the lever underneath the trigger to select forward (clockwise) or reverse (anti-clockwise) rotation (See fig. 4).
7. Beware of the tool running on for some time after the throttle lever is released.




Fig. 2



Fig. 3




Fig. 4

MAINTENANCE

Disassemble and inspect higher wear parts every three months if the tool is used every day and replace damaged or worn parts.

Replace as necessary all "O" rings, bearings and rotor blades, see parts break down. It is recommended that adequate stocks of standard service parts are held for servicing requirements.

The use of other than genuine Kobe replacement parts may result in safety hazards, decreased tool performance and increased maintenance.

Mineral spirits are recommended when cleaning the tool and its parts. Do not clean with any solvents or oils containing acids, esters, ketones, chlorinated hydrocarbons or nitro carbons. Do not use chemicals that have a low flash point.

For spare parts or servicing please contact your nearest agent. Remember to quote tool model number and spare part number when ordering spares.

When disposing of components, lubricants, etc. ensure that relevant environmental procedures are carried out.

NOTES