KOBE

CE

# Product Datasheet

## IW750 - 3/4" Square Drive Air Impact Wrench

3/4" heavy duty air impact wrench with a one-piece aluminium housing offering high durability and operator comfort.




### Features and Benefits:

- High-low power regulator
- Maximum bolt size: M24 (7/8”)
- One handed easy push button for forward-reverse operation
- Finger throttle lever

### Typical Applications:

- The IW750 has a is ideal for tightening/loosening of wheel bolts, truck and bus maintenance, farm machinery, and construction equipment.

### Specifications:

| | | | |
|---|---|---|---|
| Order Code | **KBE2702325S** | Air Inlet Thread | ¼” NPT |
| Drive Size | 3/4” | Minimum Hose Size | 3/8” (10mm) |
| Free Speed | 4,800 rpm | Sound Pressure Level | 86 dBA |
| Maximum Torque | 1085 Nm | Sound Power Level | |
| Working Torque | 949 Nm | Vibration Level | 5.8 m/s² |
| Recommended Air Pressure | 6.2 bar (90psi) | Overall Length | 248 mmm |
| Air Consumption | 4.2 cfm (198 L/min) | Weight | 4.6 Kg |

### Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)

- EN ISO 11148-9:2011 / Hand-held non-electric power tools - Safety requirements Part 6: Assembly power tools for threaded fasteners (ISO 11148-6:2010)

- EN ISO 28927-2:2009 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 2: Wrenches, nut runners and screwdrivers (ISO 28927-2:2009)

- EN ISO 15744:2008 / Hand-held non-electric power tools Noise measurement code - Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT
©Copyright 2020 – The Kennedy Group Ltd