Product Datasheet

NB160 High Performance Air Nibbler - Pull Type

KOBE RED LINE professional air tool offering a high standard and superb value combined with the design elements of a modern industrial classic

Features and Benefits:

- Powerful ½" HP motor
- Produces burr free cuts without distortion
- Built-in regulator matches speed to application
- Teasing throttle for precise control
- Down facing exhaust clear debris from the work area
- Forward, reverse, left and right cutting positions
- Supplied with the up cut punch and die



Typical Applications:

- Ideal for body shop and sheet metal work

Specifications:

Order Code	**KBE2703400K**	Minimum Hose Size	3/8" (10mm)
Cutting Capacity Steel	1.2mm	Sound Pressure Level	96.63 dBA
Cutting Capacity Aluminium	2 mm	Sound Power Level	107.63 dBA
Cutting Speed	2.6 MPA	Vibration Level	8.65 m/s²
Recommended Air Pressure	6.2 bar (90psi)	Vibration Level Uncertainty K	1.35 m/s²
Air Consumption	4 cfm (113 L/min)	Overall Length	180 mm
Air Inlet Thread	¼" NPT	Weight	0.98 Kg

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)

- EN ISO 11148-4:2012 / Hand-held non-electric power tools - Safety requirements Part 4: Non-rotary percussive power tools (ISO 11148-4:2012)

- EN ISO 28927-10:2011 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 7: Nibblers and shears (ISO 28927-7:2009)

- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT
©Copyright 2020 – The Kennedy Group Ltd