Product Datasheet

BS920L Multi-Purpose Air Body Saw

KOBE RED LINE professional air tool offering a high standard and superb value combined with the design elements of a modern industrial classic.

Features and Benefits:

- Safety release throttle prevents accidental start-ups
- Lightweight and easy to use
- Universal side-locking blade clamps
- Adjustable blade guide
- Burr-free cuts
- Accepts most square-ended blades including jigsaw blades, hacksaw blades and mini files up to 13mm
- Complete with hex key and two blades



Typical Applications:

- Ideal for body shop and sheet metal work
- Cuts through any sheet material, doors, sills, chassis, fibre glass, Perspex or ply

Specifications:

Order Code	**KBE2703500K**	Air Inlet Thread	¼" NPT
Strokes per Minute	9,000 spm	Minimum Hose Size	3/8" (10mm)
Stroke Length	10 mm	Sound Pressure Level	87.3 dBA
Cutting Capacity Steel	1.6 mm	Sound Power Level	100.3 dBA
Cutting Capacity Aluminium	2.0 mm	Vibration Level	25.7 m/s^2
Max. Square End Blade Size	13mm x 1 mm	Vibration Level Uncertainty K	4 m/s^2
Recommended Air Pressure	6.2 bar (90psi)	Overall Length	235 mm
Air Consumption	4 cfm (113 L/min)	Weight	0.55 Kg

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)
- EN ISO 11148-4:2012 / Hand-held non-electric power tools - Safety requirements Part 4: Non-rotary percussive power tools (ISO 11148-4:2012)
- EN ISO 28927-10:2011 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 1: Saws (ISO 28927-8:2009)
- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT
©Copyright 2020 – The Kennedy Group Ltd