Product Technical Datasheet

KRK001 Air Riveter Kit

KOBE RED LINE professional air tool offering a high standard and superb value combined with the design elements of a modern industrial classic.



Features and Benefits:

- For blind riveting.
- Adjustable Safety cap which collects ejected rivet pins.
- Suitable for both aluminium and steel rivets up to 4.8mm (3/16").
- Swivel adaptor
- Kit Contents:
  4 Packs of Rivets in sizes 2.4, 3.2, 4.0, 4.8.
  Rivet head 2.4|3.2|4.0|4.8mm plus safety cap,
  O-ring repair kit and jaw case set,
  Oil pot, swivel adaptor, springs, spanner gauge and spanner

Typical Applications:

- The ideal kit for industrial or production workplace, garage or maintenance workshop.
- Ideal for blind riveting
- Suitable for both aluminium and steel rivets





Specifications:

Order Code	**KBE2703710K**	Sound Pressure Level	76.3 dBA
Traction Power	8,629Nm (1,940lbs)	Sound Power Level	87.3 dBA
Stroke Length	14mm	Vibration Level	1.01 m/s²
Recommended Air Pressure	6.2 bar (90psi)	Vibration Level Uncertainty K	0.6 m/s²
Air Consumption	4 cfm (113 L/min)	Overall Height	270mm
Air Inlet Thread	¼" NPT	Weight	1.4 Kg
Minimum Hose Size	3/8" (10mm)		

Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)

- EN ISO 11148-1:2011 / Hand-held non-electric power tools - Safety requirements Part 1: Assembly power tools for non-threaded mechanical fasteners (ISO 11148-1:2011)

- EN ISO 20643:2008+A1:2012 / Mechanical vibration - Hand-held and hand-guided machinery Principles for evaluation of vibration emission (ISO 20643:2005)

- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT
©Copyright 2020 – The Kennedy Group Ltd