# Product Datasheet

## CSP005s – Automatic Shut-off Air Screwdriver 0.6 - 5.1 Nm

KOBE BLUE LINE professional air tool with a higher specification offering maximum user comfort and durability - designed for extensive periods of heavy duty use in a production environment

### Features and Benefits:

- Push to start type with auto shut-off clutch for precision applications
- 3 interchangeable torque springs allow for easy conversion for new applications
- External torque adjustment does not require disassembly of the tool
- Variable speed throttle
- Soft ergonomic grip for operator comfort
- Forward / reverse control on top for easy access
- Handle exhaust directs air away from the workpiece and operator
- Hanging ring included



### Typical Applications:

- Heavy duty reverse action pistol grip screwdriver suitable for production assembly applications

### Specifications:

| | | | |
|---|---|---|---|
| Order Code | **KBE2703760K** | Sound Pressure Level | 84 dBA |
| Hex Drive Capacity | ¼" | Sound Power Level | 93 dBA |
| Free Speed | 600 rpm | Vibration Level | 0.5 m/s² |
| Recommended Air Pressure | 6.2 bar (90psi) | Vibration Level Uncertainty K | 0.3m/s² |
| Air Consumption | 4 cfm (113 L/min) | Overall Length | 235 mm |
| Air Inlet Thread | ¼" NPT | Weight | 0.8 Kg |
| Minimum Hose Size | 3/8" (10mm) | | |

### Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)

- EN ISO 11148-4:2012 / Hand-held non-electric power tools - Safety requirements Part 6: Assembly power tools for threaded fasteners (ISO 11148-6:2010)

- EN ISO 28927-10:2011 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 2: Wrenches, nut runners and screwdrivers (ISO 28927-2:2009)

- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT
©Copyright 2020 – The Kennedy Group Ltd