KOBE

CE

# Product Datasheet

## SS1525K Stainless Steel ¼" Straight Air Screwdriver Kit

KOBE RED LINE professional air tool offering a high standard and superb value combined with the design elements of a modern industrial classic.



### Features and Benefits:

- Adjustable clutch
- Fingertip control of reverse action with lock
- ¼" hex bit size
- Ball retainer mechanism for easy bit change
- Rear exhaust directs away from the work area
- Kit contains:

SS1525s Air Screwdriver, 3 Clutch springs
No.1 Crosspoint double ended bit 65mm
5mm slotted bit 50mm
2x spanners, Clutch adjusting hex wrench
¼" NPT nipple, Mini oil bottle
Robust moulded case



### Typical Applications:

- Ideal tool for general maintenance applications, assembly and refurbishing

### Specifications:

| | | | |
|---|---|---|---|
| Order Code | **KBE2703800K** | Minimum Hose Size | 3/8" (10mm) |
| Free Speed | 1,500 rpm | Sound Pressure Level | 77 dBA |
| Capacity | ¼" Hex | Sound Power Level | 89 dBA |
| Torque Range | 0.3 – 0.7 Nm | Vibration Level | 1.0 m/s² |
| Recommended Air Pressure | 6.2 bar (90psi) | Vibration Level Uncertainty K | 0.6 m/s² |
| Air Consumption | 4 cfm (113 L/min) | Overall Length | 220 mm |
| Air Inlet Thread | ¼" NPT | Weight | 0.6 Kg |

### Standards:

- EN ISO 12100:2010 / Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100:2010)
- EN ISO 11148-4:2012 / Hand-held non-electric power tools - Safety requirements Part 6: Assembly power tools for threaded fasteners (ISO 11148-6:2010)
- EN ISO 28927-10:2011 / Hand-held portable power tools - Test methods for evaluation of vibration emission Part 2: Wrenches, nut runners and screwdrivers (ISO 28927-2:2009)
- EN ISO 15744:2008 / Hand-held non-electric power tools - Noise measurement code Engineering method (grade 2) (ISO 15744:2002)

Cromwell
P.O. Box 14, Wigston, Leicester, England LE18 1AT

©Copyright 2020 – The Kennedy Group Ltd