KENNEDY®

DATA SHEET

QUALITY INDUSTRIAL TOOLING

SDS Hammer Drill Bits

High performance drill bits that withstand extreme heat generation ensuring maximum performance coupled with wear resistance.



- Material: Tungsten carbide-tipped
- Flute construction: Ground flute
- Shank type: SDS
- Suitable for all SDS direct fitting hammer drills
- Manufactured to DIN 8035

Drill Diam. (mm)	Overall Length (mm)	Order Code
5	110	KEN-057-1000K
5	160	KEN-057-1020K
5.5	110	KEN-057-1200K
5.5	160	KEN-057-1220K
6	110	KEN-057-1400K
6	160	KEN-057-1420K
6	210	KEN-057-1440K
6.5	110	KEN-057-1600K
6.5	160	KEN-057-1620K
7	110	KEN-057-1800K
7	160	KEN-057-1820K
8	110	KEN-057-2000K
8	160	KEN-057-2020K
8	210	KEN-057-2040K
8	260	KEN-057-2080K
8	400	KEN-057-2120K
9	210	KEN-057-2240K
10	110	KEN-057-2400K
10	160	KEN-057-2420K
10	210	KEN-057-2440K
10	260	KEN-057-2480K
10	360	KEN-057-2520K
10	460	KEN-057-2540K
11	160	KEN-057-2620K
11	300	KEN-057-2680K
12	166	KEN-057-2820K
12	216	KEN-057-2840K
12	316	KEN-057-2900K
12	466	KEN-057-2940K
12	600	KEN-057-2980K

© Copyright 2021 - Kennedy Tools

SDS Hammer Drill Bits

- Material: Tungsten carbide-tipped
- Flute construction: Ground flute
- Shank type: SDS
- Suitable for all SDS direct fitting hammer drills
- Manufactured to DIN 8035



Drill Diam. (mm)	Overall Length (mm)	Order Code
13	166	KEN-057-3020K
13	210	KEN-057-3040K
13	466	KEN-057-3140K
14	166	KEN-057-3220K
14	216	KEN-057-3240K
14	266	KEN-057-3280K
14	316	KEN-057-3300K
14	466	KEN-057-3340K
14	600	KEN-057-3380K
15	166	KEN-057-3420K
15	266	KEN-057-3480K
15	450	KEN-057-3540K
16	250	KEN-057-3640K
16	300	KEN-057-3700K
16	450	KEN-057-3740K
16	600	KEN-057-3760K
18	250	KEN-057-4040K
15	450	KEN-057-4140K
20	200	KEN-057-4440K
20	300	KEN-057-4500K
20	450	KEN-057-4540K
22	250	KEN-057-4680K
22	450	KEN-057-4740K
24	250	KEN-057-4880K
24	450	KEN-057-4940K
25	250	KEN-057-5080K
25	450	KEN-057-5140K
26	250	KEN-057-5280K
26	450	KEN-057-5340K

© Copyright 2021 - Kennedy Tools