Solid Carbide Jobber Drills - Metric

For drilling steels, cast steels, cast iron, chilled cast iron, malleable cast iron, non-ferrous heavy and light metal and abrasive plastic.

- Uncoated
- Material grade: Micrograin
- Helix type: Normal
- Ground flute
- Flute type: Spiral
- Number of flutes: 2
- Point type: Standard
- Point angle: 118°
- Helix angle: 30°
- Shank diameter tolerance: H6
- Drill diameter tolerance: H7
- Coolant delivery: External
- Cutting direction: Right hand
- BS 328
- DIN 338



Diameter. (mm)	Flute Length (mm)	Overall Length (mm)	Order Code
1	12	34	KEN-158-0100K
1.5	18	40	KEN-158-0150K
1.6	20	43	KEN-158-0160K
2	24	49	KEN-158-0200K
2.5	30	57	KEN-158-0250K
3	33	61	KEN-158-0300K
3.3	36	65	KEN-158-0330K
3.5	39	70	KEN-158-0350K
4	43	75	KEN-158-0400K
4.2	43	75	KEN-158-0420K
4.5	47	80	KEN-158-0450K
5	52	86	KEN-158-0500K
5.5	57	93	KEN-158-0550K
6	57	93	KEN-158-0600K
6.5	63	101	KEN-158-0650K
6.8	69	109	KEN-158-0680K
7	69	109	KEN-158-0700K
7.5	69	109	KEN-158-0750K
8	75	117	KEN-158-0800K
8.5	75	117	KEN-158-0850K
9	81	125	KEN-158-0900K
9.5	81	125	KEN-158-0950K
10	87	133	KEN-158-1000K
11	94	142	KEN-158-1100K
11.5	94	142	KEN-158-1150K
12	101	151	KEN-158-1200K

© Copyright 2021 - Kennedy Tools