KENNEDY®

DATA SHEET

QUALITY INDUSTRIAL TOOLING

Carbide Shank Milling Cutters - Regular Series - Metric

For optimum performance and maximum swarf removal when plunging, slotting and routing in light alloys, brass, aluminium, non-ferrous and other soft materials.

- Uncoated
- Material grade: Micrograin
- Shank type: Plain round
- Flute type: Helical
- Number of flutes: 2
- Helix angle: 30°
- Plunge type: Centre cutting
- Cutting direction: Right hand
- Metric tolerance for dia. over 1mm up to 6mm: +0.000, -0.050
- Metric tolerance for dia. over 6mm up to 25mm: +0.000, -0.080.mm
- Shank diameter tolerance: H6
- Cutter diameter tolerance: H10
- USCTI Standards



Diameter. (mm)	Shank Dia. (mm)	Flute Length (mm)	Overall Length (mm)	Order Code
1	4	3	40	KEN-161-0020K
1.5	4	4	40	KEN-161-0030K
2	2	8	32	KEN-161-0040K
2.5	2.5	8	32	KEN-161-0050K
3	3	12	32	KEN-161-0060K
3.5	3.5	12	32	KEN-161-0070K
4	4	12	40	KEN-161-0080K
5	5	14	50	KEN-161-0100K
6	6	16	50	KEN-161-0120K
8	8	20	60	KEN-161-0160K
9	9	20	60	KEN-161-0180K
10	10	22	70	KEN-161-0200K
11	11.0	22.0	70.0	KEN-161-0220K
12	12	22	70	KEN-161-0240K
16	16	25	75	KEN-161-0320K
18	18	25	75	KEN-161-0360K
20	20	32	100	KEN-161-0400K

© Copyright 2021 - Kennedy Tools