KENNEDY®

DATA SHEET

QUALITY INDUSTRIAL TOOLING

Carbide Burrs - Cylindrical Plain End

- Uncoated
- Suitable for deburring and polishing of cast iron, cast steel, carbon steel, alloy steel and stainless steel up to HRC65 hardness
- Not suitable for milling large amounts of material
- Ideal for light stock removal at high rpms



Rapid cut (Cut 3):

For use on aluminium, fibreglass, plastics, hard rubber and zinc alloy

Chipbreaker (Cut 9):

For use on cast iron, carbon steel, alloy steel 50RC and 60RC

Please note:

Workpiece and tools should always be steady and well supported.
Always ensure that at least 70% of the shank length is clamped by the collet or chuck of the tool being used. Always ensure that the tool is rated to the recommended operating speed of the burr.

Head Dia. (mm)	Head Length (mm)	Cut Type	Overall Length (mm)	Shank Dia. (mm)	Order Code
3	14	Chipbreaker	3	40	KEN-210-0580K
6	12	Chipbreaker	3	40	KEN-210-0620K
6	18	Rapid Cut	6	50	KEN-210-0640K
6	18	Chipbreaker	6	50	KEN-210-0660K
8	20	Chipbreaker	6	65	KEN-210-0700K
10	20	Rapid Cut	6	65	KEN-210-0720K
10	20	Chipbreaker	6	65	KEN-210-0740K
12	20	Chipbreaker	6	65	KEN-210-0780K
12	25	Rapid Cut	6	70	KEN-210-0840K
16	25	Chipbreaker	6	70	KEN-210-0900K
19	25	Rapid Cut	6	70	KEN-210-0980K

© Copyright 2021 - Kennedy Tools